

## AXIS P3214-VE Network Camera

Streamlined and versatile varifocal with HDTV 720p

AXIS P3214-VE is a streamlined, outdoor-ready fixed dome with HDTV 720p video quality and up to 1.3 MP resolution. It features a varifocal lens, P-Iris control and day/night functionality. P-Iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning, and day and night functionality provide superb image quality both in daylight and dark conditions. AXIS P3214-VE provides multiple, individually configurable H.264 and Motion JPEG video streams. With a built-in memory card slot, the camera enables local storage of video. The IK10-rated AXIS P3214-VE is dust-resistant and vandal-resistant.

- > [HDTV 720p and H.264](#)
- > [Day/night functionality](#)
- > [Remote zoom and focus](#)
- > [P-Iris control](#)
- > [IK10 vandal-resistant](#)



# AXIS P3214-VE Network Camera

Camera		Data streaming	Event data
<b>Image sensor</b>	Progressive scan RGB CMOS 1/2.8"	<b>Built-in installation aids</b>	Remote zoom, Remote focus, Pixel counter
<b>Lens</b>	Varifocal, 2.8-10 mm, F1.6 Horizontal angle of view: 92°-33° Vertical angle of view: 49°-20° Remote focus and zoom, P-Iris control, IR corrected	<b>General</b>	
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Casing</b>	Aluminum inner camera module with encapsulated electronics IP66- and NEMA 4X-rated, IK10 impact-resistant, polycarbonate casing with dehumidifying membrane PVC free Color: White NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
<b>Minimum illumination</b>	Color: 0.3 lux, F1.6 B/W: 0.06 lux, F1.6	<b>Memory</b>	256 MB RAM, 128 MB Flash
<b>Shutter time</b>	1/33500 s to 2 s	<b>Power</b>	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 8.4 W, Typical 3.5 W
<b>Camera angle adjustment</b>	Pan ±180°, Tilt 90°, Rotation ±95°	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE
<b>Video</b>		<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and Baseline Profile Motion JPEG	<b>Operating conditions</b>	-30 °C to 50 °C (-22 °F to 122 °F) Humidity 10 to 100% RH (condensing)
<b>Resolutions</b>	1280x960 to 160x90	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Frame rate</b>	Up to 25/30 fps with power line frequency 50/60 Hz in all resolutions	<b>Approvals</b>	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, EN 50121-4, IEC 62236-4, FCC Part 15 Subpart B Class A+B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22, KCC KN22 Class B, KN24, IEC/EN/UL 60950-22, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27 Class 4M4, IEC 60068-2-14, IEC 60068-2-78 Class 4K3, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth, VBR/MBR H.264	<b>Weight</b>	790 g (1.7 lb)
<b>Multi-view streaming</b>	2 individually cropped out view areas	<b>Dimensions</b>	101 x 149 x 149 mm (4.0 x 5.9 x 5.9 in)
<b>Image settings</b>	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control (including automatic gain control), Exposure zones, Backlight compensation, Fine tuning of behavior at low light, WDR - Dynamic Contrast, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	<b>Included accessories</b>	Installation Guide, Windows decoder 1-user license, Mounting bracket, Cable gasket, Resistorx T20 L-key, Drill template Weather shield
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Optional accessories</b>	AXIS T90B Illuminators AXIS ACI Conduit Bracket A AXIS T94T01D Pendant Kit including weather shield AXIS T94M01L Recessed Mount AXIS T94T01S Mounting Bracket AXIS T91 Mounts AXIS T98A17-VE Surveillance Cabinet
<b>Network</b>		<b>Video management software</b>	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	<b>Languages</b>	German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>System integration</b>		<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="http://www.openssl.org">www.openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:eyay@cryptsoft.com">eyay@cryptsoft.com</a>).</p>	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>	<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	
<b>Analytics</b>	Video motion detection, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>		
<b>Event triggers</b>	Analytics, Edge storage events		
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS, TCP and SNMP trap Video recording to edge storage Pre- and post-alarm video buffering Send video clip Overlay text		