

Lund, May 17, 2011

Axis introduces high-performance indoor PTZ dome camera with 35x zoom and extended D1 resolution

Axis Communications today introduces an indoor pan/tilt/zoom dome camera with 35x zoom, wider picture with extended D1 resolution and outstanding mechanical performance. AXIS Q6032 PTZ Dome Network Camera, which has an IP52-rated protection against dust and dripping water, enables easy and reliable installation and is ideal for use in airports, train stations, shopping malls and conference centers.

“AXIS Q6032 provides high video quality, fast and robust pan/tilt capability for wide area coverage, and a powerful zoom that enables facial identification some 150 m (490 ft.) away,” says Erik Frännlid, Axis’ Director of Product Management. “With AXIS Q6032, we are also the first to introduce an extended D1 resolution.”

AXIS Q6032 offers a wider picture with an extended D1 resolution of 752x480 pixels in 60 Hz and 736x576 pixels in 50 Hz, enabling an increase of roughly 15,400 and 9,200 pixels, respectively, over standard D1 resolution, which has a pixel width of only 720 pixels.

The PTZ dome camera provides 35x optical and 12x digital zoom with autofocus. It enables continuous 360° pan at a speed of 0.05° to 450° per second and a tilt range of 180°. A new tour recording functionality enables easy set-up of automatic guard tour operations by enabling an operator’s pan/tilt/zoom movements, including the length of time spent between positions, to be recorded and replayed at a touch of a button or at a scheduled time.

The camera’s day and night functionality allows high image quality to be maintained even in low light conditions, while support for wide dynamic range enables objects in both dark and light areas of a scene to be visible. AXIS Q6032 can deliver multiple H.264 and Motion JPEG video streams simultaneously. H.264 optimizes bandwidth and storage use without compromising image quality.

The camera supports High Power over Ethernet (IEEE 802.3at), which simplifies installation since only one cable is required for power, video and PTZ controls. A High PoE midspan is supplied with the camera.

AXIS Q6032 features the Active Gatekeeper functionality, which enables the camera to automatically move to a preset position when motion is detected in a pre-defined area and then track the detected object. The camera supports two-way audio and audio detection, and inputs/outputs for connection to devices such as sensors and relays. The camera’s SD/SDHC slot enables recordings to be stored locally.

AXIS Q6032 is supported by AXIS Camera Station and the industry's largest base of application software through Axis's partner programs. The camera will be available to order in June 2011. For photos and other resources, please visit http://www.axis.com/corporate/press/press_material.htm?key=q6032.

About Axis

Axis is an IT company offering network video solutions for professional installations. The company is the global market leader in network video, driving the ongoing shift from analog to digital video surveillance. Axis products and solutions focus on security surveillance and remote monitoring, and are based on innovative, open technology platforms.

Axis is a Swedish-based company, operating worldwide with offices in more than 20 countries and cooperating with partners in more than 70 countries. Founded in 1984, Axis is listed on the NASDAQ OMX Nordic, under the ticker AXIS. For more information about Axis, please visit our website at www.axis.com

For further information about Axis Communications, please contact:

*Lena Hedén, PR Marketing Manager, Axis Communications, Axis Communications
Phone: + 46 46 272 1800, E-mail: pressoffice@axis.com*