

## AXIS Q6075-SE PTZ Camera

Outdoor-ready, stainless steel PTZ with HDTV 1080p and 40x zoom

AXIS Q6075-SE PTZ Camera offers great overviews and excellent details. It comes with autotracking 2, as well as an orientation aid for active object tracking and quick orientation. With Axis Lightfinder 2.0 the camera delivers low-light images with more saturated colors and sharper images of moving objects. Plus, the included TPM module ensures highest network security. Furthermore, Zipstream with H.264/ H.265 significantly lowers bandwidth and storage requirements. The media converter enables daisy chain installation using standard network or fiber optic cables.

- > [Marine-grade stainless steel casing](#)
- > [HDTV 1080p and 40x optical zoom](#)
- > [SFP slots for fiber, RJ45 connections](#)
- > [I/O for alarm in/out](#)
- > [Built-in analytics](#)



# AXIS Q6075-SE PTZ Camera

## Variants

AXIS Q6075-SE 50 Hz  
AXIS Q6075-SE 60 Hz

## Camera

### Image sensor

1/2.8" progressive scan CMOS

### Lens

4.25–170 mm, F1.6–4.95  
Horizontal field of view: 65.1°–2.00° (1080p)  
Vertical field of view: 39.1°–1.18° (1080p)  
Autofocus, auto-iris

### Day and night

Automatically removable infrared-cut filter

### Minimum illumination

Color: 0.1 lux at 30 IRE, F1.6  
B/W: 0.002 lux at 30 IRE, F1.6  
Color: 0.15 lux at 50 IRE, F1.6  
B/W: 0.003 lux at 50 IRE, F1.6

### Shutter speed

1/11000 s to 1/3 s with 50 Hz  
1/11000 s to 1/3 s with 60 Hz

### Pan/Tilt/Zoom

Pan: 360° endless, 0.05°–450°/s  
Tilt: 220°, 0.05°–450°/s  
Zoom: 40x optical, 12x digital, total 480x zoom  
E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, focus recall

## System on chip (SoC)

### Model

ARTPEC-7

### Memory

1024 MB RAM, 512 MB Flash

### Compute capabilities

Machine learning processing unit (MLPU)

## Video

### Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles  
H.265 (MPEG-H Part 2/HEVC) Main Profile  
Motion JPEG

### Resolution

HDTV 1080p 1920x1080 to 320x180

### Frame rate

Up to 50/60 fps (50/60 Hz) in HDTV 1080p

### Video streaming

Multiple, individually configurable streams in H.264, H.265 and Motion JPEG  
Axis Zipstream technology in H.264 and H.265  
Controllable frame rate and bandwidth  
VBR/ABR/MBR H.264/H.265

### Image settings

Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, polygon privacy masks, electronic image stabilization (EIS), freeze on PTZ, automatic defog, backlight compensation, scene profiles  
Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation

## Network

### Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS<sup>1</sup>, TLS<sup>1</sup>, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP<sup>®</sup>, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, PTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

1. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

## System integration

### Application Programming Interface

Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at [axis.com](http://axis.com)

One-Click Cloud Connection

ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specification at [onvif.org](http://onvif.org)

### Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at [axis.com/vms](http://axis.com/vms).

### Event conditions

Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature  
Edge storage: recording ongoing, storage disruption  
I/O: digital input, manual trigger, virtual input  
MQTT subscribe

PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready

Scheduled and recurring: scheduled event

Video: live stream open

### Event actions

Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap

PTZ: PTZ preset, start/stop guard tour

File upload via FTP, SFTP, HTTP, HTTPS network share and email

Notification via email, HTTP, HTTPS and TCP

MQTT publish

### Built-in installation aids

Pixel counter, leveling guide

## Analytics

### Applications

#### Included

AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, autotracking 2, active gatekeeper

Basic analytics (not to be compared with third-party analytics): object removed, enter/exit detector, object counter

#### Supported

Support for AXIS Camera Application Platform enabling installation of third-party applications, see [axis.com/acap](http://axis.com/acap)

### AXIS Object Analytics

Object classes: humans, vehicles

Scenarios: line crossing, object in area, crossline counting, time in area

Up to 10 scenarios

Other features: triggered objects visualized with trajectories, color-coded bounding boxes and tables  
Polygon include/exclude areas

Perspective configuration

ONVIF Motion Alarm event

### AXIS Scene Metadata

Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates

Object attributes: confidence, position

## Approvals

### EMC

EN 50121-4, IEC 62236-4, EN 55024,

EN 55032 Class A, EN 55035, EN 61000-3-2,

EN 61000-3-3, EN 61000-6-1, EN 61000-6-2

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KCC KN32 Class A, KN35

USA: FCC Part 15 Subpart B Class A

### Safety

IEC/EN/UL 60950-1, IS 13252

IEC/EN/UL 60950-22, IEC/EN/UL 62368-1

### Environment

IEC/EN 60529 IP66/IP67, IEC 60068-2-1,

IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14,

IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10,

NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9),

MIL-STD 810G (Method 509)

## Network

NIST SP500-267

---

## Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS 140

---

Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR

## Cybersecurity

### Edge security

**Software:** Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, Axis Cryptographic Module (FIPS 140-2 level 1), AES-XTS-Plain64 256bit SD card encryption  
**Hardware:** Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), secure keystore, secure boot

---

### Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)<sup>2</sup>, IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS<sup>2</sup>, TLS v1.2/v1.3<sup>2</sup>, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

---

### Documentation

*AXIS OS Hardening Guide*

*Axis Vulnerability Management Policy*

*Axis Security Development Model*

AXIS OS Software Bill of Material (SBOM)

To download documents, go to [axis.com/support/cybersecurity/resources](https://axis.com/support/cybersecurity/resources)

To read more about Axis cybersecurity support, go to [axis.com/cybersecurity](https://axis.com/cybersecurity)

---

## General

### Casing

IP66-, IP67-, NEMA 4X- and IK10-rated  
Stainless steel casing (V4A, SAE 316L/UNS S31603/EN 1.4404), nylon clear dome

---

### Sustainability

PVC free

---

### Power

Camera consumption: Max 65 W  
PSU: 24 V DC +/- 0.5 V, min 3.2 A (75 W)

---

## Connectors

IP68-rated multiconnector for DC power, Ethernet 10BASE-T/100BASE-TX and I/O

---

## Storage

Support for SD/SDHC/SDXC card

Support for SD card encryption

Support for recording to network-attached storage (NAS)

For SD card and NAS recommendations see [axis.com](https://axis.com)

---

## Operating conditions

-30 °C to 50 °C (-22 °F to 122 °F)

Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)

Humidity 10–100% RH (condensing)

---

## Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Humidity 5–95% RH (non-condensing)

---

## Weight

6.0 kg ( 13 lb)

---

## Dimensions

Ø224 x 256 mm (Ø8.82 x 10.1 in)

---

## Included accessories

AXIS T8607 Media Converter Switch, 7 m (23 ft) IP68-rated multicable

Installation Guide, Windows decoder 1-user license

---

## Optional accessories

AXIS T8008 Power Supply, AXIS T94A02D Pendant Kit,

AXIS T91F67 Pole Mount<sup>3</sup>, AXIS Q60-S Smoked Dome,

AXIS T8415 Wireless Installation Tool, AXIS T90

Illuminators, AXIS T8310 Video Surveillance Control

Board, multi-user decoder license pack

---

## Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

---

## Warranty

5-year warranty, see [axis.com/warranty](https://axis.com/warranty)

---

2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](https://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

3. Requires AXIS T91K61 Wall Mount

## AXIS T8607 Media Converter Switch

### General

#### Casing

Metal

Color: White NCS S 1002-B

#### Power

24 V DC, max 4 W (power supply not included)

#### Connectors

2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP) CAT5 or higher.)

2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP to copper modules

1x power

2x configurable alarm input/output ports

Camera multicable

#### Display and indicators

Power LED indicator

Camera network LED indicator

Network LED indicator (4x)

#### Compliance

RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756

#### Mounting

DIN Rail mount

#### Environment

Indoor/Cabinet

#### Operating conditions

-40 °C to 75 °C (-40 °F to 167 °F)

Humidity 10-85% RH (non-condensing)

#### Storage conditions

-40 °C to 75 °C (-40 °F to 167 °F)

Humidity 10-85% RH (non-condensing)

#### Approvals

EMC

EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15

Subpart B Class A, ICES-003 Class A, VCCI Class A,

RCM AS/NZS CISPR 22, KCC KN22 Class A, KN24

Safety

IEC/EN 60950-1

#### Dimensions

150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in)

#### Weight

284 g (0.63 lb)

#### Included accessories

Bracket Mount DIN Clip

#### Warranty

3-year warranty, see [axis.com/warranty](https://axis.com/warranty)