

## AXIS D2110-VE Security Radar

Reliable area protection with 180° coverage 24/7

AXIS D2110-VE Security Radar is a smart network-based security device that uses advanced radar technology to deliver wide 180° coverage. Thanks to built-in analytics developed using machine learning and deep learning, it can accurately detect, classify and track people and vehicles with a low false alarm rate. Featuring PoE-out it's easy to connect and power an additional device, such as a camera for visual verification or a network horn speaker for deterrence. Furthermore, smart coexistence functionality allows the use of multiple radars close to each other. For instance, it's possible to mount two radars back-to-back for complete 360° coverage.

- > **Extensive 180° area coverage**
- > **Built-in analytics**
- > **Low false alarm rate 24/7**
- > **Smart coexistence functionality**
- > **PoE-out to power additional devices**



# AXIS D2110-VE Security Radar

|                                   |  |
|-----------------------------------|--|
| <b>Radar</b>                      |  |
| Settings                          | Area Monitoring Profile<br>Road Monitoring Profile   |
| Sensor                            | Phased array FMCW (Frequency Modulated Continuous Wave)  |
| Object data                       | Range, direction, velocity, object type  |
| Frequency                         | 24.05–24.25 GHz  |
| RF transmit power                 | <100 mW (EIRP)<br>License free. Unharmful radio-waves.   |
| Recommended mounting height       | 3.5 m (11 ft) <sup>a</sup>   |
| Detection range                   | Area Monitoring Profile: 3–60 m (10–200 ft) when detecting a person<br>3–85 m (10–280 ft) when detecting a vehicle<br>Road Monitoring Profile: 30–60 m (98–197 ft) at 105 km/h (65 mph)<br>Check the user manual for the recommended positioning   |
| Radial speed                      | Area Monitoring Profile: up to 55 km/h (34 mph)<br>Road Monitoring Profile: up to 105 km/h (65 mph)  |
| Field of detection                | Horizontal: 180°   |
| Speed accuracy                    | +/- 2 km/h (1.25 mph)  |
| Distance accuracy                 | 0.7 m (2.3 ft)   |
| Angle accuracy                    | 1°   |
| Spatial differentiation           | 3 m <sup>b</sup>   |
| Data refresh rate                 | 10 Hz  |
| Coverage                          | 5600 m <sup>2</sup> (61000 sq ft) for persons<br>11300 m <sup>2</sup> (122000 sq ft) for vehicles  |
| Object classification             | Humans, vehicles, unknown  |
| Radar controls                    | Multiple detection zones, crossline detections, and exclude zones with filters for short-lived objects, object speed, and object type. Radar transmission on/off, coexistence, reference map with rotation and cropping, grid opacity, zone opacity, color scheme, trail lifetime, detection sensitivity, swaying object filter  |
| <b>System on chip (SoC)</b>       |  |
| Model                             | ARTPEC-7   |
| Memory                            | 1024 MB RAM, 512 MB Flash  |
| <b>Video</b>                      |  |
| Video compression                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>H.265 (MPEG-H Part 2/HEVC) Main Profile<br>Motion JPEG  |
| Resolution                        | 1920x1080 HDTV 1080p to 640x360  |
| Frame rate                        | Up to 10 fps in all resolutions  |
| Video streaming                   | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG<br>Controllable frame rate and bandwidth<br>VBR/ABR/MBR H.264/H.265  |
| Image settings                    | Compression, rotation: 0°, 90°, 180°, 270° including corridor format, dynamic text and image overlay   |
| <b>Audio</b>                      |  |
| Audio streaming                   | Audio output via edge-to-edge technology   |
| Audio input/output                | Network speaker pairing  |
| <b>Network</b>                    |  |
| Security                          | Password protection, IP address filtering, HTTPS <sup>c</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>c</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware   |
| Supported protocols               | IPv4/v6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS <sup>c</sup> , TLS <sup>c</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)  |
| <b>System integration</b>         |  |
| Application Programming Interface | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a><br>One-click cloud connection<br>ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>  |
| Analytics                         | Radar Motion Detection (detect, track, and classify objects), Radar autotracking<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>   |
| Event conditions                  | Analytics, object data, supervised external input, edge storage events, time scheduled<br>Radar data failure<br>Casing open, shock detected<br>MQTT subscribe  |
| Event actions                     | File upload: FTP, SFTP, HTTP, HTTPS, network share and email<br>Notification: email, HTTP, HTTPS and TCP<br>External output activation, relay activation<br>MQTT publish<br>Video recording to edge storage<br>Pre- and post-alarm video buffering<br>Overlay text<br>Status LED activation<br>Send SNMP trap  |
| Data streaming                    | Event data<br>Analytics<br>data with object GPS <sup>d</sup> position and velocity   |
| Built-in installation aids        | Reference map calibration, sensor for tilt angle, GPS position <sup>d</sup>  |
| <b>General</b>                    |  |
| Casing                            | IP66-, NEMA 4X- and IK08-rated<br>Aluminum and plastic casing<br>Color: White NCS S 1002-B   |
| Sustainability                    | PVC free   |
| Power                             | Power over Ethernet (PoE) IEEE 802.3at, Type 2 Class 4, typical 11 W, max 15 W<br>Power over Ethernet (PoE) IEEE 802.3bt, Type 3 Class 5 or Axis Midspan 60 W required for PoE Out<br>8–28 V DC, typical 10 W, max 15 W  |
| Connectors                        | DC input<br>RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE<br>RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE output to power an external PoE device<br>Relay: 2-pin terminal block<br>I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs  |
| Relays                            | 1x 1 form A, 1 NO, max 5A, 24 V DC<br>Expected lifetime 25,000 operations  |
| Storage                           | Support for microSD/microSDHC/microSDXC card<br>Support for SD card encryption (AES-XTS-Plain64 256bit)<br>Recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>   |
| Operating conditions              | -40 °C to 60 °C (-40 °F to 140 °F)<br>Humidity 10–100% RH (condensing)   |
| Storage conditions                | -40 °C to 65 °C (-40 °F to 149 °F)   |
| Approvals                         | Radio<br>EN 300440, EN 301489-1, EN 301489-51, EN 62311, FCC Part 15 Subpart C<br>EMC<br>EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, RCM AS/NZS CISPR 32 Class A, VCCI Class B, EAC<br>Safety<br>IEC/EN/UL 62368-1, IEC/EN/UL 60950-22<br>Environment<br>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK08, NEMA 250 Type 4X |

|                             |  |
|-----------------------------|--|
| <b>Dimensions</b>           | 285 x 206 x 152 mm (11.2 x 8.1 x 6.0 in)   |
| <b>Weight</b>               | 2.4 kg (5.3 lb)  |
| <b>Included accessories</b> | Installation guide, connector kit, pipe adapters, cable gland, cable gaskets, Windows® decoder 1-user license  |
| <b>Optional accessories</b> | AXIS T91R61 Wall Mount<br>AXIS T91B47 Pole Mount<br>AXIS T94R01B Corner Bracket<br>AXIS T8415 Wireless Installation Tool<br>For more accessories, see <a href="http://axis.com">axis.com</a>   |
| <b>Applications</b>         | Radar motion detection (detect, track, and classify objects)<br>AXIS Speed Monitor<br>Radar autotracking<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a> |
| <b>Supporting software</b>  | AXIS Radar Autotracking for PTZ (Slew to Cue)<br>For supported cameras, see <a href="http://axis.com/products/axis-radar-autotracking">axis.com/products/axis-radar-autotracking</a>   |

|                                  |   |
|----------------------------------|---|
| <b>Video management software</b> | AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a> |
| <b>Languages</b>                 | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese                             |
| <b>Warranty</b>                  | 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>   |

- a. *Mounting at another height affects the detection range. For more information, go to [axis.com](http://axis.com)*
- b. *Minimum distance between moving objects.*
- c. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([eyay@cryptsoft.com](mailto:eyay@cryptsoft.com)).*
- d. *Enter the radar's GPS position manually to get the objects' GPS position in the data stream.*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)