

# AXIS C1510 Network Pendant Speaker

For installation in high ceilings—large

This all-in-one speaker system makes audio announcements smart and easy. For instance, it can be used to make general live or prerecorded voice messages, remotely and proactively warn off intruders, and deliver instructions. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing. This visually attractive pendant speaker is ideal for mounting in high ceilings. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Easy installation with just one network cable \(PoE\)](#)
- > [Scalable and easy to integrate](#)
- > [Remote health testing](#)



# AXIS C1510 Network Pendant Speaker

<b>Audio hardware</b>		Notification via email, HTTP, HTTPS and TCP, external output activation
<b>Enclosure</b>	One way enclosure with 6.5 inches broadband dynamic cone speaker	<b>Built-in installation aids</b>
<b>Max sound pressure level</b>	96 dB	Test tone verification and identification
<b>Frequency response</b>	60 Hz - 20 kHz	<b>Cybersecurity</b>
<b>Coverage pattern</b>	130° coaxial	<b>Edge security</b>
<b>Audio input/output</b>	Built-in microphone (can be disabled) External microphone, Line in	Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot
<b>Built-in microphone specification</b>	50 Hz - 20 kHz	<b>Network security</b>
<b>Amplifier description</b>	Built-in 7 W Class D amplifier	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
<b>Digital signal processing</b>	Built-in and pre-configured	<b>Documentation</b>
<b>Audio management</b>		<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>
<b>AXIS Audio Manager Edge</b>	Built in: – Content management for music and live/pre-recorded announcements. – Scheduling to decide when and where to play specific content. – Content prioritization to ensure urgent messages interrupt the schedule. – Zone management allowing you to divide up to 200 speakers into 20 zones. – Health monitoring for remote discovery of system errors. – User management to control who has access to what features. See separate datasheet for more details.	<b>General</b>
<b>AXIS Audio Manager Pro</b>	For larger and more advanced systems. Sold separately. See separate datasheet for specifications.	<b>Casing</b>
<b>Audio software</b>		IP40 Baffle: plastic Mesh: Surface-treated steel plate Mesh color: Off-white (RAL 9010 or equivalent) Top cover: Plastic Repaintable. For repainting instructions and impact on warranty, contact your Axis partner. Speaker mounting method: Hook
<b>Audio streaming</b>	One-way/two-way with optional half-duplex echo cancellation. Mono.	<b>Power</b>
<b>Audio encoding</b>	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis $\mu$ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	Power over Ethernet (PoE), IEEE 802.3af/802.3af, Type 1 Class 3 (max 12.95 W)
<b>System on chip (SoC)</b>		<b>Connectors</b>
<b>Model</b>	i.MX 6SoloX	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for 2x supervised configurable I/Os
<b>Memory</b>	512 MB RAM, 512 MB Flash	<b>Storage</b>
<b>Network</b>		Support for microSD/microSDHC/microSDXC card Max. size 64 GB For SD card recommendations see <a href="https://www.axis.com">www.axis.com</a>
<b>Network protocols</b>	IPv4/v6 <sup>a</sup> , HTTP, HTTPS, SSL/TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), NTCP, SIP (Cisco, Avaya, Asterisk)	<b>Reliability</b>
<b>System integration</b>		Designed for 24/7 operation.
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX®, One-click cloud connection, AXIS Camera Application Platform (ACAP).	<b>LED indicators</b>
<b>VoIP</b>	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	<b>Operating conditions</b>
<b>Intelligent audio</b>	Auto Speaker Test (verification via built-in microphone)	-30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–85% RH (condensing)
<b>Event triggers</b>	Call, virtual inputs, external input, AXIS Camera Application Platform (ACAP)	<b>Approvals</b>
<b>Event actions</b>	Play audio clip, send SNMP trap, send Auto Speaker Test, status LED, File upload via HTTP, network share and email,	EMC CISPR 24, CISPR 35, CISPR 32 Class A, EN 55024, EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN35, KC KN32 Class A, RCM AS/NZS CISPR 32 Class A, VCCI Class A <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, EC 60068-2-27, IEC/EN 60529 IP4X <b>Safety</b> CAN/CSA C22.2 No. 62368-1, IEC/EN 62368-1, KC-Mark, UL 62368-1
		<b>Dimensions</b>
		Height: 180 mm (7.1 in), Ø 290 mm (11.4 in)
		<b>Weight</b>
		4100 g (9.0 lbs)
		<b>Optional accessories</b>
		AXIS TC1901 Wire Kit, AXIS Safety Wire 3M For accessories, see <a href="https://axis.com">axis.com</a>
		<b>Video management software</b>
		AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <a href="https://axis.com/techsup/software">axis.com/techsup/software</a>
		<b>Languages</b>
		English, German, French, Spanish, Italian
		<b>Warranty</b>
		5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>

a. Audio synchronization with IPv4 only.