

AXIS M3047-P Network Camera

6 MP mini dome with 360° panoramic view

AXIS M3047-P is an affordably priced fixed dome with a 6 MP sensor in an environment-friendly, discreet design. It offers 360° overview and dewarped views such as panorama, view area, corridor, corner and quad views with outstanding sharpness. HDMI support enables live streaming to an HDTV monitor for public viewing. Black, vandal-resistant and smoke-detector casings are available as accessories, and AXIS M3047-P is easily repaintable to blend in with any environment. Installation is quick with bayonet-fitted casing and easy cable connection. No manual focusing is needed since the camera comes factory-focused.

- > **Complete panoramic overview with outstanding sharpness**
- > **Quick installation with small and discreet design**
- > **Zipstream for reduced bandwidth and storage**
- > **HDMI™ support enables streaming to a monitor**
- > **70% recycled plastics and PVC-free design**



2048 x 2048
3072 x 2048

AXIS M3047-P Network Camera

Camera		Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text
Image sensor	6 MP (3072x2048) 1/1.8" progressive scan RGB CMOS	Data streaming	Event data
Lens	F2.8, fixed iris, fixed focus, 1.6 mm Horizontal field of view: 185° Vertical field of view: 185°	Built-in installation aids	Pixel counter
Minimum illumination	0.3 lux at 50 IRE F2.8	General	
Shutter speed	1/31500 s to 1/2 s	Casing	Aluminum and plastic casing, encapsulated electronics Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Camera adjustment	Rotation ±180°	Sustainability	PVC free, 70% recycled plastics
Video		Memory	1024 MB RAM, 256 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 4.2 W, max 6.49 W
Resolution	360° overview: 2048x2048 to 480x480 Panorama: 2304x648 to 640x240 Double Panorama: 2304x1296 to 480x360 Quad view: 2304x1296 to 480x360 View area: 1920x1440 to 480x360 Corner left or right: 1920x720 to 640x240 Double Corner: 1920x1440 to 480x360 Corridor: 2304x1296 to 480x360	Connectors	Shielded RJ45 10BASE-T/100BASE-TX PoE HDMI™ Type D ^b Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology (no support for AXIS T61 Mk II)
Frame rate	360° overview only, up to 2048x2048: 30/25 fps @ 60Hz/50Hz Dewarped view in max resolution + 360° overview up to 1920x1920: 15/13 fps @ 60Hz/50Hz View area in 1280x720 + 360° overview up to 1200x1200: 30/25 fps @ 60Hz/50Hz	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations, see axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264 HDMI™	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)
Multi-view streaming	360° overview. Dewarped panorama, corridor, corner and quad views. Two individually cropped out and dewarped view areas. The 360° overview can be streamed simultaneously with two view areas or one other dewarped view.	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
HDMI output	HDMI 720p@50/60 fps (50/60 Hz)	Approvals	EMC EN 55024, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, WDR – dynamic contrast, noise reduction, rotation: 0°, 180°, text and image overlay, privacy masks, mirroring of images	Dimensions	Height: 46 mm (1.8 in) ø: 101 mm (4.0 in)
Pan/Tilt/Zoom	Digital PTZ of view areas, preset positions, guard tour, digital tilt of panorama, and quad views	Weight	240 g (0.53 lb)
Audio		Included accessories	Installation guide, Windows® decoder 1-user license, drill hole template
Audio input/output	Two-way audio connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology (no support for AXIS T61 Mk II)	Optional accessories	AXIS T94B02D Pendant Kit AXIS T94B05L Recessed Mount AXIS T94B01P Conduit Back Box AXIS T94B02M J-Box/Gang Box Plate AXIS M30 Casing B, Black AXIS M30 Vandal-resistant Casing A AXIS M30 Smoke Detector Casing A Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories, see axis.com
Network		Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/support/downloads
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Network protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, HDMI™ 1.4b	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
System integration		<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</p> <p>b. Make sure that the cable has a slim connector plug</p>	
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF® Profile G and ONVIF® Profile S, specifications at onvif.org		
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		
Event triggers	Analytics, edge storage events, virtual inputs through API		