

AXIS P3925-R Network Camera

For advanced indoor surveillance onboard trains and buses

Specifically designed for indoor surveillance for trains and buses, AXIS P3925-R complies with all relevant transportation industry regulations including EN50155, EN45545, and NFPA 130. Featuring Axis Lightfinder and Axis Forensic WDR, it delivers true colors and great detail in challenging light or near darkness. Enclosed in an IK10-, IP66-, IP67-rated metal casing, this robust, vandal-resistant camera offers extended capabilities for analytics. Furthermore, enhanced security features prevent unauthorized access and safeguard your system.

- > **Vandal-resistant, metal casing**
- > **Indoor camera**
- > **Complies with EN50155, EN45545, and NFPA 130**
- > **Lightfinder and Forensic WDR**
- > **Electronic image stabilization**



AXIS P3925-R Network Camera

Variants

AXIS P3925-R RJ45

AXIS P3925-R M12

Camera

Image sensor

1/2.9" Progressive scan RGB CMOS

Lens

2.8 mm, F1.6

Horizontal field of view: 110°

Vertical field of view: 62°

M12 mount, fixed iris

See [Optional accessories](#) for exchangeable lenses

Day and night

Automatically removable infrared-cut filter

Minimum illumination

Color: 0.06 lux at 30 IRE F1.6

B/W: 0.01 lux at 30 IRE F1.6

Color: 0.12 lux at 50 IRE F1.6

B/W: 0.02 lux at 50 IRE F1.6

Shutter speed

1/33500 s to 2 s

Camera adjustment

Pan: ±30°

Tilt: 15–90°

Rotation: ±175°

System on chip (SoC)

Model

ARTPEC-7

Memory

1 GB RAM, 512 MB Flash

Video

Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles

H.265 (MPEG-H Part 2/HEVC) Main Profile

Motion JPEG

Resolution

1280x960 to 160x120

1920x1080 to 160x90

WDR

Forensic WDR

Frame rate

Up to 25/30 fps (50/60 Hz) in all resolutions

45 fps in 720p

Capture mode 2MP 1920x1080 (16:9) @25/30 fps

Capture mode 1MP 1280x720 (16:9) @45 fps

Video streaming

Multiple, individually configurable streams in H.264, H.265 and Motion JPEG

Axis Zipstream technology in H.264 and H.265

Controllable frame rate and bandwidth

VBR/ABR/MBR H.264 and H.265

Video streaming indicator

Low latency mode

Multi-view streaming

Up to 8 individually cropped out view areas

Image settings

Compression, brightness, sharpness, contrast, white balance, Forensic WDR, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, dynamic overlay, 20 individual polygonal privacy mask, mirroring of images, defogging, electronic image stabilization¹
Scene profiles: forensic, vivid, traffic overview

Pan/Tilt/Zoom

Digital PTZ, preset positions, guard tour, control queue

1. Use this function only when camera is directed to capture scenes outside of the vehicle

Network

Network protocols

IPv4, IPv6, USGv6, HTTP, HTTPS², HTTP/2, TLS², QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

System integration

Application Programming Interface

Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com

AXIS Video Hosting System (AVHS) with One-Click Connection

One-click cloud connection

ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Event conditions

Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature

Edge storage: recording ongoing, storage disruption

I/O: manual trigger, virtual input

MQTT subscribe

Scheduled and recurring: scheduled event

Video: average bitrate degradation, day-night mode, live stream open, tampering

Event actions

Day-night mode

Defog

Guard tours

Upload images or video clips: FTP, HTTP, HTTPS, SFTP, email and network share

Notification: HTTP, HTTPS, TCP and email

Overlay text

Preset positions

Record video: SD card and network share

SNMP trap messages

WDR mode

MQTT publish

Data streaming

Event data

Built-in installation aids

Pixel counter

Analytics

Applications

Included

AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard

AXIS Video Motion Detection, active tampering alarm³, blocked view detection⁴, shock detection

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption
Hardware: Secure boot

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)², IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS², TLS v1.2/v1.3², Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).

3. For detection of tampering attempts in static and non-crowded scenes.

4. For detection of tampering attempts in onboard environments.

Documentation

Axis OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

Axis OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

IP66/67-, NEMA 250 4X- and IK10-rated aluminum casing, polycarbonate clear dome

Sustainability

PVC free

Mounting

Inside vehicles and rolling stock

Power

Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2

Typical 4.2 W, max 6.4 W

Connectors

RJ45: male, 10BASE-T/100BASE-TX

M12: female, rugged, D-coded with rotatable coupling nut

All connectors support PoE

Storage

Support for microSD/microSDHC/microSDXC card with UHS Speed Class U1

Support for SD card encryption (AES-XTS-Plain64 256bit)

Support for recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com

Operating conditions

Normal: -40 °C to 55 °C (-40 °F to 131 °F)

Maximum (intermittent): 70 °C (158 °F)

Arctic Temperature Control: start-up at -40 °C (-40 °F)

Humidity: 10-100% RH (condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Approvals

EMC

EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.06 (E approval), EN 50498

Safety

IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, EN 45545-2, UN ECE R118, NFPA 130, IS 13252

Environment

IEC/EN 61373 Category 1 Class B, IEC/EN 60529 IP66, IEC/EN 60529 IP67, parts of

NEMA 250 Type 4X (ingress of water and gasket test), IEC/EN 62262 IK10,

IEC 60721-3-5 Class 5M3 (vibration and shock),

EN 50155:2021 OT2/ST2, IEC 60068-2-1,

IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64,

IEC 60068-2-78

Network

NIST SP500-267

Dimensions

Height: 49.4 mm (1.94 in), ø 110 mm (4.33 in)

Weight

RJ45: 400 g (0.88 lb)

M12: 410 g (0.90 lb)

Included accessories

Installation guide, Windows® decoder 1-user license, drill hole template, lens tool, Resistorx® L-key

Optional accessories

Lenses

Lens M12 2.1 mm F1.8 IR: horizontal field of view 145°

Lens M12 3.6 mm F1.8 IR: horizontal field of view 87°

Lens M12 6 mm, F1.9 IR: horizontal field of view 56°

Lens M12 8 mm F1.8 IR: horizontal field of view 40°

Other

AXIS T94D01S Mount Bracket,

AXIS T94D02S Curved Mount Bracket,

Network coupler IP66, network cable coupler indoor

For more accessories, see axis.com

Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty