

AXIS V5925 PTZ Camera

Broadcast-quality HDTV 1080p PTZ camera

AXIS V5925 combines excellent image quality with smooth PTZ control and broadcast-quality audio for professional webcasting. It's compatible with VISCA joysticks and VISCA over IP, making it easy to integrate with your existing AV installations. Offering enhanced security features such as signed firmware and secure boot, it ensures the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with H.264 and H.265 significantly reduces bandwidth and storage requirements without compromising image quality. NDI[®] compliant (license to be bought separately).

- > **HDTV 1080p at 60 fps and 30x zoom**
- > **High-quality audio with XLR inputs**
- > **VISCA and VISCA over IP support**
- > **Camstreamer 3-month trial included**
- > **3G-SDI and HDMI outputs**



AXIS V5925 PTZ Camera

Camera		
Image sensor	Progressive scan RGB CMOS 1/2.8"	Output impedance: < 100 Ohm, short circuit proof Maximum output level: > 0.707 Vrms Bandwidth: 20 Hz - 20 kHz (± 3 dB), may be limited by sample rate THD+N: < 0.03% @ 10 kOhm load Signal-to-Noise ratio: > 87 dB
Lens	4.4-132 mm, F1.4-4.6 Horizontal field of view: 62°-2.3° Vertical field of view: 37°-1.3° Autofocus, P-iris control	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 1.0 lux at 30 IRE F1.4 B/W: 0.03 lux at 30 IRE F1.4	
Shutter speed	1/10000 s to 1 s	
Pan/Tilt/Zoom	Pan: $\pm 170^\circ$, 0.2-100°/s Tilt: -20° - 90° , 0.2-90°/s Zoom: 30x Optical, 12x Digital, Total 360x 256 presets positions, Control queue, On-screen directional indicator, Adjustable zoom speed, PTZ response profiles	
System on chip (SoC)		
Model	ARTPEC-7	
Memory	1 GB RAM, 512 MB Flash	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	1920x1080 HDTV 1080p to 160x90 HDMI/SDI Output: 1080p@50/60 fps (50/60 Hz)	
Frame rate	Up to 60/50 fps (60/50 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 HDMI HD-SDI: SMPTE 292 3G-SDI: SMPTE 424 ,SMPTE 425 (3G-SDI mapping supports Level A / Level B dual link mapping)	
Image settings	Saturation, brightness, sharpness, white balance, day/night threshold, exposure mode, exposure zones, defogging, rotation: 0°, 180°	
Audio		
Audio streaming	Two-way, stereo HD-SDI: SMPTE ST 299-1 3G-SDI: SMPTE ST 299-2	
Audio encoding	SDI: AES3 24 bit, 48 kHz HDMI: LPCM Network: AAC LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz, Configurable bit rate	
XLR input	2 balanced inputs (left/right) Microphone phantom power 48 V Balanced external microphone Balanced line level Line input impedance: >10 kOhm Maximum input level: 4.4 Vrms Bandwidth: 20 Hz - 20 kHz (± 3 dB), may be limited by sample rate THD+N: < 0.03% Signal-to-Noise ratio: > 85 dB @ 0 dB gain, > 78 dB @ 30 dB gain	
3.5 mm input	Microphone Power 5 V via 2.2 kOhm Unbalanced external microphone Unbalanced line Line input impedance: >10 kOhm Maximum input level: 2.2 Vrms Bandwidth: 20 Hz - 20 kHz (± 3 dB), may be limited by sample rate THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB @ 0 dB gain, > 83 dB @ 30 dB gain	
3.5 mm output	3.5 mm unbalanced stereo output	
SDI output	Bandwidth: 20 Hz - 20 kHz (± 3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB	
HDMI output	Bandwidth: 20 Hz - 20 kHz (± 3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot	
Network protocols	IPv4/v6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT, Syslog, Link-Local address (ZeroConf), HDMI, 3G-SDI, VISCA	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.	
Event conditions	Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, live stream open	
Event actions	MQTT publish Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call	
Data streaming	Event data	
Built-in installation aids	Pixel counter, leveling guide	
Analytics		
Applications	Included AXIS Video Motion Detection, AXIS PTZ Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
General		
Casing	ASA plastic cover Color: White NCS S 1002-B	
Power	11-13 V DC (12 V power supply included), typical 14 W, max 25 W	
Connectors	RJ45 10BASE-T/100BASE-TX	

	Terminal block for 2 configurable alarm input/output 3.5 mm stereo mic/line in, 3.5 mm stereo line out XLR-3 (left + right) mic/line in (with 48 V phantom power) HDMI Type A, BNC for SDI DC input RS232 serial connector for VISCA	Network NIST SP500-267
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	Dimensions Height: 180 mm (7.1 in) Ø 136 mm (5.4 in)
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10-85% RH (non-condensing)	Weight 1.5 kg (3.3 lb)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5 - 95% RH (non-condensing)	Included accessories Power supply, wall/ceiling mount, terminal connector for I/O, installation guide, Windows® decoder user license, Camstreamer 3-month trial
Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, KC-Mark, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78	Optional accessories AXIS T8310 Video Surveillance Control Board AXIS VISCA Cable For more accessories, see axis.com
		Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty 5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility