

AXIS TP1001-E Wall-and-Pole Mount

Robust mount for dome cameras

With this wall-and-pole mount, installers can choose to use either an RJ45 or IDC (insulation-displacement contact) connector for the installation. It features a built-in cable with an Ethernet IP66-rated RJ45 connector to facilitate installation and prevent water and dust from entering the camera. Made from impact-resistant, outdoor-ready material, AXIS TP1001-E is suited for both indoor and outdoor environments. Flipping the mounting bracket makes it possible to turn AXIS TP1001-E from a wall mount to a pole mount (AXIS Steel Straps TX30 are required). The mount is also suitable for corner mounting with an optional accessory.

- > **Robust, IK10-rated**
- > **For indoor and outdoor use**
- > **Versatile connection with IDC connector**
- > **Built-in IP66-rated RJ45 connector**
- > **5-year warranty**



AXIS TP1001-E Wall-and-Pole Mount

Approvals

Product markings

CSA, UL/cUL, UKCA, CE, KC, VCCI, RCM

Supply chain

TAA compliant

EMC

CISPR 35, CISPR 32 Class A, EN 55035,
EN 55032 Class A, EN 50121-4, EN 61000-6-1,
EN 61000-6-2

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KS C 9835, KS C 9832 Class A

USA: FCC Part 15 Subpart B Class A

Railway: IEC 62236-4

Safety

CAN/CSA C22.2 No. 62368-1 ed. 3,

IEC/EN/UL 62368-1 ed. 3

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6,
IEC 60068-2-27, IEC/EN 60529 IP66, IEC/EN 62262
IK10, NEMA 250 Type 4X, MIL-STD 810G 509.5

General

Supported products

Cameras compatible with specific pendant kits with
1.5" NPS thread mount, such as:

AXIS P3255-LVE camera

AXIS Q3538-LVE camera

AXIS P3727-PLC camera

For a complete list of compatible cameras, go to axis.com/products/axis-tp1001-e-wall-and-pole-mount#compatible-products

Casing

IP66-, NEMA 4X- and IK10-rated

Powder-coated aluminum casing

Color: white NCS S 1002-B

Mounting

Back: Cable hole

Bottom: 3/4" (M25) conduit side entries

Connectors

Output: RJ45 Ethernet (male)

Input: RJ45 Ethernet (female), IDC

Operating conditions

-50 °C to 65 °C (-58 °F to 149 °F)

Humidity 10–100% RH (non-condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Humidity 10–100% RH (non-condensing)

Dimensions

For the overall product dimensions, see the dimension drawing in this datasheet.

Weight

2164 g (4.8 lb)

Maximum load: 40 kg (88.2 lb)

Box content

Mount, wall bracket, installation guide, cable ties, RJ45 mounting tool

Optional accessories

AXIS ACI Conduit Adapters

AXIS T91A64 Corner Bracket

AXIS Steel Straps TX30 570 mm

AXIS Steel Straps TX30 1450 mm

For more accessories, go to axis.com/products

Warranty

5-year warranty, see axis.com/warranty

Part numbers

Available at axis.com/products/axis-tp1001-e-wall-and-pole-mount#part-numbers

Sustainability

Substance control

PVC free

Materials

Screened for conflict minerals in accordance with OECD guidelines

To read more about sustainability at Axis, go to axis.com/about-axis/sustainability

Environmental responsibility

axis.com/environmental-responsibility

Axis Communications is a signatory of the UN Global Compact, read more at *unglobalcompact.org*

Dimension drawing

