

AXIS Q6075-S PTZ Network Camera

Outdoor-ready, stainless steel PTZ with HDTV 1080p and 40x zoom

AXIS Q6075-S PTZ Network Camera offers great overviews and excellent details. The marine-grade stainless steel casing can be filled with nitrogen to prevent internal condensation and create a nonflammable environment. It comes with autotracking 2, as well as an orientation aid for active object tracking and quick orientation. With Axis Lightfinder 2.0 the camera delivers low-light images with more saturated colors and sharper images of moving objects. Plus, the included TPM module ensures highest network security. Furthermore, Zipstream with H.264/ H.265 significantly lowers bandwidth and storage. The media converter enables daisy chain installation using standard network or fiber optic cables.

- > **Pressurized marine-grade stainless steel casing**
- > **HDTV 1080p and 40x optical zoom**
- > **SFP slots for fiber, RJ45 connections**
- > **I/O for alarm in/out**
- > **Built-in analytics**



AXIS Q6075-S PTZ Network Camera

Variants

AXIS Q6075-S 50 Hz
AXIS Q6075-S 60 Hz

Camera

Image sensor

1/2.8" progressive scan CMOS

Lens

4.25–170 mm, F1.6–4.95
Horizontal field of view: 65.1°–2.00° (1080p)
Vertical field of view: 39.1°–1.18° (1080p)
Autofocus, auto-iris

Day and night

Automatically removable infrared-cut filter

Minimum illumination

Color: 0.1 lux at 30 IRE, F1.6
B/W: 0.002 lux at 30 IRE, F1.6
Color: 0.15 lux at 50 IRE, F1.6
B/W: 0.003 lux at 50 IRE, F1.6

Shutter speed

1/11000 s to 1/3 s with 50 Hz
1/11000 s to 1/3 s with 60 Hz

Pan/Tilt/Zoom

Pan: 360° endless, 0.05°–450°/s
Tilt: 220°, 0.05°–450°/s
Zoom: 40x optical, 12x digital, total 480x zoom
E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, focus recall

System on chip (SoC)

Model

ARTPEC-7

Memory

1024 MB RAM, 512 MB Flash

Compute capabilities

Machine learning processing unit (MLPU)

Video

Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles
H.265 (MPEG-H Part 2/HEVC) Main Profile
Motion JPEG

Resolution

HDTV 1080p 1920x1080 to 320x180

Frame rate

Up to 50/60 fps (50/60 Hz) in HDTV 1080p

Video streaming

Multiple, individually configurable streams in H.264, H.265 and Motion JPEG
Axis Zipstream technology in H.264 and H.265
Controllable frame rate and bandwidth
VBR/ABR/MBR H.264/H.265

Image settings

Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, polygon privacy masks, electronic image stabilization (EIS), freeze on PTZ, automatic defog, backlight compensation, scene profiles
Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation

Network

Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS¹, TLS¹, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, PTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

1. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

System integration

Application Programming Interface

Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com

One-Click Cloud Connection

ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Event conditions

Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature
Edge storage: recording ongoing, storage disruption
I/O: digital input, manual trigger, virtual input
MQTT subscribe

PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready

Scheduled and recurring: scheduled event

Video: live stream open

Event actions

Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap

PTZ: PTZ preset, start/stop guard tour

File upload via FTP, SFTP, HTTP, HTTPS network share and email

Notification via email, HTTP, HTTPS and TCP

MQTT publish

Built-in installation aids

Pixel counter, leveling guide

Analytics

Applications

Included

AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, autotracking 2, active gatekeeper

Basic analytics (not to be compared with third-party analytics): object removed, enter/exit detector, object counter

Supported

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

AXIS Object Analytics

Object classes: humans, vehicles

Scenarios: line crossing, object in area, crossline counting

Up to 10 scenarios

Other features: triggered objects visualized with color-coded bounding boxes

Polygon include/exclude areas

Perspective configuration

ONVIF Motion Alarm event

AXIS Scene Metadata

Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates

Object attributes: confidence, position

Approvals

EMC

EN 50121-4, IEC 62236-4, EN 55024, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KCC KN32 Class A, KN35

USA: FCC Part 15 Subpart B Class A

Safety

IEC/EN/UL 60950-22, IEC/EN/UL 62368-1

Environment

IEC/EN 60529 IP66/IP67, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), MIL-STD 810G (Method 509)

Network

NIST SP500-267

Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS 140

Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, Axis Cryptographic Module (FIPS 140-2 level 1), AES-XTS-Plain64 256bit SD card encryption
Hardware: Secure boot, Axis Edge Vault with secure keystore (CC EAL4+, FIPS 140-2 level 2 certified hardware protection of cryptographic operations and keys)

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)², IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS², TLS v1.2/v1.3², Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

Documentation

AXIS OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

IP6K9K-, IP66-, IP67-³, NEMA 4X-, NEMA 6P and IK10-rated⁴

Stainless steel casing (V4A, SAE 316L/UNS S31603/EN 1.4404), nylon clear dome

Sustainability

PVC free

Power

Camera consumption: Max 65 W

PSU: 24 V DC +/- 0.5 V, min 3.2 A (75 W)

Connectors

IP68-rated multiconnector for DC power, Ethernet 10BASE-T/100BASE-TX and I/O

Storage

Support for SD/SDHC/SDXC card

Support for SD card encryption

Support for recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com

Operating conditions

-30 °C to 50 °C (-22 °F to 122 °F)

Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)

Humidity 10–100% RH (condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Humidity 5–95% RH (non-condensing)

Weight

6.0 kg (13 lb)

Dimensions

Ø224 x 256 mm (Ø8.82 x 10.1 in)

Included accessories

AXIS T8607 Media Converter Switch, 7 m (23 ft) IP68-rated multicable

Installation Guide, Windows decoder 1-user license

Optional accessories

AXIS T8008 Power Supply, AXIS T94A02D Pendant Kit, AXIS T91F67 Pole Mount⁵, AXIS Q60-S Smoked Dome, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack

Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty

2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

3. Applies when the camera is filled with nitrogen.

4. Except valves on top.

5. Requires AXIS T91K61 Wall Mount

AXIS T8607 Media Converter Switch

General

Casing

Metal

Color: White NCS S 1002-B

Power

24 V DC, max 4 W (power supply not included)

Connectors

2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP) CAT5 or higher.)

2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP to copper modules

1x power

2x configurable alarm input/output ports

Camera multicable

Display and indicators

Power LED indicator

Camera network LED indicator

Network LED indicator (4x)

Compliance

RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756

Mounting

DIN Rail mount

Environment

Indoor/Cabinet

Operating conditions

-40 °C to 75 °C (-40 °F to 167 °F)

Humidity 10-85% RH (non-condensing)

Storage conditions

-40 °C to 75 °C (-40 °F to 167 °F)

Humidity 10-85% RH (non-condensing)

Approvals

EMC

EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15

Subpart B Class A, ICES-003 Class A, VCCI Class A,

RCM AS/NZS CISPR 22, KCC KN22 Class A, KN24

Safety

IEC/EN 60950-1

Dimensions

150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in)

Weight

284 g (0.63 lb)

Included accessories

Bracket Mount DIN Clip

Warranty

3-year warranty, see axis.com/warranty