

AXIS M5000 PTZ Camera

Situational awareness camera with build-in PTZ

AXIS M5000 PTZ features three 5 MP sensors and one PTZ camera with 10x optical zoom for total situational awareness of indoor areas up to 400 m² (4300 ft²). With everything displayed on one monitor, you can move from overview to detailed views in a single click. It features autofocus capabilities and day/night functionality. This cost-effective camera offers the benefits of four cameras while installing just one camera. Furthermore, edge storage lets you record directly to an onboard memory card.

- > **3x 5 MP sensors for situational awareness**
- > **Total overview, zoomed-in details**
- > **Covers indoor areas up to 400 m² (4300 ft²)**
- > **10x optical zoom with HDTV 1080p**
- > **Autofocus**



AXIS M5000 PTZ Camera

| | | | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera | | Audio encoding | 24 bit LPCM, AAC-LC 8/16/32/44.1 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate |
| Image sensor | PTZ camera: 1/2.8" progressive scan RGB CMOS Overview cameras: 1/2.8" progressive scan RGB CMOS | Audio input/output | External microphone input or line input, line output, automatic gain control |
| Lens | PTZ camera: Varifocal, 4.7–47 mm, F1.6–3.0 Horizontal field of view: 61.8°–6.7° Vertical field of view: 36.3°–3.8° Autofocus, auto-iris, P-Iris control Overview cameras: Focal length 2.39 mm, F2.0 Horizontal field of view: 360° Vertical field of view: 93° | Network | |
| Day and night | PTZ camera: Automatically removable infrared-cut filter | Security | HTTPS ^b encryption, IEEE 802.1x (EAP-TLS) network access control, user access log, centralized certificate management, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified) |
| Minimum illumination | PTZ camera: Color: 0.09 lux at 30 IRE F1.6 B/W: 0.01 lux at 30 IRE F1.6 Color: 0.1 lux at 50 IRE F1.6 B/W: 0.01 lux at 50 IRE F1.6 Overview cameras: Color: 0.08 lux at 30 IRE F2.0 B/W: 0.03 lux at 30 IRE F2.0 Color: 0.4 lux at 50 IRE F2.0 B/W: 0.03 lux at 50 IRE F2.0 | Network protocols | IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^c , HTTP/2, TLS ^d , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP ^e , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf) |
| Shutter speed | PTZ camera: 1/66500 s to 2 s Overview cameras: 1/50000 s to 2 s | System integration | |
| Pan/Tilt/Zoom | PTZ camera: Pan: 360° with autoflip, 1.8°–150°/s Tilt: 180°, 1.8°–150°/s 10x optical zoom, 12x digital zoom, total 120x zoom 100 preset positions, limited guard tour, control queue, on-screen directional indicator, E-flip, click-in-image | Application Programming Interface | Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org |
| System on chip (SoC) | | Video management systems | Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms . |
| Model | ARTPEC-7 | Onscreen controls | Focus recall area Video streaming indicator Privacy masks Day/night shift |
| Memory | 2048 MB RAM, 512 MB Flash | Event conditions | Audio: audio clip playing Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open |
| Video | | Event actions | Audio clips: play, play while the rule is active, stop playing Guard tours: Run while the rule is active, start MQTT publish Notification: email, HTTP, HTTPS, TCP and SNMP trap Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Day-night mode, overlay text, preset positions, WDR mode |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG | Data streaming | Event data |
| Resolution | PTZ camera: 1920x1080 to 320x180 Overview cameras: 2592x1944 to 320x180 | Built-in installation aids | Pixel counter |
| Frame rate | PTZ camera: Up to 25/30 fps with power line frequency 50/60 Hz Overview cameras: Up to 12 fps with power line frequency 50/60 Hz | Analytics | |
| Video streaming | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator Streaming modes: unicast and multicast ^a | Applications | Included AXIS Loitering Guard AXIS Video Motion Detection, audio detection, shock detection, advanced gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap |
| Image settings | Saturation, contrast, brightness, sharpness, WDR – forensic capture, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, compression, text and image overlay, polygon privacy masks, image freeze on PTZ, local contrast, max shutter, max gain, noise/motion priority, aperture lock, exposure level Scene profiles: indoor, forensic | Approvals | |
| Signal-to-noise ratio | >55 dB | EMC | EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2 USA: FCC Part 15 Subpart B Class A Canada: ICES-3(A)/NMB-3(A) Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Korea: KS C 9832 Class A, KS C 9835 |
| Audio | | Safety | CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IS 13252 |
| Audio streaming | Two-way, full duplex | Environment | IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP51 |

| | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network | NIST SP500-267 |
| Cybersecurity | ETSI EN 303 645, BSI IT Security Label |
| Cybersecurity | |
| Edge security | Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot |
| Network security | IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) ^e , IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS ^f , TLS v1.2/v1.3 ^g , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall |
| Documentation | <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity |
| General | |
| Casing | IP51-rated Repaintable plastic casing, polycarbonate (PC) dome |
| Sustainability | PVC free, BFR/CFR free |
| Power | Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4 Typical 7.4 W, max 13.0 W 20–28 V DC, typical 6.5 W, max 11.9 W (PoE midspan and power supply not included) |
| Connectors | RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE DC input terminal block Audio: mic/line in, line out terminal block |
| Storage | Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) |

| | |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com |
| Operating conditions | 0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing) |
| Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing) |
| Dimensions | Height: 138 mm (5.4 in), ø 247 mm (9.7 in) |
| Weight | 1.95 kg (4.3 lb) |
| Included accessories | Installation Guide, Windows® decoder 1-user license, drill hole template, terminal block connectors, connector guard, bayonette screws |
| Optional accessories | AXIS TM5601 Conduit Back Box AXIS TM5801 Black Dome For more accessories, see axis.com |
| Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese |
| Warranty | 5-year warranty, see axis.com/warranty |

- We recommend that you use multicast when multiple streams per sensor is required.*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*