

ExCam XF Q1645 Explosion-Protected Network Camera

Zone-certified fixed camera with excellent light sensitivity

ExCam XF Q1645 Explosion-Protected Network Camera is an easy-to-install and easy-to-integrate fixed box camera. It delivers high-resolution video (2 MP) at full frame rate (up to 120 fps) for crystal-clear images. The electronic image stabilization greatly improves video quality where the camera is subject to vibrations. The camera is adapted for explosion-prone applications with ATEX, IECEx, EAC Ex, and IA certifications. With low weight, PoE support for plug-and-play installation, ExCam XF Q1645 offers significant savings. The camera helps detecting unauthorized individuals and monitor employee safety in hazardous areas. Suitable for onshore, offshore, marine, and heavy industrial environments.

- > **Certified for ATEX, IECEx, EAC Ex, and IA; Zones 1, 2, 21, and 22; Groups IIC and IIIC**
- > **Cost-efficient installation with PoE**
- > **HDTV 1080p at 100/120 fps**
- > **Unparalleled light sensitivity with 1/2" sensor**
- > **Electronic image stabilization (EIS) and low weight**



ExCam XF Q1645 Explosion-Protected Network Camera

Camera

Image sensor

1/2" progressive scan RGB CMOS

Lens

IR corrected i-CS lens
Varifocal 3.9–10.0 mm, F1.5
Horizontal field of view: 85°–42°
Vertical field of view: 47°–23°

Day and night

Automatically removable infrared-cut filter

Minimum illumination

HDTV 1080p 25/30 fps:
Color: 0.03 lux, B/W: 0.01 lux, SNR: 0.03 lux, at 50 IRE F1.5
HDTV 1080p 25/30 fps (WDR off):
Color: 0.02 lux, SNR: 0.02 lux, at 50 IRE F1.5

Shutter speed

1/100000 to 2 s

Pan/Tilt/Zoom

Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)

System on chip (SoC)

Model

ARTPEC-6

Memory

1 GB RAM, 512 MB Flash

Video

Video compression

H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile
Motion JPEG

Resolution

1920x1080 to 320x180

Frame rate

Up to 100/120 fps (50/60 Hz) in 1920x1080 (no WDR)

Video streaming

Multiple, individually configurable streams in H.264 and Motion JPEG
Axis Zipstream technology in H.264
Controllable frame rate and bandwidth
VBR/MBR H.264

Image settings

Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, text and image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light
Scene profiles: forensic, live, traffic overview, backlit entrance

Network

Security

Password protection, IP address filtering, HTTPS¹ encryption, IEEE 802.1X¹ network access control, digest authentication, user access log, centralized certificate management, brute force delay protection

Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS¹, TLS¹, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnPTM, SNMPv1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, PTP, NTS, RTSP, RTP, SFTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

System integration

Application Programming Interface

Open API for software integration, including VAPIX[®] and AXIS Camera Application Platform; specifications at axis.com/developer-community.
One-Click Cloud Connection
ONVIF Profile S and ONVIF Profile G, specifications at onvif.org

1. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Event triggers

Analytics, external input, edge storage events
Detectors: live stream accessed, video motion detection, shock detection
Hardware: network, temperature
Input Signal: manual trigger, virtual inputs
MQTT subscribe
PTZ: error, moving, preset reached, ready
Storage: disruption, recording
System: system ready
Time: recurrence, use schedule

Event actions

File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip
Notification: email, HTTP, HTTPS and TCP
Overlay text, Send SNMP Trap
Video recording to edge storage
Pre- and post-alarm video buffering
External output activation, day/night vision mode, status LED, WDR mode, Defog mode, PTZ control
MQTT publish

Data streaming

Event data

Built-in installation aids

Remote focus and zoom with supplied i-CS lens
Traffic wizard, pixel counter, levelling assistant

Analytics

Applications

Included

AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard

AXIS Video Motion Detection, active tampering alarm

Supported

AXIS Perimeter Defender

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

Approvals

EMC

EN 55032 Class A, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 62479, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11

Safety

IS 13252

Environment

IEC/EN 60529 IP68, IEC/EN 62262 IK10

Network

NIST SP500-267

Explosion

DIN EN/IEC 60079-0, DIN EN/IEC 60079-1, DIN EN/IEC 60079-7, DIN EN/IEC 60079-31, TR CU 012/2011, GOST R IEC 60079-0, GOST IEC 60079-1, GOST R IEC 60079-7, GOST R IEC 60079-31

Certifications

Camera:

Model key: T08-VA2.3.K3.BOR2-LL.H-005.A-T

ATEX: II 2 G Ex db IIC T5 Gb,

Ex II 2 D Ex tb IIIC T95°C Db, I M2 Ex db I Mb

Certificate: TÜV 18 ATEX 8218X

IECEX: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, Ex d I Mb

Certificate: IECEX TUR 18.0023X

IA: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, Ex d I Mb

Certificate: MASC MS/18-3256X

EAC Ex: 1Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, PB db I Mb

Series: T08, Model: T08-VA2.3.

Certificate: RU C-DE.AB61.B.00381/19

EXTB-3 Junction Box ExCam: (to be removed if the camera is installed in mines)

Model key: T12-3M20

ATEX: II 2 G Ex eb IIC T5 Gb, II 2 D Ex tb IIIC T95°C Db IP66, -50°C < Tamb < +55°C

Certificate: PTB 99 ATEX 3103

IECEX: Ex e IIC T5 Gb, Ex IIIC T95°C Db IP66, -50°C < Tamb < +55°C

Certificate: IECEX PTB 06.0026

EAC Ex: 1Ex e IIc T5 Gb X, Ex tb IIIC T95°C Db X

Certificate: RU C-DE.AA71.B.00120

PESO: Ex db IIC T6 Gb

Certificate: A/P/HQ/KA/104/5735

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)², IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS², TLS v1.2/v1.3², Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

Documentation

AXIS OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

IP68-rated, SS 1.4404 (ASTM 316L) stainless steel casing for maximum corrosion protection. Casing manufactured and certified by Samcon Prozessleittechnik GmbH, www.samcon.eu

Sustainability

PVC free

Power

Camera: Power over Ethernet (PoE)

IEEE 802.3af/802.3at Type 1 Class 3

Typical 4.5 W, max 9.1 W

Heater: 24 V DC, max 40 W

24 V DC is required for operating at temperatures below 0 °C (32 °F).

Connectors

EXTB-3 Junction Box ExCam:

10 terminal clamp UT 2.5

2 conductor terminal USLKG 5

Storage

Pre-installed AXIS Surveillance microSDXC Card 128 GB
Support for SD card encryption (AES-XTS-Plain64 256bit)

Support for recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com

Operating conditions

-60 °C to 60 °C (-76 °F to 140 °F)

Humidity 10-100% RH (condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Dimensions

357 x 113 x 139 mm (14.06 x 4.45 x 5.5 in)

Weight

10.8 kg (23.8 lb)

Included accessories

Weathershield ExCam XF, Installation Guide, Windows decoder 1-user license,

ASKDP03-T Cable ExCam 5 m (16 ft),

EXTB-3 Junction Box ExCam,

AXIS Surveillance microSDXC Card 128 GB

Optional accessories

Wall Mount ExCam XF, Pole Mount ExCam XF

Non-armored cables ExCam, 10, 25,

95 m (33, 82, 312 ft), Armored cables ExCam, 10, 25,

95 m (33, 82, 312 ft)

Ex Connection Rail 4-port PoE PS 24,

Ex Connection Rail 8-port PoE PS 24

For more accessories, see axis.com

Languages

English, German, French, Spanish, Italian, Russian,

Simplified Chinese, Japanese, Korean, Portuguese,

Traditional Chinese, Dutch, Czech, Swedish, Finnish,

Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty

2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).