

AXIS Q6074-E PTZ Network Camera

Outdoor-ready PTZ with HDTV 720p and 30x optical zoom

AXIS Q6074-E PTZ Network Camera offers HDTV 720p and 30x optical zoom for great overviews and excellent details. This high-performance outdoor PTZ camera comes with autotracking 2 with click and track functionality, as well as an orientation aid for active object tracking and quick orientation. With Axis Lightfinder 2.0 the camera delivers low-light images with more saturated colors and sharper images of moving objects. Plus, enhanced security features such as signed firmware and secure boot ensures the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with H.264/ H.265 significantly lowers bandwidth and storage requirements.

- > **HDTV 720p with 30x optical zoom**
- > **Axis Lightfinder 2.0**
- > **Autotracking 2 and orientation aid**
- > **Built-in analytics**
- > **TPM, FIPS 140-2 level 2 certified**



AXIS Q6074-E PTZ Network Camera

Variants

AXIS Q6074-E 50 Hz
AXIS Q6074-E 60 Hz

Camera

Image sensor

1/2.8" progressive scan CMOS

Lens

4.25–127.5 mm, F1.6–4.2
Horizontal field of view: 63.8°–2.6° (720p)
Vertical field of view: 38.0°–1.47° (720p)
Autofocus, auto-iris

Day and night

Automatically removable infrared-cut filter

Minimum illumination

Color: 0.1 lux at 30 IRE, F1.6
B/W: 0.002 lux at 30 IRE, F1.6
Color: 0.15 lux at 50 IRE, F1.6
B/W: 0.003 lux at 50 IRE, F1.6

Shutter speed

1/11000 s to 1/3 s with 50 Hz
1/11000 s to 1/3 s with 60 Hz

Pan/Tilt/Zoom

Pan: 360° endless, 0.05°–450°/s
Tilt: 220°, 0.05°–450°/s
Zoom: 30x optical, 12x digital, total 360x zoom
E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, focus recall

System on chip (SoC)

Model

ARTPEC-7

Memory

1024 MB RAM, 512 MB Flash

Compute capabilities

Machine learning processing unit (MLPU)

Video

Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles
H.265 (MPEG-H Part 2/HEVC) Main Profile
Motion JPEG

Resolution

HDTV 720p 1280x720 to 320x180

Frame rate

Up to 50/60 fps (50/60 Hz) in HDTV 720p

Video streaming

Multiple, individually configurable streams in H.264, H.265 and Motion JPEG
Axis Zipstream technology in H.264 and H.265
Controllable frame rate and bandwidth
VBR/ABR/MBR H.264/H.265

Image settings

Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, polygon privacy masks, electronic image stabilization (EIS), freeze on PTZ, automatic defog, backlight compensation, scene profiles
Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation

Signal-to-noise ratio

>55 dB

Network

Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS¹, TLS¹, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP[®], SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

1. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

System integration

Application Programming Interface

Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com

One-Click Cloud Connection

ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Event conditions

Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature
Edge storage: recording ongoing, storage disruption
I/O: digital input, manual trigger, virtual input
MQTT subscribe

PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready

Scheduled and recurring: scheduled event

Video: live stream open

Event actions

Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap

PTZ: PTZ preset, start/stop guard tour

File upload via FTP, SFTP, HTTP, HTTPS network share and email

Notification via email, HTTP, HTTPS and TCP

MQTT publish

Built-in installation aids

Pixel counter, leveling guide

Analytics

Applications

Included

AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, autotracking 2, active gatekeeper

Basic analytics (not to be compared with third-party analytics): object removed, enter/exit detector, object counter

Supported

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

AXIS Object Analytics

Object classes: humans, vehicles

Scenarios: line crossing, object in area, crossline counting, time in area

Up to 10 scenarios

Other features: triggered objects visualized with trajectories, color-coded bounding boxes and tables
Polygon include/exclude areas

Perspective configuration

ONVIF Motion Alarm event

AXIS Scene Metadata

Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates

Object attributes: confidence, position

Approvals

EMC

EN 50121-4, IEC 62236-4

CISPR 32 Class A, EN 55035, EN 55032 Class A,

EN 61000-3-2, EN 61000-3-3, EN 61000-6-1,

EN 61000-6-2, EN 50121-4, IEC 62236-4

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KCC KN32 Class A, KN35

USA: FCC Part 15 Subpart B Class A

Safety

IEC/EN/UL 60950-1, IS 13252

IEC/EN/UL 60950-22, IEC/EN/UL 62368-1

Environment

IEC/EN 60529 IP66/IP67, NEMA TS 2 (2.2.7-2.2.9),

IEC 62262 IK10, ISO 4892-2, EN 50121-4, IEC 62236-4,

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6,

IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-60,

IEC 60068-2-78, NEMA 250 Type 4X

Network

NIST SP500-267

Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS 140

Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR

Cybersecurity**Edge security**

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption

Hardware: Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), secure keystore, secure boot

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)², IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS², TLS v1.2/v1.3², Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

Documentation*AXIS OS Hardening Guide**Axis Vulnerability Management Policy**Axis Security Development Model*

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resourcesTo read more about Axis cybersecurity support, go to axis.com/cybersecurity**General****Casing**

IP66-, IP67-, NEMA 4X- and IK10-rated Metal casing (aluminum), polycarbonate (PC) clear dome, sunshield (PC/ASA)

Sustainability

PVC free

Power

Axis High PoE 60 W SFP midspan: 100–240 V AC, max 66.1 W

Camera consumption: typical 14 W, max 51 W

Connectors

RJ45 10BASE-T/100BASE-TX PoE, RJ45 Push-pull Connector (IP66/IP67) included

Storage

Support for SD/SDHC/SDXC card

Support for SD card encryption

Support for recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com**Operating conditions**

With 30 W: -20 °C to 50 °C (-4 °F to 122 °F)

With 60 W: -50 °C to 50 °C (-58 °F to 122 °F)

Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)

Arctic Temperature Control: Start-up as low as -40 °C (-40 °F)

Humidity 10–100% RH (condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Humidity 5–95% RH (non-condensing)

Weight

3.75 kg (8.3 lb)

Dimensions

Ø232 x 271 mm (Ø9.13 x 10.7 in)

Included accessories

Axis 90 W SFP Midspan (including power cable), RJ45 Push-pull Connector (IP66), Sunshield

Installation Guide, Windows decoder 1-user license

Optional accessories

Smoked dome cover

AXIS T91 Mounting Accessories, AXIS T8415 Wireless

Installation Tool, AXIS T90 Illuminators, AXIS T8310

Video Surveillance Control Board, multi-user decoder

license pack

Languages

English, German, French, Spanish, Italian, Russian,

Simplified Chinese, Japanese, Korean, Portuguese,

Traditional Chinese, Dutch, Czech, Swedish, Finnish,

Turkish, Thai, Vietnamese

Warranty5-year warranty, see axis.com/warranty

2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).