

AXIS C1510 Network Pendant Speaker

For installation in high ceilings – large

This all-in-one speaker system makes audio announcements smart and easy. For instance, it can be used to make general live or prerecorded voice messages, remotely and proactively warn off intruders, and deliver instructions. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing. This visually attractive pendant speaker is ideal for mounting in high ceilings. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Easy installation with just one network cable \(PoE\)](#)
- > [Scalable and easy to integrate](#)
- > [Remote health testing](#)



AXIS C1510 Network Pendant Speaker

Audio hardware

| | |
|--|---|
| Enclosure | One way enclosure with 6.5 inches broadband dynamic cone speaker |
| Max sound pressure level | 96 dB |
| Frequency response | 60 Hz - 20 kHz |
| Coverage pattern | 130° coaxial |
| Audio input/output | Built-in microphone (can be disabled) External microphone, line in |
| Built-in microphone specification | 50 Hz - 20 kHz |
| Amplifier description | Built-in 7 W Class D amplifier |
| Digital signal processing | Built-in and pre-configured |

Audio management

| | |
|----------------------------------|---|
| AXIS Audio Manager Edge | Built in: <ul style="list-style-type: none"> Content management for music and live/pre-recorded announcements. Scheduling to decide when and where to play specific content. Content prioritization to ensure urgent messages interrupt the schedule. Zone management allowing you to divide up to 200 speakers into 20 zones. Health monitoring for remote discovery of system errors. User management to control who has access to what features. See separate datasheet for more details. |
| AXIS Audio Manager Pro | For larger and more advanced systems. Sold separately. See separate datasheet for specifications. |
| AXIS Audio Manager Center | AXIS Audio Manager Center is a cloud service for remote access and management of multi-site systems. |

Audio software

| | |
|------------------------|---|
| Audio streaming | One-way/two-way with optional half-duplex echo cancellation. Mono. |
| Audio encoding | AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz. |

System on chip (SoC)

| | |
|---------------|--------------------------|
| Model | i.MX 6SoloX |
| Memory | 512 MB RAM, 512 MB Flash |

Network

| | |
|--------------------------|--|
| Network protocols | IPv4/v6 ^a , HTTP, HTTPS, SSL/TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), NTCIP, SIP (Cisco, Avaya, Asterisk) |
|--------------------------|--|

System integration

| | |
|--|--|
| Application Programming Interface | Open API for software integration, including VAPIX®. One-click cloud connection, AXIS Camera Application Platform (ACAP). |
| VoIP | Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32 |
| Intelligent audio | Auto Speaker Test (verification via built-in microphone) |
| Event triggers | Call, virtual inputs, external input, AXIS Camera Application Platform (ACAP) |

| | |
|----------------------|---|
| Event actions | Play audio clip, send SNMP trap, send Auto Speaker Test, status LED, File upload via HTTP, network share and email, Notification via email, HTTP, HTTPS and TCP, external output activation |
|----------------------|---|

| | |
|-----------------------------------|---|
| Built-in installation aids | Test tone verification and identification |
|-----------------------------------|---|

Approvals

| | |
|----------------------|--|
| EMC | CISPR 24, CISPR 35, CISPR 32 Class A, EN 55024, EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN35, KC KN32 Class A, RCM AS/NZS CISPR 32 Class A, VCCI Class A |
| Safety | CAN/CSA C22.2 No. 62368-1, IEC/EN 62368-1, KC-Mark, UL 62368-1 |
| Environment | IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, EC 60068-2-27, IEC/EN 60529 IP4X |
| Cybersecurity | ETSI EN 303 645 |

Cybersecurity

| | |
|-------------------------|---|
| Edge security | Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, secure boot |
| Network security | IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall |
| Documentation | <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity |

General

| | |
|----------------------------------|--|
| Casing | IP40 Baffle: plastic Mesh: surface-treated steel plate Mesh color: white NCS S 1002-B Top cover: plastic Repaintable. For repainting instructions and impact on warranty, contact your Axis partner. Speaker mounting method: hook |
| Power | Power over Ethernet (PoE), IEEE 802.3af/802.3af, Type 1 Class 3 (max 12.95 W) |
| Connectors | RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for 2x supervised configurable I/Os |
| Storage | Support for microSD/microSDHC/microSDXC card Max. size 64 GB For SD card recommendations see www.axis.com |
| Reliability | Designed for 24/7 operation. |
| LED indicators | Status LED, front-facing LED |
| Operating conditions | Temperature: -30 °C to 50 °C (-22 °F to 122 °F) Humidity: 10–85% RH (condensing) |
| Dimensions | Height: 180 mm (7.1 in), Ø 290 mm (11.4 in) |
| Weight | 4100 g (9.0 lbs) |
| Optional accessories | AXIS TC1901 Wire Kit, AXIS Safety Wire 3M For accessories, see axis.com |
| Video management software | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on axis.com/techsup/software |
| Languages | English, German, French, Spanish, Italian |

Warranty 5-year warranty, see [axis.com/warranty](https://www.axis.com/warranty)

a. *Audio synchronization with IPv4 only.*