

Ex e Cable Gland M20 Armored

Cable gland for armored cables hazardous areas

For hazardous area compliance of maintaining a secure connection where the armored cable connects to the camera or junction box. The Ex e cable gland is certified for increased safety. The cable gland suits cable entries with M20x1.5 threads.

> [Certified for ATEX, IECEx](#)

> [Extended temperature range](#)



Ex e Cable Gland M20 Armored

General	
Supported products	Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft)
Cable routing	For cable diameter: 12.5–20.9 mm (0.49–0.82 in) Thread length: 15 mm (0.6 in)
Casing	Nickel-plated brass Color: Metal/silver
Approvals	Environment: IEC/EN 60529 IP66, IP68 Explosion: EN/IEC 60079-0, EN/IEC 60079-7, EN/IEC 60079-31
Certifications	Model key: Cable gland type C2K ATEX: II 2 G Ex e IIC Gb, II 1 D Ex ta IIIC Da
	Certificate: SIRA 13 ATEX 1070 X IECEX: Ex eb IIC Gb, Ex ta IIIC Da Certificate: IECEx SIR 13.0025X -60°C < Tamb < +130°C
	Included accessories Documentation 1 x M20 sealing ring (-60°C < Tamb < +130°C) 1 x counter nut M20 1 x Ex-e cable plug 21mm (red)
	Environmental responsibility: axis.com/environmental-responsibility