

AXIS P1467-LE Bullet Camera

Fully featured, all-around 5 MP surveillance

Based on ARTPEC-8, AXIS P1467-LE delivers excellent image quality in 5 MP. It includes a deep learning processing unit enabling advanced features and powerful analytics based on deep learning on the edge. With AXIS Object Analytics pre-installed, it offers detection and classification of humans, vehicles, and types of vehicles. This IP66/IP67, NEMA 4X, and IK10-rated camera can withstand winds up to 50 m/s. Lightfinder 2.0, Forensic WDR, and OptimizedIR, ensure sharp, detailed images under any light conditions. Furthermore, it includes Axis Edge Vault to protect your Axis device ID and simplify authorization of Axis products on your network.

- > [Lightfinder 2.0, Forensic WDR, OptimizedIR](#)
- > [Analytics with deep learning](#)
- > [Audio and I/O connectivity](#)
- > [Built-in cybersecurity features](#)
- > [Impact and weather resistant](#)



AXIS P1467-LE Bullet Camera

Camera		
Image sensor	1/2.7" progressive scan RGB CMOS	WDR
Lens	Varifocal, 2.8–8 mm, F1.3 Horizontal field of view 106°–38° Vertical field of view 78°–29° Varifocal, remote focus and zoom, P-iris control, IR corrected	Privacy masks Media clip Light control
Day and night	Automatically removable infrared-cut filter	Event conditions Audio: audio clip playing, audio clip currently playing Device status: above operating temperature, above or below operating temperature, below operating temperature, within operating temperature, IP address removed, new IP address, network lost, system ready, ring power overcurrent protection, live stream active Digital audio: digital signal contains Axis metadata, digital signal has invalid signal rate, digital signal missing, digital signal okay Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: digital input, manual trigger, virtual input MQTT subscribe Scheduled and recurring: schedule Video: average bitrate degradation, day-night mode, tampering
Minimum illumination	With WDR and Lightfinder: Color: 0.13 lux, at 50 IRE F1.3 B/W: 0.03 lux, at 50 IRE F1.3 0 lux with IR illumination on	Event actions Day-night mode, overlay text, WDR mode Audio clips: play, stop I/O: toggle I/O once, toggle I/O while the rule is active Illumination: use lights, use lights while the rule is active MQTT: publish Notification: HTTP, HTTPS, TCP and email Record video: SD card and network share SNMP traps: send, send while the rule is active Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email
Shutter speed	1/50000 s to 1/5 s	Built-in installation aids Pixel counter, remote zoom, remote focus, auto rotation
System on chip (SoC)		Analytics
Model	ARTPEC-8	AXIS Object Analytics Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Scenarios: line crossing, object in area, occupancy in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Memory	2 GB RAM, 8 GB Flash	Metadata Object data: Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Attributes: Vehicle color, upper/lower clothing color, confidence, position Event data: Producer reference, scenarios, trigger conditions
Compute capabilities	Deep learning processing unit (DLPU)	Applications Included AXIS Live Privacy Shield AXIS Object Analytics AXIS Video Motion Detection, active tampering, shock detection, audio detection, orientation aid Supported AXIS Perimeter Defender, AXIS Digital Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Video		Approvals
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	EMC EN 55032 Class A, EN 50121-4, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A USA: FCC Part 15 Subpart B Class A Railway: IEC 62236-4
Resolution	2592x1944 (5 MP) to 160x90 1280x720 (720p) to 160x90	Safety IEC/EN 62368-1, IEC/EN 62471, IS 13252
Frame rate	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 720p: 180 fps	Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator	Network NIST SP500-267
Multi-view streaming	Up to 8 individually cropped out view areas	Cybersecurity ETSI EN 303 645
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, motion-adaptive exposure, defogging, barrel distortion correction, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, polygon privacy masks Scene profiles: forensic, vivid, traffic overview	Cybersecurity Edge security Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption
Pan/Tilt/Zoom	Digital PTZ, digital zoom Guard tour (max 100), control queue, fixed orientation aid	
Audio		
Audio streaming	Audio in, simplex, two-way audio via edge-to-edge technology	
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	
Audio input/output	External microphone input or line input, digital audio input, ring power, network speaker pairing	
Network		
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org	
Onscreen controls	Video streaming indicator Day/night shift Defog	

	Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), system-on-chip security (TEE), Axis device ID, secure keystore, signed video, secure boot, encrypted filesystem (AES-XTS-Plain64 256bit)
Network security	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
General	
Casing	IP66/IP67-, NEMA 4X-, and IK10-rated casing Polycarbonate blend and aluminium Color: white NCS S 1002-B For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting .
Sustainability	PVC and BFR/CFR free
Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 5.8 W, max 12.95 W 10–28 V DC, typical 5.2 W, max 12.95 W
Connectors	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T 3.5 mm mic/line in Terminal block for 1 supervised alarm input and 1 output (12 V DC output, max. load 25 mA) DC input

IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (131 ft) or more depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS2 (2.2.7): 74 °C (165 °F) Start-up temperature: -40 °C Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Weight	With weather shield: 1.2 kg (2.65 lb)
Dimensions	Ø132 x 280 mm (Ø5.2 x 11.0 in)
Included accessories	Installation guide, Windows® decoder 1-user license, drill hole template, connector kit, mounting bracket, Torx® L-keys AXIS Weather Shield L
Optional accessories	AXIS T94F01M J-Box/Gang Box Plate, AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket, AXIS T94F01P Conduit Back Box, AXIS Weather Shield K, Axis PoE Midspans For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Warranty	5-year warranty, see axis.com/warranty