

# AXIS Q1615-LE Mk III Network Camera

For analytics with deep learning

AXIS Q1615-LE Mk III combines exceptional imaging and video performance with outstanding hardware and processing capabilities to provide the perfect platform for analytics based on artificial intelligence (AI) with deep learning. A fixed box camera with Q-line functionality, it features an innovative dual chipset that is the basis for nuanced and remarkably granular object classification. This advanced hardware offers a unique opportunity to take advantage of tailor-made third-party applications based on deep learning. The dual chipset also makes it possible for preinstalled AXIS Object Analytics to distinguish between bikes, cars, buses, trucks, and so on.

- > [Powerful AI with deep learning](#)
- > [Granular object classification](#)
- > [Support for 3rd-party AI applications](#)
- > [Edge-based processing for scalability](#)
- > [Premium Axis Q-line camera features](#)



# AXIS Q1615-LE Mk III Network Camera

<b>Camera</b>		<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a>
<b>Image sensor</b>	1/2.8" Progressive scan RGB CMOS	<b>Interface</b>	AXIS Guardian with One-Click Connection One-click cloud connection ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specifications at <a href="http://onvif.org">onvif.org</a>
<b>Lens</b>	Varifocal, IR corrected, CS-mount <b>2 MP (16:9):</b> 2.8–8.5 mm, F1.2 Horizontal field of view: 102°–40° Vertical field of view: 58°–22° i-CS lens	<b>Onscreen controls</b>	Electronic image stabilization Day/night shift Defogging Wide dynamic range Video streaming indicator
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Event conditions</b>	Analytics, external input, supervised external input, edge storage events, virtual inputs through API Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, casing open, IP address removed, network lost, new IP address, shock detection, ring power overcurrent protection, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: live stream open
<b>Minimum illumination</b>	<b>HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder:</b> Color: 0.05 lux, B/W: 0.01 lux at 50 IRE, F1.2 <b>HDTV 1080p 50/60 fps with Forensic WDR and Lightfinder:</b> Color: 0.1 lux, B/W: 0.02 lux at 50 IRE, F1.2 <b>HDTV 1080p 100/120 fps:</b> Color: 0.2 lux, B/W: 0.04 lux at 50 IRE, F1.2 0 lux with IR illumination on	<b>Event actions</b>	MQTT publish Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, zoom preset, defog mode, PTZ control
<b>Shutter speed</b>	1/125000 to 2 s	<b>Data streaming</b>	Event data
<b>System on chip (SoC)</b>		<b>Built-in installation aids</b>	Focus assistant, pixel counter, leveling assistant, camera orientation aid, traffic wizard i-CS: Remote zoom and focus Other lens: Remote back focus
<b>Model</b>	ARTPEC-7	<b>Analytics</b>	
<b>Memory</b>	2048 MB RAM, 1024 MB Flash	<b>AXIS Object Analytics</b>	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>Compute capabilities</b>	Deep learning processing unit (DLPU)	<b>Applications</b>	<b>Included</b> AXIS Object Analytics AXIS Video Motion Detection, active tampering alarm, audio detection <b>Supported</b> AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Video</b>		<b>General</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	<b>Casing</b>	IP66-, IP67-, and NEMA 4X-rated, IK10 impact resistant aluminum enclosure Weathershield with black anti-glare coating Color: White NCS S 1002-B Intrusion alarm switch
<b>Resolution</b>	<b>HDTV 1080p 100/120 fps (no WDR):</b> 1920x1080 to 160x90 <b>HDTV 1080p 50/60 fps (WDR):</b> 1920x1080 to 160x90 <b>HDTV 1080p 25/30 fps (WDR):</b> 1920x1080 to 160x90	<b>Mounting</b>	¼"-20 tripod screw thread Camera stand included
<b>Frame rate</b>	Up to 100/120 fps (50/60 Hz) in 1080p (no WDR)	<b>Sustainability</b>	PVC free
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	<b>Power</b>	Power over Ethernet IEEE 802.3at Type 2 Class 4, max. 25.5 W, typical 13.7 W
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, local contrast, exposure mode, exposure zones, defogging, electronic image stabilization, barrel distortion correction, compression, rotation: auto, 0°, 90°, 180°, 270°, dynamic text and image overlay, polygon privacy mask, mirroring of images Scene profiles: forensic, vivid, traffic overview	<b>IR illumination</b>	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 60 m (196 ft) or more depending on the scene
<b>Pan/Tilt/Zoom</b>	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)	<b>Connectors</b>	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE
<b>Audio</b>			
<b>Audio streaming</b>	Two-way, full duplex		
<b>Audio encoding</b>	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		
<b>Audio input/output</b>	External microphone input, line input, digital input with ring power, balanced microphone, balanced input, automatic gain control, line output 24 bit AD/DA-conversion		
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module		
<b>Supported protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)		
<b>System integration</b>			

	I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA). Two of the ports can be supervised. RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) with PoE Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Approvals</b>	<b>EMC</b> EN 50121-4, IEC 62236-4, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, EAC, KCC KN32 Class A, KN35 <b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, CAN/CSA C22.2 No. 62368-1, IEC 62471 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7–2.2.9) <b>Network</b> NIST SP500-267

<b>Dimensions</b>	201 x 179 x 494 mm (7.9 x 7.1 x 19.4 in)
<b>Weight</b>	6965 g (15.4 lb)
<b>Included accessories</b>	AXIS T94Q01A Wall Mount, Sunshield Connector kit, Resistorx® T20 tool, Installation Guide, Windows® decoder 1-user license
<b>Optional lenses</b>	Lens CS 12–50 mm F1.4 P-Iris 8 MP Lens i-CS 3.9–10 mm F1.5 5 MP Lens i-CS 9–50 mm F1.5 8 MP Ricom 2 MP Lens DC-iris 8–26 mm F0.9
<b>Optional accessories</b>	Axis mounts, Axis lenses, Axis midspans For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Export control</b>	The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit ([openssl.org/](http://openssl.org/)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)