

## AXIS Surveillance Card 256 GB

High endurance microSDXC™ card

AXIS Surveillance Card 256 GB is a high performing edge storage solution optimized for video surveillance. Edge storage enables flexible storage solutions such as de-centralized video recording and may eliminate the need of an onsite server, DVR or NVR. In applications with bandwidth limitations, live video can be viewed in low resolution, while high resolution video is recorded locally on AXIS Surveillance Card 256 GB. Combined with Axis Zipstream technology, even high resolution video can be recorded effectively local on AXIS Surveillance Card 256 GB, both for primary storage or as redundancy for failover recording in case of lost connections.

- > [Optimized for surveillance cameras](#)
- > [Health monitoring ready](#)
- > [SD card adapter included](#)
- > [Axis 5-year warranty](#)



## AXIS Surveillance Card 256 GB

SD card		Operating conditions	-25 °C to 85 °C (-13 °F to 185 °F)
Form factor	microSDXC™ with SD™ card adapter <sup>a</sup>	Storage conditions	-40 °C to 85 °C (-40 °F to 185 °F)
Packaging	The microSDXC™ card and SD™ card adapter are delivered in a jewel case	Sustainability	PVC free
Color	White	Approvals	EN 55032 Class B, EN 55035, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), VCCI Class B, RCM AS/NZS CISPR 32 Class B
Capacity	256 GB <sup>b</sup>	Compatibility	All Axis products with SD card support.
Class	Video Speed Class V30 and UHS Speed Class U3	Warranty	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
Transfer speed read/write	Sequential read performance: Up to 100 MB/s Sequential write performance: Up to 50 MB/s	a. <i>SanDisk is a trademark of Western Digital Corporation, registered in the United States and other countries. microSDXC and SD marks and logos are trademarks of SD-3C, LLC.</i> b. <i>1GB=1,000,000,000 bytes. Actual user storage is less.</i>	
Card dimensions	microSDXC™ card: 15 mm x 11 mm x 1.0 mm (0.59 in x 0.43 in x 0.04 in) SD™ adapter: 24 mm x 32 mm x 2.1 mm (0.94 in x 1.26 in x 0.08 in)		