

AXIS P3268-LV Dome Camera

Indoor 8 MP dome with IR and deep learning

Featuring Lightfinder 2.0, Forensic WDR, and OptimizedIR, AXIS P3268-LV delivers excellent image quality under any light conditions. Based on the latest Axis system-on-chip (SoC), it includes a deep learning processing unit enabling advanced features and powerful analytics based on deep learning on the edge. Thanks to AXIS Object Analytics, it offers detection and classification of humans, vehicles, and types of vehicles—all tailored to your specific needs. Featuring audio and I/O connectivity, you can integrate equipment and extend the value of your system. Furthermore, this robust, IK10-rated, outdoor-ready camera includes built-in cybersecurity to help prevent unauthorized access and safeguard your system.

- > [Excellent image quality in brilliant 4K](#)
- > [Lightfinder 2.0, Forensic WDR, and OptimizedIR](#)
- > [Analytics with deep learning](#)
- > [Audio and I/O connectivity](#)
- > [Built-in cybersecurity features](#)



AXIS P3268-LV Dome Camera

Camera		
Image sensor	1/1.8" progressive scan RGB CMOS	
Lens	Varifocal, 4.3–8.6 mm, F1.5 Horizontal field of view: 100°–53° Vertical field of view: 54°–30° Minimum focus distance: 50 cm (20 in) IR corrected, remote zoom and focus, P-Iris control	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.14 lux at 50 IRE, F1.5 B/W: 0 lux at 50 IRE, F1.5	
Shutter speed	1/8500 s to 1/5 s	
Camera angle adjustment	Pan ±190°, tilt -10 to +80°, rotation ±190°	
System on chip (SoC)		
Model	ARTPEC-8	
Memory	2048 MB RAM, 8192 MB Flash	
Compute capabilities	Deep learning processing unit (DLPU)	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main, and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	3840x2160 to 160x90	
Frame rate	25/30 fps with power line frequency 50/60 Hz	
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming	
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: up to 120 dB depending on scene, white balance, day/night threshold, local contrast, tone mapping, exposure mode, exposure zones, defogging, barrel distortion correction, compression, rotation: 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, privacy masks, polygon privacy mask	
Pan/Tilt/Zoom	Digital PTZ, preset positions	
Audio		
Audio streaming	Audio in, simplex, two-way audio via edge-to-edge technology	
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	
Audio input/output	External microphone input, line input, digital input with ring power, automatic gain control, network speaker pairing	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTCP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	
		Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Onscreen controls	Day/night shift Defogging Wide dynamic range Video streaming indicator IR illumination	
Event conditions	Analytics, external input, supervised external input, virtual inputs through API Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, within operating temperature, IP address removed, new IP address, network lost, system ready, ring power overcurrent protection, live stream active, casing open Digital audio: digital signal contains Axis metadata, digital signal has invalid sample rate, digital signal missing, digital signal okay Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: digital input, manual trigger, virtual input MQTT: subscribe Scheduled and recurring: schedule Video: average bitrate degradation, day-night mode, live stream open, tampering	
Event actions	Overlay text, external output activation, zoom preset, day/night mode, flash status LED, use lights, set defog mode, set WDR mode Calls: end SIP call, make SIP call, answer call I/O: toggle I/O once, toggle I/O while the rule is active MQTT: publish Notification: email, HTTP, HTTPS, TCP, and SNMP trap Pre- and post-alarm video or image buffering for recording or upload Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email	
Data streaming	Event data	
Built-in installation aids	Remote zoom and focus, straighten image, pixel counter, level grid	
Analytics		
AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event	
Applications	Included AXIS Object Analytics AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
General		
Casing	IP52- and IK10-rated Polycarbonate hard coated dome Polycarbonate casing Color: white NCS S 1002-B For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting .	
Mounting	Mounting bracket with junction box holes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount	
Sustainability	PVC free, BFR/CFR free 7% bioplastics	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 5.5 W, max 10.0 W	
Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA)	

	Audio: 3.5 mm mic/line in
IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (130 ft) or more depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 50121-4, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety CAN/CSA C22.2 No. 62368-1 ed. 3, IEC/EN/UL 62368-1 ed. 3, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 IEC/EN 60529 IP52, IEC/EN 62262 IK10 Network

	NIST SP500-267
Dimensions	Height: 107 mm (4.21 in) ø 149 mm (5.87 in)
Weight	800 g (1.8 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, drill template, RESISTORX® T20 screw bit, terminal block connectors, cable gaskets, connector guard
Optional accessories	AXIS TP3201 Recessed Mount, AXIS TP3203 Recessed Mount, AXIS T94K01D Pendant Kit, AXIS T8355 Digital Microphone 3.5 mm, AXIS ACI Conduit Adapters, smoked dome, black casing For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility