

AXIS Camera Station S9302 Workstation

Powerful, plug-and-play workstation

Extensively tested and validated with a wide range of Axis products, this powerful workstation can be used either as a client when connected to the server, or as a server when used in combination with AXIS S30 Series. It supports up to four 4K resolution monitors for optimal overview. With a small form factor, it's ideal wherever space is limited. It comes preloaded with AXIS Camera Station Pro client software. Plus, the integrated AXIS Recorder Toolbox installation wizard ensures quick and easy installation. Furthermore, it includes next business day on-site hardware replacement, 5-year warranty, and one point-of-contact for support.

- > **Scalable and powerful solution**
- > **Supports up to four 4K monitors**
- > **AXIS Camera Station Pro client software included**
- > **Extensive support and 5-year warranty**



AXIS Camera Station S9302 Workstation

Hardware

Processor

Intel® Core™ processor

Memory

16 GB (2x 8 GB)¹

Graphics card

Nvidia® A400

Power

300 W 80+ Platinum
(100–240 V AC, 4.2 A, 50/60 Hz)

Power consumption

Typical: 100 W (341.2 BTU/h)
Maximum: 130 W (443.6 BTU/h)

Connectors

Front side:

1x Universal audio jack
2x USB 2.0
1x USB 3.2
1x USB 3.2 Gen 2x2 Type-C

Rear side:

1x Universal audio jack
1x DisplayPort™ 1.4a
1x Header for remote power button
4x USB 3.2
2x USB 2.0
1x RJ45 Ethernet
3x Mini DisplayPort™ 1.4

Video

Video streaming

Live view:

1 stream x 4K at 30 fps
4 split x 1080p at 30 fps
9 split x 720p at 30 fps
16 split x 360p at 15 fps
25 split x 360p at 15 fps
36 split x 360p at 15 fps
Any combination of the above for maximum four 4K monitors where only two monitors can show streams at 30 fps.

Playback:

Supports the same split scenarios as for live view.
Playback at high speeds can affect the video performance.

Approvals

Supply chain

TAA compliant

EMC

EN 55032 Class B, EN 55035, EN 61000-3-2, EN 61000-3-3, FCC Part 2 & 15 Class B, ISSED ICES-003 Class B, RCM AS/NZS CISPR 32 Class B, KS C 9832 Class B, KS C 9835, VCCI 32-1 Class B, BSMI

Safety

IEC/EN/UL 62368-1, EN 62311, NOM-019-SCFI-1998

Cybersecurity

Edge security

FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
SBOM
Secure Boot

General

Operating system

Microsoft® Windows® 11 IoT Enterprise LTSC 2024²
Built-in operating system recovery: yes
Operating system drive: 256 GB SSD

1. Units produced prior to September 1, 2024: 8 GB (2x 4GB)

2. Units produced prior to July, 2025: Microsoft® Windows® 10 IoT Enterprise LTSC 2021

Operating conditions

0 °C to 45 °C (32 °F to 113 °F)

Humidity 20–80% RH (non-condensing)

Storage conditions

–40 °C to 65 °C (–40 °F to 149 °F)

Humidity 5–95% RH (non-condensing)

Dimensions

290 x 93 x 293 mm (11.4 x 3,7 x 11.5 in)

Weight

4.5 kg (9.8 lbs)

Included accessories

3x Mini DisplayPort™ to DisplayPort™ adapters

Wall plug power cord

Optional accessories

Axis joysticks and control boards

For more accessories, see axis.com

Services

Next Business Day Onsite Support

Warranty

5-year warranty, see axis.com/warranty

Export control

This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

Sustainability

Substance control

RoHS in accordance with EU RoHS Directive 2011/65/EU, as amended by 2015/863/EU.

REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see echa.europa.eu.

Materials

To read more about sustainability at Axis, go to axis.com/about-axis/sustainability







Environmental responsibility

axis.com/environmental-responsibility

Axis Communications is a signatory of the UN Global Compact, read more at unglobalcompact.org

AXIS Camera Station Pro

For details about AXIS Camera Station Pro features and functions, see the AXIS Camera Station Pro datasheet on *axis.com*



Revision	v.01	Revision date	2022-12-05
Paper size	A4	Release date	2022-12-05
Created by	MS	Scale	1:1

Highlighted capabilities

SBOM (Software Bill of Materials)

SBOM is a detailed list of all software components included in an Axis product, including third-party libraries and license information. This list provides customers with insight into the product's software composition, facilitating the management of software security and meeting transparency requirements.

TPM (Trusted Platform Module)

TPM is a security chip integrated into Axis devices to provide a secure environment for storing and processing sensitive data. As a component providing a set of cryptographic features, the TPM protects information from unauthorized access. Specifically, it securely stores the private key, which never leaves the TPM, and processes all related cryptographic operations within the module itself. This ensures the secret part of the certificate remains safe even in the event of a security breach. By enabling features like encryption, authentication, and platform integrity, the TPM contributes to safeguarding the device against unauthorized access and tampering.

Secure Boot

Secure Boot is a security system that ensures only approved software (operating system and embedded switch firmware when applicable) runs on an Axis device at startup. It uses a boot process consisting of an unbroken chain of cryptographically validated software, starting in immutable memory (boot ROM), to verify the authenticity of the software. By establishing the trust chain, Secure Boot guarantees that the device only executes software with a valid digital signature, preventing malicious code from running on the device and ensuring the device boots only with a signed software.

For more information, see axis.com/glossary