

# Axis network door controller



**A1210**

**A1610**

**DOOR CONTROLLER**

<b>Number of doors</b>	One door	Two doors
<b>Application</b>	Compact design - install it anywhere	Ready out of box - indoor & outdoor ready*
<b>Typical installation</b>	Wall mount, DIN rail, custom enclosure	Wall mount, DIN rail, custom enclosure
<b>Product variants</b>	Enclosure: A1210 Barebone: A1210-B 4-door kit: A1214	Enclosure: A1610 Barebone: A1610-B

**ACCESS CONTROL**

<b>Number of credentials</b>	250,000	250,000
<b>Number of event history</b>	250,000	250,000
<b>Secure element</b>	Axis Edge Vault with secure key store	Axis Edge Vault with secure key store
<b>Identification type</b>	Card, PIN, QR code, license plate	Card, PIN, QR code, license plate

**HARDWARE**

<b>Readers</b>	2x OSDP or 1x Wiegand	4x OSDP or 2x Wiegand
<b>Relays</b>	1x Form C relay Dry or wet 12V DC/24V DC)	2x Form C relay Dry or wet (12V DC/24V DC)
<b>Door lock power budget</b>	PoE+ 900mA @12V DC 1600mA @12V	PoE+ 900mA @12V DC 1800mA @12V
<b>I/Os</b>	2x configurable I/Os	6x configurable I/Os
<b>Power supply</b>	PoE+ or DC (12V DC)	PoE+ or DC (10V-28V DC)
<b>Total power budget</b>	PoE+: 1,400mA@12V DC DC: 2,100mA@12V DC	PoE+: 1,300mA@12V DC DC: 2,100mA@12V DC
<b>Operating conditions</b>	0 °C to 70 °C (32 °F to 158 °F)	-40 °C to 70 °C (-40 °F to 158 °F)
<b>Dimensions</b>	144 x 122 x 50 mm (5.7 x 4.8 x 2.0 in)	175 x 175 x 60mm (6.9 x 6.9x 2.4 in)

\*outdoor rated enclosure is required

For more information please visit: [www.axis.com/products/network-door-controllers](http://www.axis.com/products/network-door-controllers)