

## AXIS TU6004-E Cable

### Indoor- and outdoor cable

This flexible and robust indoor/outdoor cable is compatible with AXIS F91 main units, AXIS F21 sensor units, AXIS F41 sensor units, and AXIS F7225-RE Pinhole Sensor. With a 40 mm (1.6 in) bending radius, this high-speed data cable offers a high bandwidth capability to minimize latency between the sensor unit and main unit. It comes in 4 different lengths: 1 m (3 ft), 8 m (26 ft), 20 m (66 ft) and 30 m (98 ft).

- > **Indoor and outdoor rated**
- > **40 mm (1.6 in) bending radius**
- > **1 m (3 ft) cables are sold in pack of 4**
- > **8 m (26 ft) cables are sold in pack of 1 and 4**
- > **20 m (66 ft) and 30 m (98 ft) cables are sold in pack of 1**



## AXIS TU6004-E Cable

### General

#### Casing

IP66-, IP67- and IP6K9K-rated

---

#### Power

Impedance: 50 Ohms

---

#### Frequency

0–3 GHz

---

#### Connectors

SMA  
FAKRA

---

#### Operating conditions

–40 °C to 75 °C (–40 °F to 167 °F)  
Humidity 10–100% RH (condensing)

---

#### Approvals

UL CL2 Sunlight Resistant E335585-T, UN ECE R118

---

#### Dimensions

Color: black  
Length: 1 m (3 ft), 8 m (26 ft), 20 m (66 ft) and 30 m (98 ft)  
ø 5 ±0.1 mm (0.2 in)  
Maximum length of interconnected cables: 30 m (98 ft)  
Bend radius: 40 mm (1.6 in)

---

#### Weight

1 m (3 ft): 40 g (0.09 lb)  
8 m (26 ft): 300 g (0.66 lb)  
20 m (66 ft): 760 g (1.68 lb)  
30 m (98 ft): 1140 g (2.51 lb)

---

#### Compatible products

AXIS F91 main units, AXIS F21 sensor units, AXIS F41 sensor units, AXIS F7225-RE Pinhole Sensor

---

#### Optional accessories

AXIS TU6003 Connector Kit FAKRA

---

#### Warranty

3-year warranty, see [axis.com/warranty](https://www.axis.com/warranty)