

AXIS Camera Station S1116 MT Recorder

Out-of-the box ready server and client for UHD surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1116 MT Recorder

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Playback: 4 x 1080p camera split views or 1 x 4K camera view Supports two monitors.
System scalability	Qualified for up to 32 video channels and 64 doors	Recording Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
Hardware		General
Processor	Intel® Core™ i5	Operating system Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
Memory	8 GB	Operating conditions 0 °C to 45 °C (32 °F to 113 °F)
Storage	Enterprise Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 8 TB (1x8 TB)	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
RAID	RAID levels: 0, 1	Approvals EMC EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Graphic card	Intel® HD Graphics	Dimensions 274 x 154 x 350 mm (10.8 x 6.1 x 13.8 in)
Power	360 W (100 - 240 V AC, 50/60 Hz, 5.0 - 2.5 A)	Weight 7.4 kg (16 lb)
Connectors	Front side: 1x Universal audio jack 2x USB 2.0 1x USB 3.1 1x USB 3.1 Type-C Rear side: 2x USB 2.0 4x USB 3.1 2x DisplayPort™ 1.2 1x Ethernet (RJ45) 1 GbE 1x Audio line out 1x Serial port	Included accessories Power cord, keyboard, mouse
Video		Optional accessories Axis joysticks and control boards For more accessories, see axis.com
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view	Warranty 5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility