

# AXIS Q3515-LV Network Camera

Fixed dome for solid performance in HDTV 1080p

AXIS Q3515-LV is a vandal-resistant fixed dome for demanding locations. Thanks to its top-quality image sensor, along with Forensic WDR, Lightfinder technology and OptimizedIR illumination, the camera provides unparalleled video quality in any light conditions. Electronic image stabilization is instrumental for smooth and steady video when subject to vibrations. The camera offers redundancy between Power over Ethernet and DC power. Video analytics, supervised inputs and digital outputs further support the surveillance assignment.

- > **HDTV 1080p video in full frame rate with Forensic WDR**
- > **Lightfinder and OptimizedIR**
- > **Axis Zipstream technology**
- > **EIS, IK10 vandal resistance, IP52 water and dust protection**
- > **Power with redundancy and configurable I/O ports**



# AXIS Q3515-LV Network Camera

<b>Models</b>	AXIS Q3515-LV 9 mm AXIS Q3515-LV 22 mm	Support for AXIS Dome Microphone A to be mounted inside the casing.
<b>Camera</b>		<b>Network</b>
<b>Image sensor</b>	Progressive scan RGB CMOS 1/2.8"	<b>Security</b>
<b>Lens</b>	Varifocal, Remote focus and zoom, P-Iris control, IR corrected <b>9 mm:</b> 3–9 mm, F1.3 Horizontal field of view: 105°–36° Vertical field of view: 57°–21° <b>22 mm:</b> 9–22 mm, F1.6 Horizontal field of view: 36°–15° Vertical field of view: 19°–9°	Password protection, IP address filtering, IEEE 802.1X (EAP-TLS) network access control <sup>a</sup> , HTTPS <sup>a</sup> encryption, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Supported protocols</b>
<b>Minimum illumination</b>	<b>9 mm: HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder:</b> Color: 0.07 lux at 50 IRE, F1.3; B/W: 0.01 lux at 50 IRE, F1.3 <b>HDTV 1080p 50/60 fps with Forensic WDR and Lightfinder:</b> Color: 0.14 lux at 50 IRE, F1.3; B/W: 0.03 lux at 50 IRE, F1.3 <b>HDTV 1080p 100/120 fps:</b> Color: 0.28 lux at 50 IRE, F1.3; B/W: 0.06 lux at 50 IRE, F1.3 <b>22 mm: HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder:</b> Color: 0.11 lux at 50 IRE, F1.6; B/W: 0.02 lux at 50 IRE, F1.6 <b>HDTV 1080p 50/60 fps with Forensic WDR:</b> Color: 0.22 lux at 50 IRE, F1.6; B/W: 0.04 lux at 50 IRE, F1.6 <b>HDTV 1080p 100/120 fps:</b> Color: 0.44 lux at 50 IRE, F1.6; B/W: 0.08 lux at 50 IRE, F1.6 0 lux with IR illumination on	<b>System integration</b>
<b>Shutter speed</b>	1/66500 to 2 s	<b>Application Programming Interface</b>
<b>Camera angle adjustment</b>	<b>Pan:</b> 360° <b>Tilt:</b> ±80° <b>Rotation:</b> ±175°	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click Cloud Connection ONVIF Profile G, ONVIF Profile S and ONVIF Profile T, specification at <a href="http://onvif.org">onvif.org</a> Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
<b>System on chip (SoC)</b>		<b>Event triggers</b>
<b>Model</b>	ARTPEC-6	Analytics, supervised external inputs, virtual inputs through API, edge storage events, shock detection MQTT subscribe
<b>Memory</b>	1 GB RAM, 512 MB Flash	<b>Event actions</b>
<b>Video</b>		Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, external output activation, play audio clip, zoom preset MQTT publish
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Data streaming</b>
<b>Resolution</b>	1920x1080 to 160x90	Event data
<b>Frame rate</b>	<b>HDTV 1080p (1920x1080) with WDR:</b> Up to 50/60 fps with power line frequency 50/60 Hz <b>HDTV 1080p (1920x1080) without WDR:</b> Up to 100/120 fps with power line frequency 50/60 Hz	<b>Built-in installation aids</b>
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Remote zoom, remote focus, pixel counter, leveling assistant, autorotation, straighten image, traffic wizard
<b>Multi-view streaming</b>	8 individually cropped-out view areas	<b>Analytics</b>
<b>Pan/Tilt/Zoom</b>	Digital PTZ, optical zoom, preset positions <b>9 mm:</b> 3x optical zoom, 2x digital zoom <b>22 mm:</b> 2.4x optical zoom, 2x digital zoom	<b>Applications</b>
<b>Image settings</b>	Scene profiles, compression, color, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, exposure control (including automatic gain control), defogging, exposure zones, fine tuning of behavior at different light levels, Forensic WDR: Up to 120 dB depending on scene, electronic image stabilization, barrel distortion correction, dynamic text and image overlay, privacy masks, mirroring of images, straighten image, rotation: 0°, 90°, 180°, 270°, auto, including corridor format	<b>Included</b> AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection <b>Supported</b> AXIS Digital Autotracking Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner. Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Audio</b>		<b>General</b>
<b>Audio streaming</b>	Full-duplex	<b>Casing</b>
<b>Audio encoding</b>	24-bit LPCM 48 kHz, AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8kHz, Opus 8/16/48 kHz Configurable bitrate	IP52-rated, IK10 impact-resistant casing with polycarbonate hard-coated dome, aluminum base and dehumidifying membrane Encapsulated electronics, captive screws Color: White NCS S 1002-B For repainting instructions of casing or skin cover and impact on warranty, contact your Axis partner.
<b>Audio input/output</b>	Input for external microphone or line-level device Line output Automatic gain control	<b>Mounting</b>
		Mounting bracket with holes for junction boxes (double-gang, single-gang, 4" square, and 4" octagon) and for ceiling and wall mounting ½" (M20) conduit side entry
		<b>Sustainability</b>
		PVC-free
		<b>Power</b>
		Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, typical 5.6 W, max 12.5 W 8–28 V DC, typical 6.3 W, max 13.6 W Power redundancy
		<b>Connectors</b>
		RJ45 10BASE-T/100BASE-TX PoE, terminal block for two configurable supervised inputs / digital outputs (12 V DC output, max load 50 mA), 3.5 mm mic/line in, 3.5 mm line out, terminal block for DC input
		<b>IR illumination</b>
		Optimized IR with power-efficient, long-life 850 nm IR LEDs

	<p><b>9 mm:</b> Range of reach 40 m (130 ft) or more depending on the scene</p> <p><b>22 mm:</b> Range of reach 60 m (200 ft) or more depending on the scene</p>
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Operating conditions</b>	-10 °C to 50 °C (14 °F to 122 °F) Humidity 10–85% RH (non-condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Approvals</b>	<p><b>EMC</b> EN 55032 Class A, EN 55024, IEC/EN 61000-6-1, IEC/EN 61000-6-2, FCC Part 15, Subpart B, Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35</p> <p><b>Safety</b> IEC/EN/UL 60950-1, IEC/EN 62471, IS 13252</p> <p><b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78</p> <p><b>Network</b> IEC/EN 60529 IP52, IEC/EN 62262 IK10</p> <p><b>Network</b> NIST SP500-267</p>
<b>Dimensions</b>	Height: 124 mm

	ø 162 mm
<b>Weight</b>	1.4 kg (3.1 lb)
<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license, drill hole template, cable gaskets, I/O and DC connectors, connector guard, Resistorx® T20 L-key, mounting bracket
<b>Optional accessories</b>	AXIS Q35 Smoked Dome A, AXIS Dome Intrusion Switch B, AXIS Multicable B I/O Audio Power AXIS Q35-V Skin Cover A Black, Axis ACI Conduit Adapters, AXIS T94K01D Pendant Kit, AXIS T94K02L Recessed Mount, AXIS Dome Microphone A, AXIS T83 Microphones, Axis Mounts For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)