

# AXIS Camera Station S1296 Rack Recording Server

## Flexible and scalable recording server

Featuring powerful components, this secure, scalable recording server offers high performance and support for powerful applications and features. It includes AXIS Camera Station licenses and multiple RAID configurations for flexible storage and multiple redundancy configuration. And, a Trusted Platform Module (FIPS 140-2 level 2 certified) ensures secure storage of all cryptographic keys and certificates. Available in two variants with a choice of storage, it comes preloaded with preconfigured software. Plus, all supported products are available in one price list for a one-stop-shop experience. Furthermore, it offers services such as Keep Your Hard Drive, Next Business Day Onsite Support, and a 5-year warranty.

- > [Scalable and powerful solution](#)
- > [Flexible storage options including RAID](#)
- > [Available in 2 variants: 96 TB and 192 TB](#)
- > [96 AXIS Camera Station licenses included](#)
- > [Extensive support and 5-year warranty](#)



# AXIS Camera Station S1296 Rack Recording Server

<b>Models</b>	S1296 Rack 96 TB S1296 Rack 192 TB
<b>Licenses</b>	96 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).
<b>System scalability</b>	Qualified for 192 doors and a recording bitrate up to 1.5 Gbit/s, 150 video channels at 4 MP, 30 fps in a retail scenario. Check AXIS Site Designer for storage estimates. Tested with: 20 live view clients 4 clients performing heavy playback or scrubbing operations For systems with over 100 video channels or a recording bitrate over 1 Gbit/s, we recommend setting the size allocated for recording to 95%.
<b>Hardware</b>	
<b>Processor</b>	Intel® Xeon® Silver
<b>Memory</b>	2x 16 GB
<b>Storage</b>	<b>S1296 Rack 96 TB</b> Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 0 Out-of-the-box storage: 80 TB after RAID 6 Out-of-the-box capacity without RAID: 96 TB (12x8 TB) <b>S1296 Rack 192 TB</b> Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 0 Out-of-the-box storage: 160 TB after RAID 6 Out-of-the-box capacity without RAID: 192 TB (12x16 TB)
<b>RAID</b>	Factory RAID level: 6 Supported RAID levels: 0, 1, 5, 6, 10
<b>Power</b>	2 x 800 W hot-plug redundant power supplies (included) (100–240 V AC, 12–6.3 A, 50/60 Hz)
<b>Connectors</b>	<b>Front side:</b> 1x USB 2.0 1x VGA 1x iDRAC direct port <b>Rear side:</b> 1x USB 2.0 1x USB 3.0 1x VGA 1x iDRAC dedicated Ethernet port 2x RJ45 1 Gbps (Do not use) 2x RJ45 10 Gbps
<b>Video</b>	
<b>Video streaming</b>	Not intended for local viewing of video. Recommended to use Axis workstations.
<b>Cybersecurity</b>	
<b>Documentation</b>	AXIS OS Hardening Guide

*Axis Vulnerability Management Policy*  
*Axis Security Development Model*  
AXIS OS Software Bill of Material (SBOM)  
To download documents, go to [axis.com/support/cybersecurity/resources](https://axis.com/support/cybersecurity/resources)  
To read more about Axis cybersecurity support, go to [axis.com/cybersecurity](https://axis.com/cybersecurity)

## General

<b>Operating system</b>	Microsoft® Windows® 10 IoT Enterprise LTSC 2021 Built-in operating system recovery: yes Operating system drive: 240 GB SSD
<b>Remote server management</b>	iDRAC 9 basic license
<b>Security</b>	Support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
<b>Operating conditions</b>	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	EMC EN 55032 Class A, EN 55024, EN 55035, EN 61000-3-2, EN 61000-3-3, FCC Part 2 and 15 Class A, ISED ICES-003 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835, VCCI 32-1 Class A, BSMI <b>Safety</b> IEC/EN/UL 60950-1, IEC/EN/UL 62368-1, EN 62311, NOM-019-SCFI-1998
<b>Compliance</b>	TAA (Trade Agreements Act)
<b>Dimensions</b>	721.62 x 482 x 87 mm (28.42 x 19 x 3.43 in), 2U chassis <b>Rail sizing:</b> Type: sliding Minimum rail mounting depth: 719 mm (28.31 in) Square-hole rack adjustment range: 631–868 mm (24.85–34.18 in) For more information, see the Dell EMC Enterprise Systems Rail Sizing and Rack Compatibility Matrix
<b>Weight</b>	<b>S1296 Rack 96 TB</b> 22.9kg (50.49 lb) <b>S1296 Rack 192 TB</b> 25.6 kg (56.44 lb)
<b>Included accessories</b>	Dell Ready Rails 2U Sliding Rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
<b>Optional accessories</b>	Axis workstations For more accessories, see <a href="https://axis.com">axis.com</a>
<b>Services</b>	Next Business Day Onsite Support Keep Your Hard Drive
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>

## AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on [axis.com](https://axis.com)