

AXIS TP4601-E Conduit Back Box

IP66/67 rated indoor and outdoor box with conduit entrance

Available in white, impact resistant (IK11) for indoor and outdoor use, AXIS TP4601-E Conduit Back Box offers additional space needed for installation, cables, or other accessories. It's carefully designed to store for example an IP-over-COAX adapter to re-use legacy cabling or a network cable coupler to bridge between rigid and flexible network cables. 3/4" /M25 conduit interface from both side and back. The sealed compartment is IP66/67 rated to withstand challenging outdoor conditions and makes the finished installation aesthetically pleasing. Network cable and extra gaskets are included.

- > Storage space for accessories and cable slack
- > Impact resistant (IK11) against vandalism attempts
- > IP66/67 rated
- > Easy installation
- > 3/4" /M25 conduit interface from both side and back



AXIS TP4601-E Conduit Back Box

| General | | Sustainability | PVC free |
|--------------------|--|----------------------|---|
| Supported products | AXIS P4705-PLVE Network Camera AXIS P4707-PLVE Network Camera | Approvals | Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-6, IEC 60068-2-27, IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X Impact IEC/EN 62262 IK11 |
| Environment | Indoor/outdoor | Included accessories | Installation Guide 3x Gasket Tool mounting RJ45 C M20 Cable 3-5 mm 4x Stainless steel screws (TX20) and washers |
| Mounting | Double Gang Box, Single Gang Box, 4" Octagon Junction Box, 4" Square Junction Box | Optional accessories | AXIS T91B47 Pole Mount, AXIS T94R01B Corner Bracket, AXIS ACI Conduit Adapter 3/4" U-Shape 30 mm, AXIS ACI Conduit Adapter 3/4" NPS, Network cable coupler indoor, Network cable coupler indoor slim, AXIS T6101 Mk II Audio and I/O Interface, AXIS T8645 PoE+ over Coax Compact Kit |
| Casing | Material: powder-coated aluminum casing, stainless steel screws (TX20) Color: white NCS S 1002-B | Warranty | 3-year warranty, see axis.com/warranty |
| Cable routing | Back: 2 cable holes Sides: 3/4" conduit entrances Underside: 4x gaskets C M20 5-9.5 mm Top cover: 2x gaskets C M20 5-9.5 mm | | |
| Maximum load | 2.3 kg (5 lb) | | |
| Dimensions | Height: 53.5 mm (2.11 in) Width: 140.4 mm (5.53 in) Length: 215.1 mm (8.47 in) | | |
| Weight | 1.02 Kg (2.25 lb) | | |