

AXIS P1455-LE Network Camera

Versatile, feature-rich 2 MP surveillance

AXIS P1455-LE offers excellent image quality in HDTV 1080p. Featuring Axis Lightfinder 2.0 and Axis Forensic WDR it delivers true colors and great detail in challenging light or near darkness. AXIS Object Analytics lets you detect and classify humans and vehicles. And, with edge-to-edge technology, it offers smart pairing functionality with Axis Network Speakers. Motion-adaptive exposure significantly reduces the motion blur from approaching or nearby objects, and OptimizedIR enables surveillance in pitch darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis products on your network.

- > [Lightfinder 2.0 and Forensic WDR](#)
- > [OptimizedIR](#)
- > [AXIS Object Analytics](#)
- > [Enhanced security features](#)
- > [Impact and weather resistant](#)



AXIS P1455-LE Network Camera

Camera		Event conditions	Analytics Detectors: live stream accessed, video motion detection, audio detection, day/night mode, shock detection, tampering Hardware: network, temperature Input Signal: digital input port, manual trigger, virtual inputs Storage: disruption, recording System: system ready Time: recurrence, use schedule MQTT subscribe
Image sensor	1/2.8" progressive scan RGB CMOS	Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, day/night mode MQTT publish
Lens	Varifocal, 3-9 mm, F1.6-3.3 Horizontal field of view 114°-37° Vertical field of view 58°-21° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	Built-in installation aids	Pixel counter, remote zoom (3x optical), remote focus, auto rotation
Day and night	Automatically removable infrared-cut filter	Analytics	
Minimum illumination	Color: 0.07 lux, at 50 IRE F1.6 B/W: 0.01 lux, at 50 IRE F1.6 0 lux with IR illumination on	AXIS Object Analytics	Object classes: humans, vehicles Features: line crossing, object in area, time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories, color-coded bounding boxes and tables Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Shutter speed	1/66500 s to 2 s	Metadata	Object data: Classes: humans, faces, vehicles, license plates Confidence, position Event data: Producer reference, scenarios, trigger conditions
System on chip (SoC)		Applications	Included AXIS Object Analytics AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering, shock detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Model	ARTPEC-7	Cybersecurity	
Memory	1024 MB RAM, 512 MB Flash	Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), secure keystore, secure boot
Compute capabilities	Machine learning processing unit (MLPU)	Network security	IEEE 802.1X (EAP-TLS) ^a , IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Video		Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	General	
Resolution	1920x1080 to 160x90	Casing	IP66/IP67-, NEMA 4X-, and IK10-rated casing Polycarbonate blend and aluminium Color: white NCS S 1002-B For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting .
Frame rate	With Forensic WDR: Up to 25/30 fps (50/60 Hz) in all resolutions No WDR: Up to 50/60 fps (50/60 Hz) in all resolutions	Sustainability	PVC free
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 7.7 W, max 12.95 W
Multi-view streaming	Up to 8 individually cropped out view areas	Connectors	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T 3.5 mm mic/line in Terminal block for 1 alarm input and 1 output (12 V DC output, max. load 25 mA)
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, defogging, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, motion-adaptive exposure, barrel distortion correction Scene profiles: forensic, vivid, traffic overview		
Pan/Tilt/Zoom	Digital PTZ, digital zoom		
Audio			
Audio streaming	Audio in, simplex, two-way audio via edge-to-edge technology		
Audio encoding	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		
Audio input/output	External microphone input or line input, digital audio input, network speaker pairing		
Network			
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, user access log, centralized certificate management, Axis Edge Vault, Axis device ID		
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-Click Cloud Connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S and ONVIF [®] Profile T, specification at onvif.org		
Onscreen controls	Day/night shift Defogging Wide dynamic range IR illumination		

IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (131 ft) or more depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55035, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252, IEC 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7–2.2.9) Network

	NIST SP500-267
Weight	With weather shield: 1 kg (2.2 lb)
Dimensions	Ø132 x 260 mm (Ø5.2 x 10.2 in)
Included accessories	Installation guide, Windows® decoder 1-user license, drill hole template, connector kit, mounting bracket, Torx® L-keys AXIS Weather Shield L
Optional accessories	AXIS T94F01M J-Box/Gang Box Plate, AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket, AXIS T94F01P Conduit Back Box, AXIS Weather Shield K, Axis PoE Midspans For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Warranty	5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*