

AXIS Q1932-E Thermal Network Camera

Reliable detection and wide range coverage

The bullet-style, outdoor-ready AXIS Q1932-E optimizes detection performance and perimeter surveillance to meet the most challenging requirements. The thermal resolution of 640x480 and a range of lenses make it easy to detect and identify people, objects and incidents in complete darkness or difficult conditions. A noise filter gives improved thermal image contrast while keeping noise levels low, without adding blur and ghost effects or losing temperature information. AXIS Q1932-E supports two-way audio, cross line detection, Power over Ethernet (IEEE 802.3af) and memory card slot. It is designed to withstand harsh weather conditions and has a built-in heater for the window.

- > [VGA thermal imaging](#)
- > [Intelligent video applications included](#)
- > [Shock detection](#)
- > [Multiple lens options](#)



AXIS Q1932-E Thermal Network Camera

Models	AXIS Q1932-E 10 mm/19 mm/35 mm or 60 mm	Casing	Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B
Camera		Memory	256 MB RAM, 128 MB Flash
Image sensor	Uncooled Micro bolometer 640x480, pixel size: 17 µm Spectral range: 8-14 µm	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 10 W 8-28 V DC: max 11 W 20-24 V AC (50/60 Hz): max 15 VA Power supply not included.
Lens	10 mm: Horizontal field of view: 57°, F1.2 19 mm: Horizontal field of view: 32°, F1.0 35 mm: Horizontal field of view: 18°, F1.2 60 mm: Horizontal field of view: 10°, F1.25	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for power Eight circuit PCB header for two configurable inputs/outputs and audio
Sensitivity	NETD < 70 mK	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Video		Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline and Main Profiles Motion JPEG	Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F)
Resolutions	Sensor is 640x480. Image can be scaled up to 800x600 (SVGA).	Approvals	EN 50121-4, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, IEC 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3 EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR22 Class B, KCC KN22 Class B, KN24
Frame rate	Up to 8.3 fps and 30 fps	Dimensions	344 x 146 mm (13 9/16 x 5 3/4 in)
Video streaming	At least three H.264 and Motion JPEG streams using the same palette, simultaneous and individually configured in max. resolution at 30 fps Controllable frame rate and bandwidth, VBR/MBR H.264	Weight	10/19/35 mm: 2000 g (4.4 lb) 60 mm: 2200 g (4.9 lb)
Image settings	Compression, brightness, contrast, exposure control, rotation, mirroring of images, multiple palettes, text and image overlay, privacy mask Axis' Corridor Format	Included accessories	Torx® T20 screw driver Resistorx® L-key Pipe converter for US, Wall and ceiling mount bracket, RJ45 network cable 5 m (16 ft) Installation Guide, Windows decoder 1-user license
Audio		Optional accessories	AXIS T98A17-VE Surveillance Cabinet, AXIS T94G01P, AXIS T91A47 Pole Mount, AXIS Multicable A I/O Audio, Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch For more accessories, see www.axis.com
Audio streaming	Two-way, full duplex	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Audio input/output	External microphone input or line input, Line output	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Network		Export control	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Environmental responsibility:	www.axis.com/environmental-responsibility
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at www.onvif.org		
Analytics	AXIS Video Motion Detection 4, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap Audio detection		
Event triggers	Analytics, temperature, external input, time scheduled, edge storage events		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering Audio recording to edge storage		
Data streaming	Event data		
General			

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).