

AXIS Q8615-E PTZ Camera

Positioning camera with 1/2" sensor and analytics

This high-performance camera offers HDTV 1080p resolution with 31x optical zoom for outstanding image quality. It can be column-mounted for a continuous, unobstructed 360° panoramic view and a ground-to-sky view from -90° to +45°. Featuring a 1/2" sensor, Forensic WDR, and Lightfinder it ensures sharp, clear images even when in extreme low-light. And it comes with built-in analytics from Axis. For instance, Axis Object Analytics can detect and classify people and vehicles – all tailored to specific needs. It includes an SFP slot to support long-distance fiber connection. Plus, an integrated, long-life silicone wiper ensures cost-effective maintenance.

- > [Superior light sensitivity with Lightfinder](#)
- > [WDR, 31x optical zoom](#)
- > [Support for intelligent analytics](#)
- > [Built-in cybersecurity features](#)
- > [IR illumination as an optional accessory](#)



AXIS Q8615-E PTZ Camera

Variants

AXIS Q8615-E 50 Hz
AXIS Q8615-E 60 Hz

Camera

Image sensor

1/2" progressive scan RGB Outdoor CMOS

Lens

Varifocal, 6.9–214.6 mm, F1.36–4.6
Horizontal field of view: 60.6°–2.0°
Vertical field of view: 36.5°–1.1°
P-Iris control
Minimum focus distance: 1 m (3.3 ft)

Day and night

Automatically removable infrared-cut filter

Minimum illumination

Color: 0.06 lux at 50 IRE F1.36
B/W: 0.001 lux at 50 IRE F1.36

Shutter speed

1/111000 to 1/2 s

Pan/Tilt/Zoom

Pan: 360° endless, 0.05°/s to 120°/s
Tilt (default): -90° to +45°,
Tilt (inverted¹): -45° to +90°
Tilt speed: 0.05°/s to 60°/s
Jerk-free movements at low speed: $\pm 0.01^\circ/\text{s}$ (at 0.05°/s)
Zoom: 31x optical zoom, 12x digital zoom, total 372x zoom
Preset accuracy: 0.05°
256 preset positions, guard tour, control queue, on-screen directional indicator, focus recall, de-icing control, dynamic load balancing

System on chip (SoC)

Model

ARTPEC-7

Memory

2048 MB RAM, 512 MB Flash

Compute capabilities

Machine learning processing unit (MLPU)

Video

Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles
H.265 (MPEG-H Part 2/HEVC) Main Profile
Motion JPEG

Resolution

16:9: 1920x1080 to 320x180

Frame rate

Up to 50/60 fps (50/60 Hz)

Video streaming

Multiple, individually configurable streams in H.264, H.265, and Motion JPEG
Axis Zipstream technology in H.264 and H.265
Controllable frame rate and bandwidth
VBR/ABR/MBR H.264/H.265
Video streaming indicator

Image settings

Saturation, contrast, brightness, sharpness, Forensic WDR – Up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, defogging, barrel distortion correction, electronic image stabilization, compression, dynamic text and image overlay, 32 individual polygon privacy masks including mosaic and chameleon privacy masks

Signal-to-noise ratio

>55 dB

Network

Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS², HTTP/2, TLS², QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, PTP, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

1. The camera housing can be mounted in an inverted configuration if tilting directly upwards is preferred.
2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

System integration

Application Programming Interface

Open API for software integration, including VAPIX®, metadata and AXIS Camera Application Platform (ACAP); specifications at axis.com/developer-community.

One-click cloud connection

ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specifications at onvif.org

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Onscreen controls

Timed wiper

Privacy masks

White light LED

IR illumination

Event conditions

Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, PTZ power failure, storage failure, system ready, within operating temperature

Edge storage: recording ongoing, storage disruption, storage health issues detected

I/O: digital input, manual trigger, virtual input

MQTT: subscribe

PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready

Scheduled and recurring: scheduled event

Video: average bitrate degradation, day-night mode, live stream open

Event actions

Day-night mode

Defog: toggle defog once, use defog filter while the rule is active

Guard tour: run while the rule is active, start

I/O: toggle I/O once, toggle I/O while the rule is active

IR illumination: turn on, use IR lights while the rule is active

MQTT: publish

Notification: HTTP, HTTPS, TCP and email

Overlay text

Preset positions

PTZ autotracking

Recordings: SD card and network share

SNMP trap messages: send, send while the rule is active

Washer

WDR mode

White illumination

Wiper

Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email

Built-in installation aids

Pixel counter

Analytics

Applications

Included

AXIS Object Analytics, AXIS Scene Metadata, AXIS Video Motion Detection, Orientation Aid PTZ, AXIS OSDI Zones, AXIS PTZ Autotracking, active gatekeeper

Supported

AXIS Perimeter Defender, AXIS License Plate Verifier
Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner.

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

AXIS Object Analytics

Object classes: humans, vehicles

Scenarios: line crossing, object in area, crossline counting, time in area

Up to 10 scenarios

Other features: triggered objects visualized with trajectories, color-coded bounding boxes and tables
Polygon include/exclude areas

Perspective configuration

ONVIF Motion Alarm event

AXIS Scene Metadata

Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates

Object attributes: confidence, position

Approvals

EMC

EN 55032 Class A, EN 55035, EN 50121-4,
EN 61000-3-2, EN 61000-3-3, EN 61000-6-1,
EN 61000-6-2

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KS C 9832 Class A, KS C 9835

USA: FCC Part 15 Subpart B Class A

Railway: IEC 62236-4

Safety

CAN/CSA C22.2 No. 62368-1 ed. 3,
IEC/EN/UL 62368-1 ed. 3

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6,
IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78,
IEC 62262 IK10³, IEC/EN 60529 IP66, ISO 4892-2,
NEMA 250 Type 4x, NEMA TS 2 (2.2.7-2.2.9)

Network

NIST SP500-267

Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS 140

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, Axis Cryptographic Module (FIPS 140-2 level 1), AES-XTS-Plain64 256bit SD card encryption

Hardware: Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)⁴,
IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR,
HTTPS/HSTS⁴, TLS v1.2/v1.3⁴, Network Time Security
(NTS), X.509 Certificate PKI, host-based firewall

Documentation

AXIS OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

IP66-, IK10³- and NEMA 4X-rated powder coated aluminum casing

Color: white NCS S 1002-B

Front window: tempered glass with anti-reflective coating

Long-life silicone wiper

Sunshield: high-impact UV-stabilized thermoplastic

Sustainability

PVC free, 18% recycled plastics, , 1% bioplastic

Power

20-28 V AC/DC

Typical: 9.6 W

Max: 204 W

Power loss recovery

TVS 2 kV surge protection

I/O connector

Output voltage: 12 V DC

Max load: 50 mA

Connectors

Network: SFP slot (SFP module not included)⁵

Network: RJ45 10BASE-T/100BASE-TX/1000BASE-T

Power: DC input, terminal block

I/O: 6-pin terminal block with 4 configurable inputs/outputs

Storage

Support for SD/SDHC/SDXC card

Support for SD card encryption (AES-XTS-Plain64 256bit)

Recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com

3. Excluding front window.

4. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

5. If the network link is established via both the SFP and RJ45 connectors, the former acts as the primary link and the latter as the failover link.

Operating conditions

Normal: -50 °C to 55 °C (-58 °F to 131 °F)

Maximum (intermittent): 65 °C (149 °F)

Arctic Temperature Control: start-up at -40 °C (-40 °F)

Start-up temperature: -40 °C

Humidity 10–100% RH (condensing)

Wind speed (sustained): 47 m/s (106 mph), without sunshield > 60 m/s (135 mph)⁶

Storage conditions

-40 °C to 70 °C (-40 °F to 158 °F)

Humidity 5–95% RH (non-condensing)

Dimensions

229 x 411 x 579 mm (9 x 16 x 22.8 in)

Maximum height with 45° tilt upwards: 680 mm (27 in)

Maximum width/depth with 360° pan clearance: 633 mm (25 in)

Effective projected area (EPA): 0.119 m²

Weight

14.4 kg (31.7 lb)

Included accessories

Installation guide, Windows® decoder 1-user license, power connector, I/O connector

AXIS Q8615-E 60 Hz: ferrite

Optional accessories

AXIS T94J01A Wall Mount

AXIS T94N01G Pole Mount

AXIS T95A64 Corner Bracket

AXIS PT IR Illuminator Kit C

AXIS Washer Kit B

AXIS Cable 24 V DC/24–240 V AC 22 m

AXIS T8611 SFP Module LC.LX

AXIS T8612 SFP Module LC.SX

AXIS T8613 SFP Module 1000BASE-T

Power supply DIN PS24 480 W

For more accessories, see axis.com

Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty

6. The values shown are based on results from actual wind tunnel testing. The maximum wind speed when the unit is stationary is not known due to wind speed limit of 60 m/s (135 mph) at the test lab. For drag force calculations, use Effective Projected Area (EPA).