

# AXIS P3245-VE Network Camera

Streamlined outdoor-ready HDTV 1080p fixed dome

AXIS P3245-VE offers excellent image quality in HDTV 1080p under any light conditions. This outdoor-ready, IK10-rated camera features Forensic WDR to provide clarity when there's both dark and light areas in the scene. And, Lightfinder 2.0 delivers images with more life-like colors and sharp images of moving objects. Including a varifocal lens with remote zoom and focus capabilities, it eliminates the need for hands-on fine tuning. This camera features enhanced security functionality to ensure the integrity and authenticity of the camera's firmware. Furthermore, it offers Axis Zipstream with support for H.264/H.265, which significantly reduces bandwidth and storage requirements.

- > [HDTV 1080p video quality](#)
- > [Remote focus and zoom](#)
- > [Lightfinder 2.0 and Forensic WDR](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [Signed firmware and secure boot](#)



# AXIS P3245-VE Network Camera

<b>Camera</b>		Pre- and post-alarm video or image buffering for recording or upload
Image sensor	1/2.8" progressive scan RGB CMOS	Notification: email, HTTP, HTTPS, TCP, and SNMP trap
Lens	Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Remote zoom and focus, P-Iris control, IR corrected	MQTT publish Overlay text, make call
Day and night	Automatically removable infrared-cut filter	<b>Built-in installation aids</b>
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE, F1.8 B/W: 0.02 lux at 50 IRE, F1.8	Pixel counter, remote focus, remote zoom
Shutter speed	1/66500 s to 2 s	<b>Analytics</b>
Camera angle adjustment	Pan ±180°, tilt ±75°, rotation ±175°	<b>Applications</b>
<b>System on chip (SoC)</b>		<b>Included</b> AXIS Object Analytics, Scene metadata AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm
Model	ARTPEC-7	<b>Supported</b> Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/acap">axis.com/acap</a>
Memory	1024 MB RAM, 512 MB Flash	<b>AXIS Object Analytics</b>
Compute capabilities	Machine learning processing unit (MLPU)	<b>Object classes:</b> humans, vehicles <b>Scenarios:</b> line crossing, object in area, crossline counting Up to 10 scenarios <b>Other features:</b> triggered objects visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>Video</b>		<b>Scene metadata</b>
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	<b>Object classes:</b> humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position
Resolution	1920x1080 to 160x90	<b>Approvals</b>
Frame rate	With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz	<b>EMC</b>
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode	EN 55032 Class A, EN 55024, EN 50121-4, EN 61000-6-1, EN 61000-6-2 <b>Australia/New Zealand:</b> RCM AS/NZS CISPR 32 Class A <b>Canada:</b> ICES-3(A)/NMB-3(A) <b>Japan:</b> VCCI Class A <b>Korea:</b> KC KN32 Class A, KC KN35 <b>USA:</b> FCC Part 15 Subpart B Class A <b>Railway:</b> IEC 62236-4
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming	<b>Safety</b>
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252
Pan/Tilt/Zoom	Digital PTZ, preset positions	<b>Environment</b>
<b>Audio</b>		IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78 IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS2 (2.2.7-2.2.9)
Audio features	Voice enhancer	<b>Network</b>
Audio input/output	Two-way audio connectivity through optional AXIS T61 Audio and I/O Interfaces with portcast technology	NIST SP500-267
<b>Network</b>		<b>Cybersecurity</b>
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	<b>Edge security</b>
<b>System integration</b>		Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="https://axis.com">axis.com</a> One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at <a href="https://onvif.org">onvif.org</a> Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX	<b>Network security</b>
Event conditions	Analytics, edge storage events, virtual inputs through API MQTT subscribe	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email	<b>Documentation</b>
<b>General</b>		<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>
<b>Casing</b>		IP66- and NEMA 4X-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.
<b>Mounting</b>		Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
<b>Sustainability</b>		PVC free

<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 3.5 W, max 8 W		ø 149 mm (5.87 in)
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	<b>Weight</b>	With weathershield: 800 g (1.8 lb)
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>	<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license, drill template, Resistorx® T20 L-key, cable gaskets, connector guard Weathershield
<b>Operating conditions</b>	-40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Absolute maximum temperature: 74 °C (165 °F) according to NEMA TS2 2016, 2.2.7 Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)	<b>Optional accessories</b>	AXIS T94M02L Recessed Mount, AXIS T94T01D Pendant Kit, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface, AXIS ACI Conduit Adapters, Axis mounts, smoked dome, black casing For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Dimensions</b>	Without weathershield: Height: 104 mm (4.09 in)	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
		<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>