

# AXIS TU6004-E Cable

## Indoor- and outdoor cable

This flexible and robust indoor/outdoor cable is compatible with AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, and AXIS F7225-RE Pinhole Sensor. With a 40 mm (1.6 in) bending radius, this high-speed data cable offers a high bandwidth capability to minimize latency between the sensor unit and main unit. It comes in 3 different lengths: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft).

- > **Indoor and outdoor rated**
- > **40 mm (1.6 in) bending radius**
- > **1 m (3 ft), 8 m (26 ft), 30 m (98 ft)**
- > **1 m (3 ft) and 8 m (26 ft) cables are sold in pack of 1 and 4**
- > **30 m (98 ft) cable is sold in pack of 1**



## AXIS TU6004-E Cable

| General                     |  |
|-----------------------------|--|
| <b>Casing</b>               | IP66-, IP67- and IP6K9K-rated  |
| <b>Power</b>                | Impedance: 50 Ohms   |
| <b>Frequency</b>            | 0–3 GHz  |
| <b>Connectors</b>           | SMA<br>FAKRA   |
| <b>Operating conditions</b> | –40 °C to 75 °C (–40 °F to 167 °F)<br>Humidity 10–100% RH (non-condensing)   |
| <b>Approvals</b>            | UL CL2 Sunlight Resistant E335585-T, UN ECE R118   |
| <b>Dimensions</b>           | Color: black<br>Length: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft)   |
|                             | $\varnothing$ 5 ±0.1 mm (0.2 in)<br>Maximum length of interconnected cables: ≤than 30 m (98 ft)<br>Bend radius: 40 mm (1.6 in) |
| <b>Weight</b>               | 1 m (3 ft): 40 g (0.09 lb)<br>8 m (26 ft): 300 g (0.66 lb)<br>30 m (98 ft): 1140 g (2.51 lb)                                   |
| <b>Compatible products</b>  | AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, AXIS F7225-RE Pinhole Sensor                           |
| <b>Optional accessories</b> | AXIS TU6003 Connector Kit FAKRA  |
| <b>Warranty</b>             | 3-year warranty, see <a href="https://www.axis.com/warranty">axis.com/warranty</a>   |