

# AXIS A8207-VE Network Video Door Station

Multifunctional door station for better security solutions

AXIS A8207-VE Network Video Door Station combines a fully featured 6 MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID multi-frequency reader, allowing you to integrate with other access control systems. By providing both surveillance and access for visitors and employees, AXIS A8207-VE increases the efficiency while keeping down the number of devices at the door. Interaction is intuitive and accessible, with an induction loop for hearing aid. Analytics, such as motion or sound-based detection, are supported.

- > **6MP wide-angle camera**
- > **Multiple hardware interfaces: audio input/output, relays, HDMI output, RS485**
- > **Easy integration with SIP, VAPIX, and ONVIF**
- > **Analytics support**



# SIP

ONVIF | GS

**HDTV**  
NETWORK VIDEO

# AXIS A8207-VE Network Video Door Station

<b>Camera</b>		
Image sensor	1/2.9" progressive scan RGB CMOS	
Lens	1.56 mm, F2.8 Horizontal field of view: 180° Vertical field of view: 120° Fixed focus, IR corrected, fixed iris	
Minimum illumination	LED lit: 0.0 lux LED unlit (with WDR): 0.7 lux LED unlit (without WDR): 0.55 lux	
Shutter speed	1/143000 s to 2 s with 50 Hz 1/143000 s to 2 s with 60 Hz	
<b>System on chip (SoC)</b>		
Model	ARTPEC-6	
Memory	2048 MB RAM, 512 MB Flash	
<b>Video</b>		
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles Motion JPEG	
Resolution	3072x2048 to 160x90	
Frame rate	Up to 30/25 fps (60/50 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Saturation, contrast, brightness, sharpness, forensic WDR: Up to 120 dB depending on scene, white balance, exposure mode, exposure zones, compression, text and image overlay, privacy masks	
Pan/Tilt/Zoom	Digital PTZ	
<b>Audio</b>		
Audio streaming	Two-way, full duplex Echo cancellation and noise reduction	
Audio encoding	384bit LPCM, AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16 kHz Configurable bit rate	
Audio input/output	Line input, line output, dual built-in microphone (can be disabled) T-coil Built-in speaker 78 dB sound pressure at 1 kHz at 1 m distance (84 dB at 0.5 m / 20 in)	
Amplifier description	Built-in 2 W Class D amplifier	
<b>RFID reader</b>		
Entry authentication	Card, tag, PIN, door code	
Alarm status indication	User feedback for access granted, access denied, keypad, armed, disarmed	
Supported protocols	RS485 (OSDP), Wiegand, VAPIX® reader interface	
Reader technology	Generic 13.56 MHz (MIFARE Classic®, MIFARE Plus® (Level 1), MIFARE DESFire® EV1 and EV2, HID® iCLASS® (UID only)). Proximity 125 kHz (HID® Prox, iCLASS®, EM-42xx, ISOProx II).	
Output formats	Card format: Raw, Wiegand26, Wiegand34, Wiegand37, Wiegand37FacilityCode, Custom Option to Invert byte for card outputs	
<b>Accessibility</b>		
Hearing loop	T-coil 4 W Class D amplifier	
User feedback	Illuminated symbols, indicator stripe, illuminated buttons, audible feedback	
<b>Tampering</b>		
Detection type	Tamper switch, accelerometer (shock detection), video tampering	
<b>Network</b>		
Security	Password protection, IP address filtering, signed firmware, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control,	digest authentication, user access log, centralized certificate management
Supported protocols	IPv4/v6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, SIP, SIPS, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf), STUN, TURN	
<b>System integration</b>		
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Guardian with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at <a href="http://onvif.org">onvif.org</a>	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX Tested with various SIP software such as Cisco, Bria and Grandstream Tested with various PBX softwares such as Cisco, Avaya and Asterisk Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN), Contact list, parallel call forking, sequential call forking, call extension dialing Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32, G.722	
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>	
Event triggers	Analytics, external input, edge storage events, virtual inputs through API Call: DTMF, state, state changes Detectors: audio detection, live stream accessed, shock detection, tampering, PIR, motion alarm Hardware: Casing open, temperature, relays and outputs, network Input Signal: digital input port, manual trigger, virtual inputs MQTT subscribe Storage: disruption, recording System: system ready Time: recurrence, use schedule PTZ: moving, preset reached	
Event actions	Axis door control HDMI Make call: SIP, API Terminate call: SIP, API Record video and audio: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS and TCP External output activation, play audio clip, overlay text, PTZ controls, status LED, WDR mode MQTT publish	
Data streaming	Event data	
<b>General</b>		
Casing	IP66 and NEMA 4X-rated, IK08 impact- and scratch-resistant glass Aluminum casing, polycarbonate (PC) hard-coated dome Color: metallic dark grey	
Sustainability	PVC free	
PIR sensor	Passive infrared (PIR) motion sensor.	
Power	Power in: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, or Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4, or 8-28 V DC min. 25 W Power consumption: typical 8 W, max 22 W Power out: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3: 24 V/0.05 A or 12 V/0.1 A	

	Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4, or 8-28 V DC: 24 V/0.3 A or 12 V/0.7 A Relay rating: 30 V, 1 A
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX, PoE I/O: 6-pin terminal block for 4 alarm inputs/outputs DC input, 2 relays, line out, line in, microHDMI, RS485/Wiegand
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Operating conditions</b>	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 10–100% RH (condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	<b>EMC</b> EN 55032 Class A, EN 55024, EN 61000-6-2, FCC Part 15 Subpart B Class A and Subpart C and Subpart E <b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, UL 293, UL 294 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK08, NEMA 250 Type 4X <b>Other</b> EN 300330, EN 62311, RSS-Gen, RSS-210, EN 301 489-3, EN 303 348 For more information, see the Declaration of Conformity at <a href="http://axis.com">axis.com</a>

<b>Dimensions</b>	H x W x D: 248 x 106 x 51 mm (9 3/4 x 4 3/16 x 2 in)
<b>Weight</b>	1.3 kg (2.9 lbs)
<b>Mounting option</b>	Wall mount, wall mount with conduit pipe, or recessed with AXIS TA8201 Recessed Mount
<b>Included accessories</b>	Installation guide, Torx® TR20 bit, terminal block connectors, connector guard
<b>Optional accessories</b>	AXIS TA8201 Recessed Mount, AXIS A9801 Security Relay, AXIS T8133 Midspan, AXIS TA8601 Conduit Adapter 3/4" NPS, AXIS TA8801 Clear Dome Cover For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Video management software</b>	Video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Languages</b>	English, German, French, Spanish, Italian
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)