

# AXIS P3727-PLE Panoramic Camera

4x2 MP multidirectional camera with IR for 360° coverage

AXIS P3727-PLE offers four channels with 2MP per channel at 30 fps. This multidirectional camera allows for flexible positioning of four varifocal camera heads. Each head can be controlled individually to capture scenes in four directions in wide-angle or zoomed-in views. It includes 360° IR illumination with individually controllable LEDs and an automatic IR cut filter. Plus, remote zoom and focus capabilities ensure fast and accurate installation. AXIS Edge Vault protects your Axis device ID and simplifies authorization of Axis products on your network. Furthermore, AXIS Object Analytics offers highly nuanced object classification and reliable detection with fewer false positives.

- > 4x2 MP at 30 fps per channel
- > 360° IR illumination with individually controlled LEDs
- > AXIS Edge Vault and TPM module
- > AXIS Object Analytics on one channel
- > Edge storage with 2\* microSD card slots



# AXIS P3727-PLE Panoramic Camera

| Camera                            |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image sensor                      | 4 x 1/2.8" progressive scan RGB CMOS                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Lens                              | Varifocal, 3–6 mm, F1.8–2.6<br>4x1080p capture mode:<br>Horizontal field of view: 96°–49°<br>Vertical field of view: 53°–27°<br>Diagonal field of view: 113°–55°<br>Fixed iris, IR corrected, remote zoom and focus                                                                                                                                                                         | open, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature<br>Edge storage: recording ongoing, storage disruption, storage health issues detected<br>I/O: manual trigger, virtual input<br>MQTT subscribe<br>Scheduled and recurring: scheduled event<br>Video: average bitrate degradation, day-night mode, live stream open, tampering |
| Day and night                     | Automatically removable infrared-cut filter                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Minimum illumination              | With Forensic WDR and Lightfinder:<br>Color: 0.17 lux at 50 IRE, F1.8<br>B/W: 0 lux at 50 IRE, F1.8                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Shutter speed                     | 1/32500 s to 2 s with 50 Hz<br>1/32500 s to 2 s with 60 Hz                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Camera angle adjustment           | Pan ±90°, tilt +25 to +95°, rotation –5 to +95°, twist ±20°                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                   |
| System on chip (SoC)              |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Model                             | ARTPEC-7                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Memory                            | 1024 MB RAM, 512 MB Flash                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Compute capabilities              | Machine learning processing unit (MLPU)                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Video                             |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Video compression                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>H.265 (MPEG-H Part 2/HEVC) Main Profile<br>Motion JPEG                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Resolution                        | 4x 1920x1080 (4x 2 MP) to 4x 640x360                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Frame rate                        | Up to 25/30 fps (50/60 Hz)                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Video streaming                   | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG<br>Axis Zipstream technology in H.264 and H.265<br>Controllable frame rate and bandwidth<br>VBR/ABR/MBR H.264/H.265                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Image settings                    | Saturation, contrast, brightness, sharpness, Forensic WDR, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, compression, rotation: 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, polygon privacy masks                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Audio                             |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Audio input/output                | Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology.<br>A 30 W midspan or higher is required between AXIS T61 Audio and I/O Interfaces and AXIS P3727-PLE.                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Network                           |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| IP address                        | One IP address for all channels                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Security                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified) |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Network protocols                 | IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)                                |                                                                                                                                                                                                                                                                                                                                                                                                   |
| System integration                |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Application Programming Interface | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="https://axis.com">axis.com</a><br>One-click cloud connection<br>ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile T, specification at <a href="https://onvif.org">onvif.org</a>      |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Onscreen controls                 | IR illumination<br>Autofocus<br>Privacy mask                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Event conditions                  | Audio: audio clip playing<br>Device status: above operating temperature, above or below operating temperature, below operating temperature, casing                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Event actions                     |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Record video: SD card and network share<br>MQTT publish<br>Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email<br>Notification: email, HTTP, HTTPS, TCP, and SNMP trap<br>Overlay text, play audio clip, day/night mode, status LED, IR illumination, MQTT                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Built-in installation aids        |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Pixel counter, remote focus, remote zoom                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Analytics                         |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| AXIS Object Analytics             | Object classes: humans, vehicles<br>Trigger conditions: line crossing, object in area, time in area <sup>BETA</sup><br>Up to 10 scenarios<br>Metadata visualized with trajectories and color-coded bounding boxes<br>Polygon include/exclude areas<br>Perspective configuration<br>ONVIF Motion Alarm event<br>Available for one channel                                                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Metadata                          |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Object data: Classes: humans, faces, vehicles, license plates<br>Confidence, position<br>Event data: Producer reference, scenarios, trigger conditions                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Applications                      |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Included<br>AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/acap">axis.com/acap</a>                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                   |
| General                           |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Casing                            | IP66–, IP67–, NEMA 4X– and IK09–rated impact-resistant, aluminum and plastic casing with polycarbonate hard-coated dome<br>Color: white NCS S 1002-B<br>Dome intrusion switch<br>For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mounting                          |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Mounting bracket with junction box holes (double-gang, single-gang, 4" square, and 4" octagon)<br>½" (M20) conduit side entry                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Sustainability                    |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | PVC free                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Power                             |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4<br>IR illumination on <sup>b</sup> : Class 4, typical 12.5 W, max 21.7 W<br>IR illumination off <sup>b</sup> : Class 3, typical 6.4 W, Class 4, max 15.0 W                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Connectors                        |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE<br>Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                   |
| IR illumination                   |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Four individually controllable IR with power-efficient, long-life 850 nm IR LEDs<br>Range of reach 15 m (50 ft) or more depending on the scene                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Storage                           |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | Support for microSD/microSDHC/microSDXC card<br>Dual SD cards<br>Support for SD card encryption (AES-XTS-Plain64 256bit)<br>Recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a>                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operating conditions              |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | –30 °C to 50 °C (–22 °F to 122 °F)<br>Humidity 10–100% RH (condensing)<br>Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Storage conditions                |                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                   | –40 °C to 65 °C (–40 °F to 149 °F)                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                   |

|                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals                                                                                                                          | EMC<br>EN 50121-4, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A<br>Safety<br>CAN/CSA-C22.2 No. 60950-22, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC 62471, IS 13252<br>Environment<br>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK09, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)<br>Network<br>NIST SP500-267 | AXIS Surveillance Cards<br>For more accessories, see <a href="https://axis.com">axis.com</a>                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Video management software</b><br>AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Languages</b><br>English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese                                                                                                                                                                                                                                                                                                                                                                          |
|                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Warranty</b><br>5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Dimensions                                                                                                                         | Height: 92 mm (3.6 in)<br>ø 255 mm (10.0 in)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <div>a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="https://openssl.org">openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:eay@cryptsoft.com">eay@cryptsoft.com</a>).</i></div> <div>b. <i>Typical power consumption at ambient temperature 20°C (68°F) and maximum power consumption at -30°C (-22°F)</i></div> <div>c. <i>The camera's tampering alarm doesn't work when mounted in AXIS T94N01L Recessed Mount</i></div> |
| Weight                                                                                                                             | 2.0 kg (4.4 lb)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Included accessories                                                                                                               | Installation guide, Windows® decoder 1-user license, connector guard, screw bit T20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Optional accessories                                                                                                               | AXIS T94N01D Pendant Kit, AXIS T94N01L Recessed Mount <sup>c</sup> , AXIS TP3814-E Black Casing, AXIS TP3815-E Smoked Dome, Axis cabinets                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Environmental responsibility:<br><a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

Environmental responsibility:

[axis.com/environmental-responsibility](https://axis.com/environmental-responsibility)