

AXIS M3005-V Fixed Dome Network Camera

Fixed mini dome with HDTV 1080p performance

The palm-sized AXIS M3005-V is an affordably priced, vandal- and dust-resistant indoor fixed dome camera that supports HDTV 1080p and 2 MP resolution. The factory-focused camera is designed for quick and flexible installation. With its 3-axis camera angle adjustment, it can be mounted on walls or ceilings, and images can be easily leveled. AXIS M3005-V offers a horizontal viewing angle of 118° and supports Axis' Corridor Format for vertically oriented video streams of areas such as corridors, hallways or aisles. Support for AXIS Camera Application Platform enables the installation of intelligent video applications such as people counting. A microSDHC slot enables local video storage.

- > **Ultra-compact, vandal-resistant design**
- > **HDTV 1080p/2 MP**
- > **Corridor Format**
- > **Edge storage**



AXIS M3005-V Fixed Dome Network Camera

Camera		Built-in installation aids	Pixel counter
Image sensor	1/2.7" progressive scan RGB CMOS	General	
Lens	M12 mount, F2.8, Fixed iris, Megapixel resolution 2.8 mm Horizontal angle of view: 118°	Casing	Color: White NCS S 1002-B (for repainting instructions of skin covers, contact your Axis partner), Encapsulated electronics, Captive screws (resitorx 10) IP42 water- and dust-resistant, IK08 impact-resistant, polycarbonate/ABS casing
Light sensitivity	1.5-100000 lux, F2.8	Sustainability	PVC free
Shutter time	1/8000 s to 1/6 s	Memory	256 MB RAM, 128 MB Flash
Camera angle adjustment	Pan ±175°, Tilt 56°, Rotation ±175°	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 1, max. 2.7 W
Video		Connectors	Male RJ45 10BASE-T/100BASE-TX PoE on a 2 m (6.6 ft) network cable, warranty can be maintained even when cable is cut-for more information, contact your Axis partner
Video compression	H.264 Main Profile (MPEG-4 Part 10/AVC), Motion JPEG	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Resolutions	1920x1080 (HDTV 1080p) to 320x240	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 15-85% RH (non-condensing)
Frame rate	25/30 fps with power line frequency 50/60 Hz	Approvals	EN 55022 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1 IEC/EN 60529 IP42, IEC/EN 62262 Class IK08
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/CBR H.264	Dimensions	Ø 100 x 27 mm (Ø 4 x 1.1 in)
Pan/Tilt/Zoom	Digital PTZ	Weight	200 g (0.44 lb)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Backlight compensation, Wide dynamic range – dynamic contrast, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Included accessories	Installation Guide, Windows decoder 1-user license, Drill hole template, Torx L-key
Network		Optional accessories	AXIS T94B01D Pendant Kit AXIS T94B01L Recessed Mount AXIS T94B01M J-Box/Gang plate AXIS T94B01S Mount Bracket Accessory lenses, Skin covers (White/Black)
Security	Password protection, IP address filtering, HTTPS ³ encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Video management software	AXIS Camera Companion, AXIS Camera Station and video management software from Axis' Application Development Partners (not included). For more information, see www.axis.com/products/video/software
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
System integration		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>	
Analytics	Video motion detection, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Environmental responsibility: www.axis.com/environmental-responsibility	
Event triggers	Analytics, Edge storage events		
Event actions	File upload: FTP, HTTP, network share and email Notification: email, HTTP and TCP Video recording to edge storage Pre- and post-alarm video buffering		
Data streaming	Event data		