

AXIS V5938 PTZ Network Camera

Broadcast-quality 4K PTZ camera

AXIS V5938 combines excellent image quality with smooth PTZ control and broadcast-quality audio for professional webcasting. It's compatible with VISCA joysticks and VISCA over IP, making it easy to integrate with your existing AV installations. Offering enhanced security features such as signed firmware and secure boot, it ensures the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with H.264 and H.265 significantly reduces bandwidth and storage requirements without compromising image quality. NDI[®] compliant (license to be bought separately).

- > **UHD 4K at 30 fps and 20x zoom**
- > **Broadcast-quality audio with XLR inputs**
- > **VISCA and VISCA over IP support**
- > **Camstreamer 3-month trial included**
- > **3G-SDI and HDMI outputs**



AXIS V5938 PTZ Network Camera

Camera		THD+N: < 0.03%
Image sensor	Progressive scan RGB CMOS 1/2.5"	Signal-to-Noise ratio: > 85 dB @ 0 dB gain, > 78 dB @ 30 dB gain
Lens	4.4–88 mm, F2.0–3.8 Horizontal field of view: 70.2°–4.1° Vertical field of view: 39.5°–2.3° Autofocus, P-iris control	3.5 mm input Microphone Power 5 V via 2.2 kOhm Unbalanced external microphone Unbalanced line Line input impedance: >10 kOhm Maximum input level: 2.2 Vrms Bandwidth: 20 Hz – 20 kHz (±3 dB), may be limited by sample rate THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB @ 0 dB gain, > 83 dB @ 30 dB gain
Day and night	Automatically removable infrared-cut filter	3.5 mm output 3.5 mm unbalanced stereo output Output impedance: < 100 Ohm, short circuit proof Maximum output level: > 0.707 Vrms Bandwidth: 20 Hz – 20 kHz (±3 dB), may be limited by sample rate THD+N: < 0.03% @ 10 kOhm load Signal-to-Noise ratio: > 87 dB
Minimum illumination	Color: 0.7 lux at 30 IRE F2.0 1 lux at 50 IRE F2.0 B/W: 0.06 lux at 30 IRE F2.0 0.1 lux at 50 IRE F2.0	SDI output Bandwidth: 20 Hz – 20 kHz (±3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB
Shutter speed	1/10000 s to 1 s	HDMI output Bandwidth: 20 Hz – 20 kHz (±3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB
Pan/Tilt/Zoom	Pan: ±170°, 0.2–100°/s Tilt: –20° – 90°, 0.2–90°/s Zoom: 20x Optical, 12x Digital, Total 240x 256 presets positions, Control queue, On-screen directional indicator, Adjustable zoom speed, PTZ response profiles	Network
System on chip (SoC)		Network protocols IPv4/v6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf), HDMI, 3G-SDI, VISCA
Model	ARTPEC-7	System integration
Memory	2 GB RAM, 512 MB Flash	Application Programming Interface Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, ONVIF® Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Video		Event conditions Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, live stream open
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Event actions MQTT publish Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call
Resolution	3840x2160 HDTV 2160p to 160x90 HDMI Output: 2160p@25/30 fps (50/60 Hz) 1080p@25/30/50/60 fps (50/60 Hz) 1080i@50/60 fps (50/60 Hz) 720p@50/60 fps (50/60 Hz) 480p@60 fps (60 Hz) SDI Output: 1080p@25/30/50/60 fps (50/60 Hz) 1080p@50/60 fps (50/60 Hz) dual stream 1080i@50/60 fps (50/60 Hz) 720p@50/60 fps (50/60 Hz)	Data streaming Event data
Frame rate	Up to 30/25 fps (60/50 Hz) in 4K Up to 60/50 fps (60/50 Hz) in all other resolutions	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 HDMI HD-SDI: SMPTE 292 3G-SDI: SMPTE 424 ,SMPTE 425 (3G-SDI mapping supports Level A / Level B dual link mapping)	
Image settings	Saturation, brightness, sharpness, noise reduction, rotation: 0°, 180°, WDR – dynamic contrast, white balance, day/night threshold, exposure zones, backlight compensation, defogging, highlight compensation, electronic image stabilization	
Audio		
Audio streaming	Two-way, stereo HD-SDI: SMPTE ST 299-1 3G-SDI: SMPTE ST 299-2	
Audio encoding	SDI: AES3 24 bit, 48 kHz HDMI: LPCM Network: AAC LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz, Configurable bit rate	
XLR input	2 balanced inputs (left/right) Microphone phantom power 48 V Balanced external microphone Balanced line level Line input impedance: >10 kOhm Maximum input level: 4.4 Vrms Bandwidth: 20 Hz – 20 kHz (±3 dB), may be limited by sample rate	

Built-in installation aids	Pixel counter, leveling guide	Storage	Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Analytics		Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)
Applications	Included AXIS Video Motion Detection, AXIS PTZ Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5 – 95% RH (non-condensing)
Cybersecurity		Approvals	EMC EN 55032 Class A, EN 55024, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, CISPR 24, CISPR 35, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, KC-Markk, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
Edge security	Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot	Dimensions	Height: 180 mm (7.1 in) ø 136 mm (5.4 in)
Network security	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall	Weight	1.5 kg (3.3 lb)
Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity	Included accessories	Power supply, wall/ceiling mount, terminal connector for I/O, installation guide, Windows® decoder user license, Camstreamer 3-month trial
General		Optional accessories	AXIS T8310 Video Surveillance Control Board AXIS VISCA Cable For more accessories, see axis.com
Casing	ASA plastic cover Color: White NCS S 1002-B	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Power	11–13 V DC (12 V power supply included), typical 17.5 W, max 20 W	Warranty	5-year warranty, see axis.com/warranty
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T Terminal block for 1 alarm input and 1 output 3.5 mm stereo mic/line in, 3.5 mm stereo line out XLR-3 (left + right) mic/line in (with 48 V phantom power) HDMI Type A, BNC for SDI DC input RS232 serial connector for VISCA		