

## AXIS Q3527-LVE

### 5 MP dome with enhanced security features

AXIS Q3527-LVE Network Camera is a vandal-resistant fixed dome for harsh environments with enhanced security features. Signed firmware and secure boot ensure the integrity and authenticity of the camera's firmware, while a TPM provides secure storage of its certificates and cryptographic keys. Based on AXIS Q3517-LVE, the top-quality image sensor and advanced technologies such as Lightfinder and Forensic WDR ensures that AXIS Q3527-LVE delivers outstanding video quality in any light condition, even when the camera is subject to vibrations. AXIS Q3527-LVE also offers redundancy between PoE and DC power. Video analytics, supervised inputs, and digital outputs further support the surveillance task.

- > [TPM, FIPS 140-2 level 2 certified](#)
- > [Signed firmware](#)
- > [Secure boot](#)
- > [OptimizedIR and Zipstream](#)
- > [AXIS Guard Suite analytics](#)



# AXIS Q3527-LVE

Camera	
Image sensor	Progressive scan RGB CMOS 1/1.8"
Lens	Varifocal, 4.3-8.6 mm, F1.5 Horizontal field of view: 96° – 50° Vertical field of view: 53° – 29° Remote focus and zoom, P-Iris control, IR-corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	5MP 25/30 fps with WDR and Lightfinder: Color: 0.12 lux at 50 IRE, F1.5; B/W: 0.02 lux at 50 IRE, F1.5 4MP 50/60 fps: Color: 0.24 lux at 50 IRE, F1.5, B/W; 0.04 lux at 50 IRE, F1.5 0 lux with IR illumination on
Shutter speed	1/71 500 s to 2 s
Camera angle adjustment	Pan: 360° Tilt: ±80° Rotation: ±175°

System on chip (SoC)	
Model	ARTPEC-6
Memory	1 GB RAM, 512 MB Flash

Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG
Resolution	3072x1728 to 160x120
Frame rate	5MP with WDR: 25/30 fps with power line frequency 50/60 Hz 4MP without WDR: 50/60 fps with power line frequency 50/60 Hz

Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264
-----------------	--

Multi-view streaming	8 individually cropped-out view areas
----------------------	---------------------------------------

Pan/Tilt/Zoom	Digital PTZ, optical zoom, preset positions
---------------	---

Image settings	Scene profiles, compression, color, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, exposure control (including automatic gain control), defogging, exposure zones, fine tuning of behavior at different light levels, Forensic WDR: Up to 120 dB depending on scene, electronic image stabilization, barrel distortion correction, dynamic text and image overlay, privacy masks, mirroring of images, straighten image, rotation: 0°, 90°, 180°, 270°, auto, including corridor format
----------------	---

Audio	
Audio streaming	Full-duplex
Audio encoding	24-bit LPCM 48 kHz, AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8kHz, Opus 8/16/48 kHz Configurable bitrate
Audio input/output	Input for external microphone or line-level device Line output Automatic gain control

Network	
Security	Password protection, IP address filtering, IEEE 802.1X (EAP-TLS) network access control <sup>a</sup> , HTTPS <sup>a</sup> encryption, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified)
Network protocols	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

System integration	
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click Cloud Connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at <a href="http://onvif.org">onvif.org</a>

Event triggers	Analytics, supervised external inputs, virtual inputs through API, edge storage events, shock detection MQTT subscribe
----------------	---

Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, external output activation, play audio clip, zoom preset MQTT publish
---------------	--

Data streaming	Event data
----------------	------------

Built-in installation aids	Remote zoom, remote focus, pixel counter, leveling assistant, autorotation, straighten image, traffic wizard
----------------------------	--

Analytics	
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>

General	
Casing	IP66-, IP67-, IP6K9K- and NEMA 4X-rated, IK10+ (50 joules) impact-resistant casing with polycarbonate hard-coated dome, aluminum base and dehumidifying membrane Encapsulated electronics, captive screws Color: White NCS S 1002-B For repainting instructions of casing or skin cover and impact on warranty, contact your Axis partner.

Mounting	Mounting bracket with holes for junction boxes (double-gang, single-gang, 4" square, and 4" octagon) and for ceiling and wall mounting ¾" (M25) conduit side entry
----------	---

Sustainability	PVC-free
----------------	----------

Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, typical 6.5 W, max 12.9 W 8–28 V DC, typical 6.9 W, max 14.5 W Power redundancy
-------	---

Connectors	RJ45 10BASE-T/100BASE-TX PoE, terminal block for two configurable supervised inputs / digital outputs (12 V DC output, max load 50 mA), 3.5 mm mic/line in, 3.5 mm line out, terminal block for DC input
------------	--

IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range 40 m (130 ft) or more, depending on the scene
-----------------	--

Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
---------	--

Operating conditions	-50 °C to 60 °C (-58 °F to 140 °F) Start-up: -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
----------------------	--

Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
--------------------	--

Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, IEC/EN 61000-6-1, IEC/EN 61000-6-2, FCC Part 15, Subpart B, Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471, IS 13252
-----------	---

	<b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 NEMA 250 Type 4X, IEC/EN 62262 IK10+ (50J), ISO 20653 IP6K9K IEC/EN 60529 IP66/67 <b>Network</b> NIST SP500-267	AXIS Q35-VE Skin Cover A Black, AXIS ACI Conduit Adapter 3/4" NPS, AXIS T94M01D Pendant Kit including weathershield, AXIS T94M02L Recessed Mount, AXIS T8351 Microphone, Axis Mounts & Cabinets For more accessories, see <a href="http://axis.com">axis.com</a>	
<b>Dimensions</b>	Height: 182 mm including weathershield ø 183 mm	<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Weight</b>	2.0 kg (4.4 lb) including weathershield	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license, drill hole template, cable gaskets, I/O and DC connectors, connector guard, weathershield, Axis U-shape conduit adapter, Resistorx® T20 L-key, mounting bracket	<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Optional accessories</b>	AXIS Q35 Smoked Dome A, AXIS Dome Intrusion Switch B, AXIS Multicable B I/O Audio Power	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="http://www.openssl.org">www.openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</i>	