

AXIS P3245-LVE-3 License Plate Verifier Kit

Easy, cost-effective vehicle access control

AXIS P3245-LVE-3 includes an HDTV 1080p fixed dome camera and comes with AXIS License Plate Verifier preinstalled. This easy-to-install kit verifies license plates against a list of authorized or unauthorized number plates stored in the camera. Processing and storage take place in the camera, so there's no need for expensive servers, and bandwidth requirements are reduced. This vandal-resistant camera includes shock detection, so it's safe to use even when installed at lower, more accessible heights. And Axis OptimizedIR ensures the ideal image settings for license plate reading 24/7. Furthermore, it offers integration with video management systems (VMS) for complex requirements.

- > [All-in-one vehicle access control](#)
- > [Support for allow- and blacklist](#)
- > [Vandal- and weather-resistant](#)
- > [Built-in support for Axis Network Door Controllers](#)
- > [OptimizedIR for recognition in darkness](#)



AXIS License Plate Verifier

Application

Compute platform	Edge
Licenses	AXIS License Plate Verifier license included.
Configuration	Web configuration included
Settings	Define area of interest in scene. Allow- and blocklist logic. Barrier mode: Open to all, open to allowlisted, open to all but blocklisted. Minimum width: 130 pixels for one-row license plates; 70 pixels for two-row license plates. FIFO event log entries including thumbnail image of license plate. Up to 1000 entries on camera storage. Up to 100 000 entries on AXIS Surveillance Cards. Configurable retention time of stored events
Detection range	2.0 to 7.0 m (6.6 to 23 ft)
Vehicle speed	Up to 30 km/h (19 mph)
Detection time	Less than 1 second.

Scenarios

Typical applications	Vehicle access control In Access control, the application monitors entrances and exits of gated areas such as parking areas. The application verifies detected license plates against an allowlist or a blocklist for granting or denying access to an area. Maximum 10,000 license plates in each list. For a scenario where greater functionality and flexibility are required, use AXIS A1001 Network Door Controller. AXIS A1001 with AXIS Entry Manager software supports access rules including schedules and a more detailed event log. Multiple partner software that support a great number of credentials and features are available. License plate recognition in slow speed traffic In Freeflow, the application can detect and read license plates in slow speed traffic on larger access roads, city centers and enclosed areas like campuses, ports or airports. This allows for LPR-forensic search and LPR triggered events in a VMS such as ACS.
-----------------------------	--

System integration

Application Programming Interface	Open API for software integration.
Event streaming	Integrates with camera event management system to enable event streaming to management software and camera actions such as I/O control, notification, and edge storage.
Supported devices	Direct integration with AXIS A1001 Network Door Controller and AXIS A91 Network I/O Relay Modules.

General

Supported countries	For a complete list of supported countries, go to the product page at axis.com
Languages	English

AXIS P3245-LVE-3 License Plate Verifier Kit

Camera	
Image sensor	1/2.8" progressive scan RGB CMOS
Lens	Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Remote zoom and focus, P-Iris control, IR corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE, F1.8 Color: 0.1 lux at 50 IRE, F1.8/F1.6 B/W: 0.02 lux at 50 IRE, F1.8/F1.6; 0 lux with IR illumination on
Shutter speed	1/66500 s to 2 s
Camera angle adjustment	Pan ±180°, tilt ±75°, rotation ±175°
System on chip (SoC)	
Model	ARTPEC-7
Memory	1024 MB RAM, 512 MB Flash
Compute capabilities	Machine learning processing unit (MLPU)
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 to 160x90
Frame rate	With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°
Pan/Tilt/Zoom	Digital PTZ, preset positions
Audio	
Audio streaming	Full duplex
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
Audio input/output	External microphone input, line input, digital input with ring power, line output, automatic gain control Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X (EAP-TLS) ^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware Password protection, IP address filtering, HTTPS ^c encryption, IEEE 802.1X (EAP-TLS) ^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, secure boot Password protection, IP address filtering, HTTPS ^d encryption, IEEE 802.1X (EAP-TLS) ^{af} network access control, digest

authentication, user access log, centralized certificate management, brute force delay protection
Password protection, IP address filtering, HTTPS^e encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, signed firmware, secure boot
Password protection, IP address filtering, HTTPS^f encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, signed firmware
Password protection, IP address filtering, HTTPS^g encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, secure boot
Password protection, IP address filtering, HTTPS^h encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management
Password protection, IP address filtering, HTTPSⁱ encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
Password protection, IP address filtering, HTTPS^j encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, signed firmware
Password protection, IP address filtering, HTTPS^k encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, secure boot
Password protection, IP address filtering, HTTPS^l encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
IP address filtering, HTTPS^m encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, signed firmware, secure boot
Password protection, IP address filtering, HTTPSⁿ encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, signed firmware
Password protection, IP address filtering, HTTPS^o encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, secure boot
Password protection, IP address filtering, HTTPS^p encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management
IP address filtering, HTTPS^q encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
IP address filtering, HTTPS^r encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware
IP address filtering, HTTPS^s encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, secure boot
IP address filtering, HTTPS^t encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, brute force delay protection
IP address filtering, HTTPS^u encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, signed firmware, secure boot
IP address filtering, HTTPS^v encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, signed firmware
IP address filtering, HTTPS^w encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management, secure boot
IP address filtering, HTTPS^x encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, digest authentication, user access log, centralized certificate management
IP address filtering, HTTPS^y encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot

IP address filtering, HTTPS² encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, signed firmware
 IP address filtering, HTTPS^{aa} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection, secure boot
 IP address filtering, HTTPS^{ab} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, brute force delay protection
 IP address filtering, HTTPS^{ac} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, signed firmware, secure boot
 IP address filtering, HTTPS^{ad} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, signed firmware
 IP address filtering, HTTPS^{ae} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management, secure boot
 IP address filtering, HTTPS^{af} encryption, IEEE 802.1X (EAP-TLS)^{af} network access control, user access log, centralized certificate management

Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^{af} , TLS ^{af} , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf) IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^{af} , TLS ^{af} , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)
--------------------------	--

System integration

Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
--	---

Event conditions	Analytics, external input, supervision of input, edge storage events, virtual inputs through API, MQTT subscribe
-------------------------	--

Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap MQTT publish Overlay text, external output activation, play audio clip, make call
----------------------	--

Data streaming	Event data
-----------------------	------------

Built-in installation aids	Pixel counter, remote focus, remote zoom OptimizedIR with adjustable IR illumination intensity
-----------------------------------	---

Analytics

Applications	Included AXIS License Plate Verifier, AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap .
---------------------	---

Cybersecurity

Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot
----------------------	---

Network security	IEEE 802.1X (EAP-TLS) ^{af} , HTTPS/HSTS ^{af} , TLS v1.2/v1.3 ^{af} , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
-------------------------	---

Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
----------------------	---

General	
Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.
Mounting	Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
Sustainability	PVC free
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 6.4 W, max 11.3 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA) Audio: 4-pin 2.5 mm (0.098 in) terminal block for audio in and out Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 15 m (50 ft) or more depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Maximum temperature according to NEMA TS2 (2.2.7): 74 °C (165 °F) -40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–85% RH (non-condensing) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252, IEC/EN 62471 Environment IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78 IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9) Network NIST SP500-267
Dimensions	Without weathershield: Height: 104 mm (4.09 in) ø 149 mm (5.87 in)
Weight	With weathershield: 800 g (1.8 lb)
Included accessories	Installation guide, Windows [®] decoder 1-user license, drill template, Resistorx [®] T20 L-key, terminal block connectors, cable gaskets, connector guard, weathershield
Optional accessories	AXIS T94M02L Recessed Mount, AXIS T94T01D Pendant Kit, AXIS T94M01D Pendant Kit, AXIS Dome Intrusion Switch C, AXIS TP3804-E Metal Casing White, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface, AXIS ACI Conduit Adapters, Axis mounts and microphones, smoked dome, black casing For more accessories, see axis.com .
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms .
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese

