

AXIS C1510 Network Pendant Speaker

For installation in high ceilings—large

This all-in-one speaker system makes audio announcements smart and easy. For instance, it can be used to make general live or prerecorded voice messages, remotely and proactively warn off intruders, and deliver instructions. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processor (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing. This visually attractive pendant speaker is ideal for mounting in high ceilings. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Easy installation with just one network cable \(PoE\)](#)
- > [Scalable and easy to integrate](#)
- > [Remote health testing](#)



AXIS C1510 Network Pendant Speaker

Audio hardware		
Enclosure	One way enclosure with 6.5 inches broadband dynamic cone speaker	Notification via email, HTTP, HTTPS and TCP, external output activation
Max sound pressure level	96 dB	
Frequency response	60 Hz - 20 kHz	
Coverage pattern	130° coaxial	
Audio input/output	Built-in microphone (can be disabled) External microphone, Line in	
Built-in microphone specification	50 Hz - 20 kHz	
Amplifier description	Built-in 7 W Class D amplifier	
Digital signal processing	Built-in and pre-configured	
Audio management		
AXIS Audio Manager Edge	Built in: – Content management for music and live/pre-recorded announcements. – Scheduling to decide when and where to play specific content. – Content prioritization to ensure urgent messages interrupt the schedule. – Zone management allowing you to divide up to 200 speakers into 20 zones. – Health monitoring for remote discovery of system errors. – User management to control who has access to what features. See separate datasheet for more details.	
AXIS Audio Manager Pro	For larger and more advanced systems. Sold separately. See separate datasheet for specifications.	
Audio software		
Audio streaming	One-way/two-way with optional half-duplex echo cancellation. Mono.	
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	
System on chip (SoC)		
Model	i.MX 6SoloX	
Memory	512 MB RAM, 512 MB Flash	
Network		
Network protocols	IPv4/v6 ^a , HTTP, HTTPS, SSL/TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), NTCP, SIP (Cisco, Avaya, Asterisk)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX®, One-click cloud connection, AXIS Camera Application Platform (ACAP).	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	
Intelligent audio	Auto Speaker Test (verification via built-in microphone)	
Event triggers	Call, virtual inputs, external input, AXIS Camera Application Platform (ACAP)	
Event actions	Play audio clip, send SNMP trap, send Auto Speaker Test, status LED, File upload via HTTP, network share and email,	
Built-in installation aids	Test tone verification and identification	
Cybersecurity		
Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot	
Network security	IEEE 802.1X (EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, IP address filtering	
Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity	
General		
Casing	IP40 Baffle: plastic Mesh: Surface-treated steel plate Mesh color: Off-white (RAL 9010 or equivalent) Top cover: Plastic Repaintable. For repainting instructions and impact on warranty, contact your Axis partner. Speaker mounting method: Hook	
Power	Power over Ethernet (PoE), IEEE 802.3af/802.3af, Type 1 Class 3 (max 12.95 W)	
Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for 2x supervised configurable I/Os	
Storage	Support for microSD/microSDHC/microSDXC card Max. size 64 GB For SD card recommendations see www.axis.com	
Reliability	Designed for 24/7 operation.	
LED indicators	Status LED, front-facing LED	
Operating conditions	-30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–85% RH (condensing)	
Approvals	EMC CISPR 24, CISPR 35, CISPR 32 Class A, EN 55024, EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN35, KC KN32 Class A, RCM AS/NZS CISPR 32 Class A, VCCI Class A Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, EC 60068-2-27, IEC/EN 60529 IP4X Safety CAN/CSA C22.2 No. 62368-1, IEC/EN 62368-1, KC-Mark, UL 62368-1	
Dimensions	Height: 180 mm (7.1 in), Ø 290 mm (11.4 in)	
Weight	4100 g (9.0 lbs)	
Optional accessories	AXIS TC1901 Wire Kit, AXIS Safety Wire 3M For accessories, see axis.com	
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on axis.com/techsup/software	
Languages	English, German, French, Spanish, Italian	
Warranty	5-year warranty, see axis.com/warranty	

a. Audio synchronization with IPv4 only.