


## AXIS M3057-PLVE Network Camera

6 MP outdoor-ready dome with 360° panoramic view and IR illumination

AXIS M3057-PLVE Network Camera delivers outstanding video in any light conditions, using Axis-developed Forensic WDR and Lightfinder technologies. With its integrated, automatically adaptable OptimizedIR illumination, this versatile camera even sees in the dark. The camera offers 360° overview as well as dewarped views. AXIS M3057-PLVE is vandal resistant (IK10) and discreetly designed. The optional black skin, which is also easily repaintable, can be used to further blend the camera into its environment. The camera has good capacity for analytics. It comes factory-focused and is designed for easy installation.

- > [6 MP sensor](#)
- > [OptimizedIR illumination](#)
- > [Lightfinder technology](#)
- > [Forensic WDR](#)
- > [Zipstream for reduced bandwidth and storage](#)



2048 x 2048  
3072 x 2048

# AXIS M3057-PLVE Network Camera

<b>Camera</b>		ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specification at <a href="http://onvif.org">onvif.org</a> Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
<b>Image sensor</b>	6 MP (3072x2048) 1/1.8" progressive scan RGB CMOS	<b>Event triggers</b> Analytics, supervised external input, virtual inputs through API, edge storage events, open casing
<b>Lens</b>	Fixed iris, fixed focus, IR corrected, 1.6 mm, F2.0 Horizontal field of view: 185° Vertical field of view: 185°	<b>Event actions</b> Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Data streaming</b> Event data
<b>Minimum illumination</b>	Color: 0.16 lux at 50 IRE F2.0 B/W: 0.03 lux at 50 IRE F2.0 0 lux with IR illumination on	<b>Built-in installation aids</b> Pixel counter, digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views
<b>Shutter speed</b>	1/100 000 s to 2 s	<b>Analytics</b>
<b>Camera angle adjustment</b>	Rotation n ±180°	<b>Applications</b> Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm Supported AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>System on chip (SoC)</b>		<b>General</b>
<b>Model</b>	ARTPEC-6	<b>Casing</b> IP66- and NEMA 4X-rated, IK10 impact-resistant casing in polycarbonate and aluminium, with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: White NCS S 1002-B For repainting, use the optional skin cover. Contact your Axis partner for instructions.
<b>Memory</b>	2 GB RAM, 512 MB Flash	<b>Sustainability</b> PVC-free
<b>Video</b>		<b>Power</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 7.7 W, max 12.95 W
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Connectors</b> Shielded RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 supervised alarm input and 1 digital output (12 V DC output, max. load 25 mA) HDMI type D <sup>®</sup> Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
<b>Resolution</b>	Overview: 2048x2048 to 160x160 Panorama: 2560x960 to 192x72 Double panorama: 2560x1920 to 256x144 Quad view: 2560x1920 to 256x144 View area 1-4, 16:9: 1920x1080 to 256x144, 4:3: 1920x1440 to 320x240 Panorama corner left/right: 2368x1184 to 192x72 Double panorama corner: 2048x2048 to 320x240 Corridor: 2560x1920 to 256x144	<b>IR illumination</b> Optimized IR with with power-efficient, long-life 850 nm IR LEDs with adaptable illumination intensity Range of reach 20 m (66 ft) or more depending on scene
<b>Frame rate</b>	360° overview only, up to 2048x2048 without WDR: 50/60 fps @ 50/60 Hz 360° overview and dewarped views up to max resolution with WDR: up to 25/30 fps @ 50/60 Hz	<b>Storage</b> Support for microSD/microSDHC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	<b>Operating conditions</b> -40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)
<b>Multi-view streaming</b>	360° overview, dewarped panorama, double panorama, corridor and quad views. Up to 4 individually cropped out and dewarped view areas. All different views can be streamed simultaneously. When streaming 4 dewarped view areas and one 360° overview in max resolution: up to 14 fps per stream	<b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>HDMI output</b>	HDMI 1080p @ 50/60 fps (50/60 Hz)	<b>Approvals</b> EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60721-3-5 Class 5M3 (vibration and shock), IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X Network NIST SP500-267
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, local contrast, white balance, exposure control (including automatic gain control) exposure zones, fine tuning of behavior at different light levels, forensic WDR: up to 120 dB depending on scene, dynamic text and image overlay, polygon privacy masks, mirroring of images, rotation: 0°, 180°, including Corridor Format	<b>Dimensions</b> Height: 66 mm (2.6 in)
<b>Pan/Tilt/Zoom</b>	Digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views, preset positions, guard tour	
<b>Audio</b>		
<b>Audio input/output</b>	Two-way audio connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	
<b>Network</b>		
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	
<b>Supported protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, HDMI, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	
<b>System integration</b>		
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection	

	ø 149 mm (5.87 in)
<b>Weight</b>	770 g (1.7 lb)
<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license, drill hole template, cable gaskets, connector guard, I/O connector, Resistorx® T20 L-key, mounting bracket, cable hole lid, view protector
<b>Optional accessories</b>	AXIS T94T02D Pendant Kit with weathershield, AXIS T94K01D Pendant Kit, AXIS T94S02L Recessed Mount Kit, AXIS M30 Skin Cover A Black, Axis Mounts Et Cabinets, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface For more accessories, see <a href="http://axis.com">axis.com</a>

<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Polish, Portuguese, Traditional Chinese
<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- b. *Make sure that the cable has a slim connector plug*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)