


ExCam XF Q1785 Explosion-Protected Network Camera

First-class fixed box for hazardous areas

ExCam XF Q1785 Explosion-Protected Network Camera is an easy-to-install and easy-to-integrate camera. It delivers superb zoomed-in detail you expect from a top-of-the-line fixed box camera from Axis. The electronic image stabilization greatly improves video quality where the camera is subject to vibrations. The camera is adapted for explosion-prone applications with ATEX, IECEx, EAC Ex, and IA certifications. With PoE support for plug-and-play installation, ExCam XF Q1785 offers significant savings. Lightfinder and Forensic WDR technologies ensure perfect balance in scenes with strong variations in light, even in poor light. Suitable for onshore, offshore, marine, and heavy industrial environments.

- > [Certified for ATEX, IECEx, EAC Ex, and IA; Zones 1, 2, 21, and 22; Groups IIC and IIIC](#)
- > [Cost-efficient installation with PoE](#)
- > [HDTV 1080p with 32x optical zoom](#)
- > [Lightfinder and WDR technologies](#)
- > [Electronic image stabilization \(EIS\)](#)



ExCam XF Q1785 Explosion-Protected Network Camera

Camera		Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap
Image sensor	1/2.8" progressive scan RGB CMOS	General	
Lens	Varifocal 4.3–137 mm, F1.4–4.0 Horizontal field of view: 60°–2.3° Vertical field of view: 39°–1.3° Autofocus	Casing	IP68-rated, ASTM 316L (EN 1.4404) stainless steel casing for maximum corrosion protection Wiper included De-icing control ^b Casing manufactured and certified by Samcon Prozessleittechnik GmbH, www.samcon.eu
Minimum illumination	Color: 0.16 lux at 50 IRE F1.4 B/W: 0.03 lux at 50 IRE F1.4	Sustainability	PVC free
Shutter speed	1/66500 s to 1 s	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 7.7 W, max 12.95 W 24 V DC, max 40 W 24 V DC is required for operating at temperatures below 0 °C (32 °F) and for wiper functionality
System on chip (SoC)		Connectors	EXTB-3 Junction Box ExCam: 10 terminal clamp UT 2.5 2 conductor terminal USLKG 5
Model	ARTPEC-6	Storage	Pre-installed AXIS Surveillance microSDXC Card 128 GB Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Memory	1024 MB RAM, 512 MB Flash	Operating conditions	-60 °C to 60 °C (-76 °F to 140 °F) Maximum temperature (intermittent): 75 °C (167 °F) Humidity 10-100% RH (condensing)
Video		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Approvals	EMC EN 55032 Class A, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 62479, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11 Safety IS 13252 Environment IEC/EN 60529 IP68 Explosion DIN EN/IEC 60079-0, DIN EN/IEC 60079-1, DIN EN/IEC 60079-7, DIN EN/IEC 60079-31, TR CU 012/2011, GOST R IEC 60079-0, GOST IEC 60079-1, GOST R IEC 60079-7, GOST R IEC 60079-31 Network NIST SP500-267
Resolution	1920x1080 HDTV 1080p (16:9) to 160x120 (4:3) Maximum pixel density with 32x optical zoom: 25 m (82 ft): 1912 px/m 50 m (164 ft): 956 px/m 250 m (820 ft): 191 px/m	Certifications	Camera: Model key: T08-VA2.3.K3.B0R5-LLH-005.A-T ATEX: II 2 G Ex db IIC T5 Gb, II 2 D Ex tb IIIC T95°C Db Certificate: TÜV 18 ATEX 8218X IECEX: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Certificate: IECEX TUR 18.0023X IA: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Certificate: MASC MS/18-3256X EAC Ex: 1Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Series: T8, Model: T08-VA2.3 Certificate: RU C-DE.AB61.B.00381/19 EXTB-3 Junction Box ExCam: Model key: T12-3M20 ATEX: II 2 G Ex eb IIC T5 Gb, Ex II 2 D Ex tb IIIC T95°C Db IP66 Certificate: PTB 99 ATEX 3103 IECEX: Ex e IIC T5 Gb, Ex IIIC T95°C Db IP66 Certificate: IECEX PTB 06.0026 EAC Ex: 1Ex e IIC T5 Gb X, Ex tb IIIC T95°C Db X Certificate: RU C-DE.AA71.B.00120 PESO: Ex db IIC T6 Gb Certificate: A/P/HQ/KA/104/5735
Frame rate	With WDR: Up to 25/30 fps (50/60 Hz) in all resolutions Without WDR: Up to 50/60 fps (50/60 Hz) in all resolutions	Dimensions	396 x 135 x 171 mm (15 9/16 x 5 5/16 x 6 3/4 in)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Weight	11.1 kg (24.5 lb)
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, defogging, white balance, exposure mode, exposure zones, compression, mirroring of images, electronic image stabilization, barrel distortion correction, text and image overlay, dynamic text and image overlay, privacy masks Rotation: auto, 0°, 90°, 180°, 270° including Corridor Format Scene profiles: forensic, vivid, traffic overview, backlit entrance		
Pan/Tilt/Zoom	Digital ptz Zoom: 32x Optical, 12x Digital, Total 384x Preset positions		
Network			
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection		
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org		
Event triggers	Analytics, supervised external input, edge storage events, virtual inputs through API, shock detection MQTT subscribe		
Event actions	Pre- and post-alarm video buffering File upload: FTP, SFTP, HTTP, HTTPS, network share and email MQTT publish Notification: email, HTTP, HTTPS, TCP and SNMP trap		
Data streaming	Event data		
Built-in installation aids	Remote zoom, pixel counter, leveling assistant, autorotation		
Analytics			

Included accessories	Installation Guide, Windows decoder 1-user license, Weathershield ExCam XF, ASKDP03-T Cable ExCam 5 m (16 ft), EXTB-3 Junction Box ExCam, AXIS Surveillance microSDXC Card 128 GB	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available on www.axis.com/vms
Optional accessories	Wall Mount ExCam XF, Pole Mount ExCam XF Non-armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft), Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft) Ex Connection Rail 4 PoE PS 24, Ex Connection Rail 8 PoE PS 24 For more accessories, see www.axis.com	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Optional accessories	Wall mount Pole mount Pole top mount Composite cable tail Wooden crate For more accessories, see www.axis.com	Warranty	5-year warranty, see www.axis.com/warranty

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

b. *Internal heaters to defrost ice build-up, activated by HTTP API (VAPIX).*

Environmental responsibility:
www.axis.com/environmental-responsibility