

AXIS FA54 Main Unit

High-performance multi-view surveillance with Forensic WDR

AXIS FA54 supports up to four AXIS FA Sensor Units, enabling cost-effective and highly discreet surveillance of four closely situated areas with one system. The main unit can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. Ideal for retail applications, AXIS FA54 also supports quad view streaming and has an HDMI™ port for connection to a surveillance or public view monitor. The unit uses Forensic WDR (wide dynamic range) that is tuned for motion. Axis Zipstream video compression technology reduces bandwidth and storage requirements.

- > Full frame rate HDTV 1080p streams from four sensor units
- > Forensic WDR
- > Quad view stream, Axis Zipstream and Corridor Format
- > HDMI output, two-way audio, I/Os, two microSD card slots, 12 V DC



AXIS FA54 Main Unit

Video		AXIS Video Motion Detection Active tampering alarm, audio detection Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	1920x1080 (1080p) to 480x270	
WDR	Forensic WDR	
Frame rate	In 1080p: up to 25/30 fps (50/60 Hz)	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 Quad view, max 1080p resolution HDMI	
HDMI output	Single camera source Picture-in-picture Quad view Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure value, exposure control, exposure zones, local contrast, rotation, Corridor Format, text and image overlay, privacy mask, mirroring of images, Picture-in-picture, rotation in quad view	
Audio		
Audio streaming	Two-way, full-duplex and half-duplex	
Audio encoding	AAC-LC 8/16/32/48 kHz, max 128 kbit/s G.711 PCM 8 kHz 64 kbit/s G.726 ADPCM 8 kHz 32 kbit/s or 24 kbit/s Opus 8/16/48 kHz, max 128 kbit/s Configurable bit rate	
Audio input/output	External microphone input or line input, line output	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	
Event triggers	Analytics, external inputs Edge storage events MQTT subscribe	
Event actions	File upload: email, FTP, HTTP, HTTPS, network share MQTT publish Notification: email, HTTP, HTTPS and TCP Pre- and post-alarm video buffering Video and audio recording to edge storage, play audio clip, external output activation	
Built-in installation aids	Pixel counter	
Data streaming	Event data	
Analytics		
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard	
General		
Casing	Aluminum Plastic	
Sustainability	PVC-free	
Memory	1024 MB RAM, 512 MB Flash	
Power	12 V DC, typical 14 W, max 30 W	
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T RJ12 for sensor units 6-pin terminal block for four configurable inputs/outputs (12 V DC output), max load 50 mA Two 3.5 mm mic/line in, 3.5 mm line out DC connector for 12 V DC input HDMI type A	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10-85% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)	
Approvals	EMC a55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, ICES-003 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IS 13252 Environment EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27 Network NIST SP500-267	
Dimensions	202 x 102 x 31 mm (7 15/16 x 4 x 1 1/4 in)	
Weight	442 g (0.98 lb)	
Included accessories	Installation Guide, Windows [®] decoder 1-user license, power supply Rubber feet, mounting brackets	
Optional accessories	AXIS F7315 Cable White 15 m For more accessories, see axis.com	
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	5-year warranty, see axis.com/warranty	
<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p> <p>Environmental responsibility: axis.com/environmental-responsibility</p>		