

## **AXIS Camera Station S1232 Rack Recording Server**

Flexible and scalable recording server

Featuring powerful components, this secure, scalable recording server offers high performance and support for powerful applications and features. It includes AXIS Camera Station licenses and multiple RAID configurations for flexible storage and multiple redundancy configuration. And, a Trusted Platform Module (FIPS 140-2 level 2 certified) ensures secure storage of all cryptographic keys and certificates. Available in two variants with a choice of storage, it comes preloaded with preconfigured software. Plus, all supported products are available in one price list for a one-stop-shop experience. Furthermore, it offers services such as Keep Your Hard Drive, Next Business Day Onsite Support, and a 5-year warranty.

- > Scalable and powerful solution
- > Flexible storage options including RAID
- > Available in 2 variants: 16 TB and 32 TB
- > 32 AXIS Camera Station licenses included
- > Extensive support and 5-year warranty



www.cxis.com T10180498/EN/M5.2/2302

	AXIS Camera Station \$123	32 RUCK R	recording server
Models	S1232 Rack 16 TB S1232 Rack 32 TB 32 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold		Axis Security Development Model AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecu- rity/resources
	separately).		To read more about Axis cybersecurity support, go to axis.com/cybersecurity
System scalability	Qualified for 128 doors and a recording bitrate up to 500 Mbit/s, 64 video channels at 4 MP, 30 fps in a retail scenario. Check	General	
	AXIS Site Designer for storage estimates. Tested with: 15 live view clients	Operating system	Microsoft® Windows® 10 IoT Enterprise LTSC 2021 Built-in operating system recovery: yes Operating system drive: 240 GB SSD
Hardware	3 clients performing heavy playback or scrubbing operations	Remote server management	iDRAC 9 basic license
Processor	Intel® Xeon® E processor	Security	Support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Storage	2x 8 GB  S1232 Rack 16 TB  Hot swappable Enterprise Class HDD  Total HDD slot: 4  Free HDD slot: 0  Out-of-the-box storage: 12 TB after RAID 5  Out-of-the-box capacity without RAID: 16 TB (4x4 TB)  S1232 Rack 32 TB  Hot swappable Enterprise Class HDD  Total HDD slot: 4  Free HDD slot: 0  Out-of-the-box storage: 24 TB after RAID 5	Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 8–80% RH (non-condensing)
		Storage conditions	Humidity 5–95% RH (non-condensing)
		Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, FCC Part 2 and 15 Class A, ISED ICES-003 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835, VCCI 32-1 Class A, BSMI Safety IEC/EN/UL 62368-1, EN 62311, NOM-019-SCFI-1998
DAID	Out-of-the-box capacity without RAID: 32 TB (4x8 TB)	Compliance	TAA (Trade Agreements Act)
RAID	Factory RAID level: 5 Supported RAID levels: 0, 1, 5, 6, 10	Dimensions	599 x 482 x 43 mm (23.59 x 19 x 1.7 in), 1U chassis Rail sizing: Type: static Minimum rail mounting depth: 622 mm (24.49 in) Square-hole rack adjustment range: 608–879 mm (23.94–34.61 in) For more information, see the Dell EMC Enterprise Systems Rail Sizing and Rack Compatibility Matrix
Power	2 x 600 W hot-plug redundant power supplies (included) (100–240 V AC, 7.1–3.6 A, 50/60 Hz)		
Power consumption Connectors	Average: 127 W (433 BTU/h) Maximum: 158 W (539 BTU/h) Front side:		
	1x USB 2.0 1x iDRAC direct port	Weight	12.9 kg (28.44 lb)
	Rear side: 1x USB 2.0 1x USB 3.2 1x VGA 1x Serial port	Included accessories	Dell Ready Rails 1U Static Rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
		Optional accessories	Axis workstations For more accessories, see axis.com
	1x iDRAC dedicated Ethernet port 2x RJ45 1 Gbps	Services	Next Business Day Onsite Support Keep Your Hard Drive
Video		Warranty	5-year warranty, see axis.com/warranty
Video streaming	Not intended for local viewing of video. Recommended to use Axis workstations.	Export control	This product is subject to export control regulations, and you should always comply with all applicable national and
Cybersecurity			international export or re-export control regulations.
Documentation	AXIS OS Hardening Guide Axis Vulnerability Management Policy		

## **AXIS Camera Station**

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on *axis.com* 

