

# AXIS Camera Station S1116 MT Recorder

Out-of-the box ready server and client for UHD surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



## AXIS Camera Station S1116 MT Recorder

<b>Licenses</b>	16 AXIS Camera Station core licenses included, can be upgraded with additional licenses (sold separately)	<b>Playback:</b> 4 x 1080p camera split views or 1 x 4K camera view Supports two monitors.
<b>System scalability</b>	Qualified for up to 32 video channels and 64 doors	<b>Recording</b>
<b>Hardware</b>		Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
<b>Processor</b>	Intel® Core™ i5	<b>General</b>
<b>Memory</b>	8 GB	<b>Operating system</b>
<b>Storage</b>	Enterprise Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 8 TB (1x8 TB)	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
<b>RAID</b>	RAID levels: 0, 1	<b>Operating conditions</b>
<b>Graphic card</b>	Intel® HD Graphics	0 °C to 45 °C (32 °F to 113 °F)
<b>Power</b>	360 W (100 - 240 V AC, 50/60 Hz, 5.0 - 2.5 A)	<b>Storage conditions</b>
<b>Connectors</b>	<b>Front side:</b> 1x Universal audio jack 2x USB 2.0 1x USB 3.1 1x USB 3.1 Type-C <b>Rear side:</b> 2x USB 2.0 4x USB 3.1 2x DisplayPort™ 1.2 1x Ethernet (RJ45) 1 GbE 1x Audio line out 1x Serial port	<b>Approvals</b>
<b>Video</b>		EMC EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, <b>Safety</b> IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
<b>Video streaming</b>	Live view: Up to 25 camera split views or 1 x 4K camera view	<b>Dimensions</b>
		274 x 154 x 350 mm (10.8 x 6.1 x 13.8 in)
		<b>Weight</b>
		7.4 kg (16 lb)
		<b>Included accessories</b>
		Power cord, keyboard, mouse
		<b>Optional accessories</b>
		Axis joysticks and control boards For more accessories, see <a href="http://axis.com">axis.com</a>
		<b>Warranty</b>
		5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

## AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on [axis.com](http://axis.com)

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)