

AXIS P3248-LV Network Camera

Streamlined 4K dome for any light

AXIS P3248-LV offers excellent image quality in brilliant 4K resolution. This IK10-rated camera features Axis Lightfinder 2.0 and Axis Forensic WDR to deliver true colors and great detail in challenging light or near darkness. It includes OptimizedIR for surveillance in complete darkness and motion-adaptive exposure significantly reduces motion blur from approaching or nearby objects. AXIS Object Analytics lets you detect and classify humans and vehicles. And, thanks to two-way audio and I/O connectivity, you can add audio analytics and integrate peripheral equipment. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis products on your network.

- > [4K resolution at 30 fps](#)
- > [Lightfinder 2.0 and Motion-adaptive exposure](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [AXIS Object Analytics](#)
- > [Enhanced security features](#)



AXIS P3248-LV Network Camera

Camera		
Image sensor	1/1.8" progressive scan RGB CMOS	
Lens	Varifocal, 4.3–8.6 mm, F1.5 Horizontal field of view: 100°–53° Vertical field of view: 54°–30° Remote zoom and focus, P-Iris control, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.14 lux at 50 IRE, F1.5 B/W: 0 lux at 50 IRE, F1.5	
Shutter speed	1/8500 s to 1/5 s	
Camera angle adjustment	Pan ±180°, tilt ±75°, rotation ±175°	
System on chip (SoC)		
Model	ARTPEC-7	
Memory	2048 MB RAM, 512 MB Flash	
Compute capabilities	Machine learning processing unit (MLPU)	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	3840x2160 to 160x90	
Frame rate	25/30 fps with power line frequency 50/60 Hz	
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), motion-adaptive exposure, exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ, preset positions	
Audio		
Audio streaming	Full duplex	
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	
Audio input/output	External microphone input, line input, digital input with ring power, line output, automatic gain control Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, signed video, Axis Edge Vault, Axis device ID	
Supported protocols	IPv4, IPv6, USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	
		Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
Event conditions	Analytics, external input, supervision of input, edge storage events, virtual inputs through API MQTT subscribe	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap MQTT publish Overlay text, external output activation, play audio clip, make call	
Data streaming	Event data	
Built-in installation aids	Pixel counter, remote focus, remote zoom OptimizedIR with adjustable IR illumination intensity	
Analytics		
AXIS Object Analytics	Object classes: humans, vehicles Trigger conditions: line crossing, object in area, time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories and color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event	
Applications	Included AXIS Object Analytics AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm Audio detection Supported AXIS Live Privacy Shield Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
General		
Casing	IP52-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.	
Mounting	Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread	
Sustainability	PVC free	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 8.2 W, max 11.4 W	
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA) Audio: 4-pin 2.5 mm (0.098 in) terminal block for audio in and out Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (130 ft) or more depending on the scene	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A,	

	<p>ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35</p> <p>Safety IEC/EN/UL 62368-1, IS 13252, IEC/EN 62471</p> <p>Environment IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78 IEC/EN 60529 IP52, IEC/EN 62262 IK10</p> <p>Network NIST SP500-267</p>	<p>and I/O Interface, AXIS T6112 Audio and I/O Interface, AXIS TP3901 Microphone Kit, AXIS ACI Conduit Adapters, Axis mounts and microphones, smoked dome, black casing For more accessories, see axis.com</p>
Dimensions	Height: 103 mm (4.06 in) ø 149 mm (5.87 in)	
Weight	720 g (1.6 lb)	
Included accessories	Installation guide, Windows® decoder 1-user license, drill template, Resistorx® T20 L-key, terminal block connectors, cable gaskets, connector guard	
Optional accessories	AXIS TP3201 Recessed Mount, optionally with AXIS Device Microphone B, AXIS T94K01D Pendant Kit, AXIS Dome Intrusion Switch C, AXIS T6101 Audio	
		<p>Video management software AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms</p> <p>Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese</p> <p>Warranty 5-year warranty, see axis.com/warranty</p> <p>a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p> <p>Environmental responsibility: axis.com/environmental-responsibility</p>