

## AXIS T92E20 Outdoor Housing

Smart features for a wide range of environments

AXIS T92E20 protects Axis fixed network camera in adverse conditions. An internal shell stores heat in cold environments, and fan ventilation transfers excess heat to the outer chassis for efficient cooling in hot environments. Arctic Temperature Control ensures that the camera can start up even at -40 °C (-40 °F) following a power failure. One-cable installation with Power over Ethernet or High Power over Ethernet connection. AXIS T92E20 is IP66- and NEMA 4X-rated against the ingress of dust, rain, high pressure water jets and damage from external ice formation. It is also IK10-rated for protection against impact and vandal acts.

- > **Arctic Temperature Control**
- > **Dual shell**
- > **IP66- and NEMA 4X-rated**
- > **IK10-rated**
- > **One-cable installation**



## AXIS T92E20 Outdoor Housing

### Supported products

AXIS M1124/M1125  
Indoor models of AXIS P13 Series  
AXIS Q1604/Q1614/Q1615  
AXIS Q1775

### Casing

Aluminium casing, polycarbonate sunshield and cable cover  
IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure  
Color: White NCS 1002-B

### Power

Power over Ethernet (PoE) IEEE 802.3af or High Power over Ethernet (High PoE)  
Power supply not included

### Environment

Indoor/Outdoor

### Operating conditions

#### AXIS M1124/M1125:

PoE IEEE 802.3af/at: -30 °C to 50 °C (-22 °F to 122 °F),  
down to -35 °C (-31 °F) with High PoE IEEE 802.3at  
Humidity 15-100% RH (condensing)

#### Indoor models of AXIS P13 Series:

PoE IEEE 802.3af/at: -30 °C to 50 °C (-22 °F to 122 °F),  
down to -40 °C/°F with High PoE IEEE 802.3at  
Humidity 15-100% RH (condensing)

#### AXIS Q1604/Q1614:

PoE IEEE 802.3af/at: -30 °C to 50 °C (-22 °F to 122 °F),  
down to -40 °C/°F with High PoE IEEE 802.3at  
Humidity 15-100% RH (condensing)

#### AXIS Q1615:

PoE IEEE 802.3af/at: -30 °C to 60 °C (-22 °F to 140 °F),  
down to -40 °C/°F with High PoE IEEE 802.3at  
Humidity 15-100% RH (condensing)

#### AXIS Q1775:

PoE IEEE 802.3af/at: -30 °C to 45 °C (-22 °F to 113 °F),  
down to -40 °C/°F with High PoE IEEE 802.3at  
Humidity 15-100% RH (condensing)

### Approvals

EN 55022 Class B, EN 61000-3-2, EN 61000-3-3,  
EN 55024, EN 61000-6-1, EN 61000-6-2,  
FCC Part 15 Subpart B Class B, ICES-003 Class B,  
VCCI Class B, RCM AS/NZS CISPR 22, EN 60950-22,  
IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6,  
IEC 60068-2-27, IEC/EN 62262 IK10, EN 62368-1

### Weight

2.5 kg (5.5 lb)

### Sustainability

PVC free, BFR/CFR free

### Included accessories

AXIS T94Q01A Wall Mount  
AXIS T92E Camera Holder Plate C  
Cable Gland M20x1.5, RJ45  
Front glass kit  
Sunshield Kit  
Electronics kit, board including fan and heater  
2x short Ethernet cables  
Installation Guide, Screw driver torx 20

### Optional accessories

AXIS T94R01P Conduit Back Box  
AXIS Bird Control Spike  
AXIS T8120 Midspan 15 W 1-port  
AXIS T8133 Midspan 30 W 1-port  
YP3040 Pan-Tilt Motor

### Warranty

Axis 3-year warranty, [www.axis.com/warranty](http://www.axis.com/warranty)