

AXIS T94S01L Recessed Mount

Swift and effortless ceiling installation

AXIS T94S01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations of indoor Axis fixed dome cameras. It features a patent-pending single-screw ceiling attachment design, which makes the installation quick and easy without having to remove the ceiling tile. Axis fixed dome camera attached to the recessed mount is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring.

- > **Cost-effective mount for Axis fixed dome cameras**
- > **Recessed ceiling installation made quick and easy**
- > **Enables sleek and discreet video surveillance**



AXIS T94S01L Recessed Mount

General

Supported products

AXIS P32-V/-LV Mk II Network Camera Series

Casing

Material: plastic

Color: white NCS S 1002-B

Sustainability

PVC free

Mounting

Recessed in drop ceilings

Environment

Indoor

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Approvals

Safety

IEC/EN/UL 60950-1

Environment

IEC 60068-2-2, IEC 60068-2-6 (vibration),

IEC 60068-2-27 (shock), IEC/EN 62262 IK08, REACH,

RoHS, WEEE

Dimensions

Outer dimensions: 252 x 179 x 146 mm

(9.9 x 7.0 x 5.7 in)

Dimensions when recess-mounted with a camera: Ø

179 mm (7.0 in), height 65 mm (2.6 in)

Weight

300 g (0.7 lb)

Maximum load

600 g (1.3 lb)

Cable routing

Top: cable hole

Included accessories

Installation Guide

Optional accessories

AXIS Safety Wire 3 m

For more accessories, see www.axis.com

Warranty

3-year warranty, see axis.com/warranty

