

AXIS TU6004-E Cable

Indoor- and outdoor cable

This flexible and robust indoor/outdoor cable is compatible with AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, and AXIS F7225-RE Pinhole Sensor. With a 40 mm (1.6 in) bending radius, this high-speed data cable offers a high bandwidth capability to minimize latency between the sensor unit and main unit. It comes in 3 different lengths: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft).

- > **Indoor and outdoor rated**
- > **40 mm (1.6 in) bending radius**
- > **1 m (3 ft), 8 m (26 ft), 30 m (98 ft)**
- > **1 m (3 ft) and 8 m (26 ft) cables are sold in pack of 1 and 4**
- > **30 m (98 ft) cable is sold in pack of 1**



AXIS TU6004-E Cable

General

Casing

IP66-, IP67- and IP6K9K-rated

Power

Impedance: 50 Ohms

Frequency

0–3 GHz

Connectors

SMA
FAKRA

Operating conditions

–40 °C to 75 °C (–40 °F to 167 °F)
Humidity 10–100% RH (condensing)

Approvals

UL CL2 Sunlight Resistant E335585-T, UN ECE R118

Dimensions

Color: black
Length: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft)
ø 5 ±0.1 mm (0.2 in)
Maximum length of interconnected cables: 30 m (98 ft)
Bend radius: 40 mm (1.6 in)

Weight

1 m (3 ft): 40 g (0.09 lb)
8 m (26 ft): 300 g (0.66 lb)
30 m (98 ft): 1140 g (2.51 lb)

Compatible products

AXIS F91 main units, AXIS F21 sensor units,
AXIS F4105-LRE Dome Sensor, AXIS F7225-RE Pinhole
Sensor

Optional accessories

AXIS TU6003 Connector Kit FAKRA

Warranty

3-year warranty, see [axis.com/warranty](https://www.axis.com/warranty)