

AXIS T94K02L Recessed Mount

Discreet installation in drop ceilings

AXIS T94K02L Recessed Mount is designed for indoor drop ceiling installations, and is suitable for AXIS P32-V/-LV series, AXIS P33/-V/-LV series, AXIS Q35-V/-LV series network cameras. The recessed mount is applicable for indoor environments and is suitable for installation in air-handling (plenum) spaces as the enclosure is made of metal alloy with both 1/2" (M20) and 3/4" (M25) conduit holes for protected cable routing.

- > Supports a wide range of indoor fixed dome cameras
- > Quick and easy indoor drop ceiling installations
- > Support for 1/2" (M20) and 3/4" (M25) conduits



AXIS T94K02L Recessed Mount

General		EN 50581	
Supported products	AXIS P32-V/-LV Series AXIS P33-V/-LV Series AXIS Q35-V/-LV Series	Dimensions	Height: 123 mm (4 27/32 in) Cover ring ø 196 mm (7 23/32 in) Ceiling tile hole ø 168 mm (6 5/8 in)
Mounting	Recessed in ceiling tiles	Weight	700 g (1.54 lb)
Casing	Enclosure: Chromated aluminum alloy in natural color Cover ring: High-impact engineering polymer in white NCS S 1002-B	Included accessories	Installation Guide, drill template, Gasket C M20, kit for changing between compatible cameras
Sustainability	PVC free	Optional accessories	AXIS Safety wire 3m
Environment	Indoor	Warranty	Axis 3-year warranty, see www.axis.com/warranty
Cable routing	Back: Cable conduit holes 1/2" and 3/4"	Environmental responsibility: axis.com/environmental-responsibility	
Approvals	IEC/EN 60950-1 IEC/EN 60950-22		