

## AXIS D2110-VE Security Radar

Reliable area protection with 180° coverage 24/7

AXIS D2110-VE Security Radar is a smart network-based security device that uses advanced radar technology to deliver wide 180° coverage. Thanks to built-in analytics developed using machine learning and deep learning, it can accurately detect, classify and track people and vehicles with a low false alarm rate. Featuring PoE-out it's easy to connect and power an additional device, such as a camera for visual verification or a network horn speaker for deterrence. Furthermore, smart coexistence functionality allows the use of multiple radars close to each other. For instance, it's possible to mount two radars back-to-back for complete 360° coverage.

- > **Extensive 180° area coverage**
- > **Built-in analytics**
- > **Low false alarm rate 24/7**
- > **Smart coexistence functionality**
- > **PoE-out to power additional devices**



# AXIS D2110-VE Security Radar

## Radar

### Profiles

Area monitoring  
Road monitoring

### Sensor

Phased array FMCW (Frequency Modulated Continuous Wave)

### Object data

Range, direction, velocity, object type

### Frequency

24.05–24.25 GHz

### RF transmit power

<100 mW (EIRP)  
License free. Unharmful radio-waves.

### Recommended mounting height

3.5 m (11 ft)<sup>1</sup>

### Detection range

**Area Monitoring Profile:** 3–60 m (10–200 ft) when detecting a person  
3–85 m (10–280 ft) when detecting a vehicle  
**Road Monitoring Profile:** 30–60 m (98–197 ft) at 105 km/h (65 mph)  
Check the user manual for the recommended positioning

### Radial speed

**Area Monitoring Profile:** up to 55 km/h (34 mph)  
**Road Monitoring Profile:** up to 105 km/h (65 mph)

### Field of detection

Horizontal: 180°

### Speed accuracy

+/- 2 km/h (1.25 mph)

### Distance accuracy

0.7 m (2.3 ft)

### Angle accuracy

1°

### Spatial differentiation

3 m (9 ft)<sup>2</sup>

### Data refresh rate

10 Hz

### Coverage

5600 m<sup>2</sup> (61000 sq ft) for persons  
11300 m<sup>2</sup> (122000 sq ft) for vehicles

### Coexistence zone

Frequency band: 24 GHz  
Radius: 350 m (1148 ft)  
Recommend number of radars: up to 6

### Object classification

Humans, vehicles, unknown

### Radar controls

Multiple detection zones, line crossing detection with one or two lines, exclude zones with filters for short-lived objects, object speed, and object type. Radar transmission on/off, coexistence, grid opacity, zone opacity, color scheme, trail lifetime, detection sensitivity, swaying object filter, small object filter<sup>BETA</sup>, stationary rotating object filter<sup>BETA</sup>, reference map calibration with options to scale, pan, and zoom map

## System on chip (SoC)

### Model

ARTPEC-7

### Memory

1024 MB RAM, 512 MB Flash

## Video

### Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles  
H.265 (MPEG-H Part 2/HEVC) Main Profile  
Motion JPEG

1. Mounting at another height affects the detection range. For more information, go to [axis.com](http://axis.com)  
2. Minimum distance between moving objects.

## Resolution

1920x1080 HDTV 1080p to 640x360

---

## Frame rate

Up to 10 fps in all resolutions

---

## Video streaming

Multiple, individually configurable streams in H.264, H.265 and Motion JPEG  
Controllable frame rate and bandwidth  
VBR/ABR/MBR H.264/H.265

---

## Image settings

Compression, rotation: 0°, 90°, 180°, 270° including corridor format, dynamic text and image overlay

---

## Audio

### Streaming

Audio output via edge-to-edge technology

---

### Input/output

Speaker pairing

---

## Network

### Network protocols

IPv4/v6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS<sup>3</sup>, TLS<sup>3</sup>, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP<sup>TM</sup>, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, PTP, NTS, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

---

## System integration

### Application Programming Interface

Open API for software integration, including VAPIX<sup>®</sup> and AXIS Camera Application Platform; specifications at [axis.com](http://axis.com)

One-click cloud connection

ONVIF<sup>®</sup> Profile G, ONVIF<sup>®</sup> Profile S, ONVIF<sup>®</sup> Profile T, and ONVIF<sup>®</sup> Profile M specification at [onvif.org](http://onvif.org)

---

### Video management systems

Compatible with AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at [axis.com/vms](http://axis.com/vms).

---

## Edge-to-edge

Speaker pairing  
PTZ camera pairing

---

## Analytics

Radar motion detection (detect, track, and classify objects), Radar autotracking  
Support for AXIS Camera Application Platform enabling installation of third-party applications, see [axis.com/acap](http://axis.com/acap)

---

## Event conditions

Application

Device status: above/below/within operating temperature, casing open, fan failure, IP address blocked, IP address removed, live stream active, network lost, new IP address, system ready, radar data failure; interference, no data, tampering

Edge storage: recording ongoing, storage disruption, storage health issues detected

I/O: digital input, manual trigger, virtual input

MQTT: stateless

Radar motion detection

Scheduled and recurring: schedule

---

## Event actions

I/O: toggle I/O once, toggle I/O while the rule is active  
LEDs: flash status LED, flash status LED while the rule is active

MQTT: publish

Notification: HTTP, HTTPS, TCP and email

Overlay text

Radar: radar autotracking, radar detection

Recordings: SD card and network share

Security: erase configuration

SNMP traps: send, send while the rule is active

Images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email

---

## Data streaming

Event data

Analytics data with object GPS<sup>4</sup> position and velocity

---

## Built-in installation aids

Reference map calibration, sensor for tilt angle, GPS position<sup>5</sup>

---

3. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

4. Enter the radar's GPS position manually to get object GPS position in the data stream.

5. Enter the radar's GPS position manually to get the objects' GPS position in the data stream.

## Approvals

### EMC

EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, EAC

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KC KN32 Class A

USA: FCC Part 15 Subpart B Class A

### Safety

IEC/EN/UL 62368-1, IEC/EN/UL 60950-22

### Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK08, NEMA 250 Type 4X

### Network

NIST SP500-267

### Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS 140, EN 18031-1

### Wireless

EN 300440, EN 301489-1, EN 301489-51, EN 62311, FCC Part 15 Subpart C

## Cybersecurity

### Edge security

**Software:** Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection

### Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)<sup>6</sup>, IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS<sup>6</sup>, TLS v1.2/v1.3<sup>6</sup>, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

## Documentation

*AXIS OS Hardening Guide*

*Axis Vulnerability Management Policy*

*Axis Security Development Model*

AXIS OS Software Bill of Material (SBOM)

To download documents, go to [axis.com/support/cybersecurity/resources](https://axis.com/support/cybersecurity/resources)

To read more about Axis cybersecurity support, go to [axis.com/cybersecurity](https://axis.com/cybersecurity)

## General

### Casing

IP66-, NEMA 4X- and IK08-rated

Aluminum and plastic casing

Color: White NCS S 1002-B

### Sustainability

PVC free

### Power

Power over Ethernet (PoE) IEEE 802.3at, Type 2 Class 4, typical 11 W, max 15 W

**For PoE output:** Power over Ethernet (PoE)

IEEE 802.3bt, Type 3 Class 5, or Axis 60 W midspans, max 38 W. The radar provides Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4 (30 W) to a second device.

8–28 V DC, typical 10 W, max 15 W

### Connectors

DC input

RJ45 1000BASE-T PoE

RJ45 1000BASE-T PoE output to power an external PoE device

Relay: 2-pin terminal block

I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs

### Relays

1x 1 form A, 1 NO, max 5A, 24 V DC

Expected lifetime 25,000 operations

### Storage

Support for microSD/microSDHC/microSDXC card

Support for SD card encryption (AES-XTS-Plain64 256bit)

Recording to network-attached storage (NAS)

For SD card and NAS recommendations see [axis.com](https://axis.com)

### Operating conditions

-40 °C to 60 °C (-40 °F to 140 °F)

Humidity 10–100% RH (condensing)

6. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](https://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

## Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

---

## Dimensions

285 x 206 x 152 mm (11.2 x 8.1 x 6.0 in)

---

## Weight

2.4 kg (5.3 lb)

---

## Included accessories

Installation guide, connector kit, pipe adapters, cable gland, cable gaskets, Windows® decoder 1-user license

---

## Optional accessories

AXIS T91R61 Wall Mount

AXIS T91B47 Pole Mount

AXIS T94R01B Corner Bracket

AXIS T8415 Wireless Installation Tool

For more accessories, see [axis.com](http://axis.com)

---

## Applications

Radar motion detection (detect, track, and classify objects)

AXIS Speed Monitor

AXIS Radar Integration for Microbus

Support for AXIS Camera Application Platform enabling installation of third-party applications, see [axis.com/acap](http://axis.com/acap)

---

## Supporting software

AXIS Radar Autotracking for PTZ (Slew to Cue)

For supported cameras, see [axis.com/products/axis-radar-autotracking](http://axis.com/products/axis-radar-autotracking)

---

## Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

---

## Warranty

5-year warranty, see [axis.com/warranty](http://axis.com/warranty)