

AXIS F1035-E Sensor Unit

Fisheye lens for wide area surveillance indoors or outdoors

AXIS F1035-E is ideal for highly discreet, wide area coverage in indoor, outdoor and in-vehicle surveillance applications, such as in buses and trams. For use with an AXIS F Main Unit, AXIS F1035-E provides a 1080p resolution and a fisheye lens with a 194° horizontal field of view. The unit also supports Wide Dynamic Range (WDR) – Forensic Capture, ideal for scenes with very bright and dark areas. The rugged AXIS F1035-E withstands dust, rain, snow, vibration, shock and impact. It comes with a 3- or 12-m (10/39 ft.) pre-mounted cable for connection to a main unit. A vari-angle mounting bracket is included.

- > **Flexible, rugged design for indoor, outdoor and mobile use**
- > **Fisheye lens with 1080p resolution**
- > **Ultra-wide 194° horizontal field of view**
- > **WDR – Forensic Capture (with AXIS F41 /F44 Main Unit)**



AXIS F1035-E Sensor Unit

Variants

AXIS F1035-E 3 m / 10 ft. cable: Fisheye, IP66/IP67-rated

AXIS F1035-E 12 m / 39 ft. cable: Fisheye, IP66/IP67-rated

Camera

Image sensor

1/2.8" (effective) progressive scan RGB CMOS

Lens

Fixed iris

1.3 mm, F2.8

With AXIS F34/F41/F44 in 1080p:

Horizontal angle of view: 194°

Vertical angle of view: 113°

With AXIS F34/F44 in 720p:

Horizontal angle of view: 112°

Vertical angle of view: 66°

Resolution

Max. 1920x1200/1080

WDR

WDR – Forensic Capture

With AXIS F41: 1080p, 25/30 fps (50/60 Hz)

With AXIS F44: 720p, 12.5/15 fps (50/60 Hz)

Minimum illumination

Color: 0.3 lux

Shutter speed

With AXIS F34/F44:

HDTV 720p 25/30 fps: 1/28000 s to 2 s

1080p 12.5/15 fps: 1/22500 s to 2 s

With AXIS F41:

HDTV 1080p 25/30/50/60 fps: 1/143000 s to 2 s

WUXGA (1920x1200) 25/30 fps: 1/143000 s to 2 s

Frame rate

Max. 50/60 fps (50/60 Hz)

General

Casing

IP66-, IP67-rated, Aluminum

Operating conditions

-30 °C to 55 °C (-22 °F to 131 °F)

Humidity 10-100% RH (condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Approvals

EMC

ECE R10 rev.04, EN 50121-4, IEC 62236-4, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24

Safety

IEC/EN/UL 60950-1

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-60, IEC 60068-2-78, IEC 60529 IP4X, IEC 60529 IP66/IP67, IEC 60721-3-5 5M3 (vibration, shock), IEC/EN/UL 60950-22, NEMA 250 Type 4X, EN 50581

Dimensions

62 mm (2 7/16 in) ø 30 mm (1 3/16 in)

Weight

3 m / 10 ft. cable: 96 g (0.21 lb)

12 m / 39 ft. cable: 346 g (0.76 lb)

Required hardware

AXIS F34/F41/F44 Main Unit

Included accessories

Installation guide, AXIS F8201 Var-angle Mounting Bracket

Optional accessories

AXIS F8203 Fixed Mount Bracket, AXIS F8204 Mounting Band, AXIS F8212 Trim Ring, AXIS F8235 Fisheye Accessory

Warranty

5-year warranty, see axis.com/warranty